

D400E

**Superior Performance
and Outstanding Style**



CLEVO[®]

Broadband Mobile Wireless infotainment

D400E Specification



CLEVO®

Model	D400E
CPU	<ul style="list-style-type: none"> ■ Intel Pentium 4 Processor, Northwood, 2.0/2.2/2.26/2.4/2.5/2.53/2.6/2.66/2.8GHz ■ Intel Pentium 4 Processor, Northwood, 3.06GHz(0.13u core with H.T. Technology) ■ Intel Celeron Processor, 1.7/1.8/2.0/2.1/2.2GHz(0.18u) ■ Intel Pentium 4 (Portability), 2.4/2.66/2.8/3.06GHz (u0.13) ■ uFC-PGA 478 Package
Core Logic	<ul style="list-style-type: none"> ■ SiS M645DX+962 chipset
Display	<ul style="list-style-type: none"> ■ 14.1"XGA/15.0"XGA and 15.0"SXGA+ TFT
Memory (RAM)	<ul style="list-style-type: none"> ■ 2x 200-pin DDR SODIMM sockets, support DDR200/DDR266/DDR333 ■ Expandable Memory up to 1 GB, depend on 128/256/512MB SODIMM Module
Display Memory	<ul style="list-style-type: none"> ■ 64MB DDR SGRAM on board
Video Controller	<ul style="list-style-type: none"> ■ ATi Mobility Radeon 9000 high performance chip ■ Support AGP™ 4X ■ Integrated 128-bit 2D/3D Graphics Accelerator - Advanced HW Acceleration for DVD Playback ■ Fully DirectX8 with Hardware ■ Dual-view Display Monitor
Storage	<ul style="list-style-type: none"> ■ Bay one 3.5" 3-mode FDD ■ Bay two 12.7mm(h) DVD-ROM/CD-ROM/Combo drive/ CD-RW/DVD-RW changeable ■ 1x Changeable 2.5" 9.5 mm/12.7mm(h) HDD ■ Support Ultra-DMA 33/66/100/133
Keyboard	<ul style="list-style-type: none"> ■ Win key, Multi-language ■ Built-in 3 instant keys, www, email, and applications.
PCMCIA	<ul style="list-style-type: none"> ■ One PCMCIA 3.3V/5V sockets, one typeII ■ Support Cardbus
Sound System	<ul style="list-style-type: none"> ■ AC'97 2.1 Compliant Interface ■ 3D stereo enhanced sound system ■ Compatible Sound-Blaster PRO™ ■ S/PDIF Digital output(5.1CH) ■ Built-in 2 speakers ■ Built-in Microphone
I/O Ports	<ul style="list-style-type: none"> ■ 1x PS/2 port support Mouse and Keyboard Port/ 1x Parallel Port(LPT1),support ECP/EPP ■ 3x USB 2.0/1.1 ports/ Infrared file transfer, IrDA 1.1 FIR/SIR/ASKIR/ 1xRJ45 for LAN ■ 1x RJ11 jack for MDC modem/ DC-in jack/ 1xmini-IEEE 1394 port/ External CRT monitor ■ 1x Jack for microphone/ 1x Jack for headphone/ 1x S-Video jack for TV output/1xserial port/ 1x wireless device on/off switch
Communication	<ul style="list-style-type: none"> ■ Infrared transfer: 115.2K bps SIR/4M bps FIR, 1cm~1M operating distance, IrDA 1.1 compliant ■ 10/100Mb Ethernet LAN built-in ■ 802.11b Wireless LAN (Option) ■ Bluetooth module (Option) ■ Video Camera module (Option) ■ 56K MDC modem with V.90& V.92 compliant
Power Management	<ul style="list-style-type: none"> ■ Full Range AC Adapter - AC in 100~240V, 56~60Hz DC Output 20V, 6.0A ■ Support Smart Li-Ion Battery ■ Support ACPI v.10b ■ Support suspend to RAM ■ Support suspend to disk, battery low suspend and modem resume from system suspend
Security	<ul style="list-style-type: none"> ■ Kensington® Lock
Dimension	<ul style="list-style-type: none"> ■ 329(W) x 275(D) x 36.5(H) mm ■ 3.3Kg, with Lithium-Ion battery
Options	<ul style="list-style-type: none"> ■ DVD-ROM driver module ■ CD-RW driver module ■ Combo driver module ■ Software DVD Player ■ Wireless LAN module ■ Bluetooth model ■ Video Camera ■ DVD-RW driver module