Everywhere, Any time with your D400K!

Break through the time & space limitations!

People travel from time to time!

You can't be at your family's award presentation in New York because you

had a Sales meeting in Shanghai the other day! Clevo's **D400K** combines

the powerful AMD CPU, 15" TFT LCD, Video Camera, and polular communications

such as Gigabit Ethernet and WLAN.

Your family will be able to feel your cares at all times!

CLEVO®

D400K Specification

Model	D400K
CPU	. AMD Athlon™ 64 (DTR) 3000+/3200+/3400+/3700+ (130nm, 1 MB L2 cache, uPGA478) . AMD Mobile Athlon™ 64 (62W) 2800+/3000+/3200+/3400+/3700+ (130nm, 1 MB L2 cache, uPGA478)
Core Logic	. VIA K8T800 + VT8235CE
Display	. 15.0" XGA (1024x768) TFT / 15.0" SXGA+ (1400x1050) TFT
Memory	. 64-bit DDR data channel . Two 200-pin SODIMM sockets, supporting DDR266/333/400 . Expandable Memory up to 2GB, based on 128/256/512/1024MB SODIMM Module
Video Controller	. ATi Mobility Radeon 9700 High performance graphic chip . 64MB DDR Video RAM on board . 128 bit graphic engine . UtraAGP 8X . Fully DirectX® 9.0 support
Storage	. One changeable 2.5" 12.7mm(H) HDD . One changeable 9.5mm(H) CD-ROM / DVD-ROM / Combo / DVD-Dual Drive . Supporting Master mode IDE , supporting PIO mode 4/ATA-33/66/100/133 (Ultra DMA)
Keyboard	. A4 size keyboard, Multi-Language support . Built-in Touchpad with scrolling function
Sound System	. AC'97 2.2 Compliant Interface . 3D stereo enhanced sound system . Virtual 6-channel audio output . Sound-Blaster PRO™ Compatible . S/PDIF Digital output (5.1 CH) . 1x Built-in Microphone . 2x Built-in Speakers
I/O Ports	. 3x USB 2.0 ports . 1x Mini IEEE1394a port . 1x S-Video jack for TV output . 1x Serial port . 1x Parallet port (LPT1), supporting ECP/EPP . 1x Infrared Transfer port . 1x External CRT monitor output . 1x PS/2 port . 1x Headphone jack . 1x Microphone jack . 1x S/PDIF output jack . 1x RJ-45 port for LAN . 1x RJ-11 port for Modem . 1x DC-In jack . Embedded 4-in-1 Card Reader (MS/MS Pro/SD/MMC)
Card Reader	. 1x Type II PCMCIA socket
PCMCIA	. Infrared Transfer : 115.2Kbps SIR/4Mbps FIR, IrDA 1.1 compliant
Communication	. 10/100/1000BASE-TX Fast Ethernet on board . (Option) 802.11b MiniPCI Wireless LAN . (Option) 802.11g MiniPCI Wireless LAN . (Option) 802.11b+g MiniPCI Wireless LAN . Integrated V.90/56K MDC Modem (V.92 compliant) . (Option) Bluetooth 1.1, MDC Interface, combo with MDC modem . (Factory Option) 300K-pixel Video Camera module
Power	. Full Range 120W AC adapter - AC input 100~240V, 50~60Hz, DC output 20V, 6A . Chageable Standard 8-cell Smart Li-ion battery pack, 4400mAh
Security	. Kensington® Lock
Dimension	. 329(W) x 275(D) x 36.5(H)mm, 13.0"(W) x 10.8"(D) x 1.4"(H) . 3.5Kg with 8 cells Lithium-ion battery
Options	. One changeable 9.5mm(H) CD-ROM / DVD-ROM / Combo / DVD-Dual Drive . Software DVD Player . 802.11b MiniPCI Wireless LAN . 802.11g MiniPCI Wireless LAN . 802.11b+g MiniPCI Wireless LAN . Bluetooth 1.1, MDC Interface, combo with MDC modem . (Factory Option) 300K-pixel Video Camera module