D400S
D400E

Superior Performance and Outstanding Style

CMOS Camera

intel inside
H
T
pentium 4

CLEVO ®

Broadband **M**obile **W**ireless **i**nfotainment

D400E / D400S Specification

CLEVO®

Model	D400E	D400S
CPU	. Intel® Pentium® 4 Processor 2.0~3.06GHz (0.13u, 400/533MHz FSB) . Intel® Celeron Processor 1.7~1.8GHz (0.18u, 400MHz FSB) . Intel® Celeron Processor 2.0~2.6GHz (0.13u, 400MHz FSB) . Intel® Mobile Pentium®4 Processor 2.26~3.06GHz (0.13u, 533MHz FSB) . CPU package supports uFC-PGA478 . Supporting HT Technology	. Intel® Pentium® 4 Processor 2.0 ~2.8GHz, (0.13u, 400/533MHz FSB) . Intel® Celeron Processor 1.7 ~1.8GHz (0.18u, 400MHz FSB) . Intel® Celeron Processor 2.0 ~2.8GHz (0.13u, 400MHz FSB) . CPU package supports uFC-PGA478
Core Logic	. SiS M645DX	. SiS M650
Display	. 14.1" XGA / 15.0" XGA / 15.0" SXGA+ TFT	
Memory (RAM)	. 2x 200-pin SODIMM sockets, supporting DDR200/266/333 . Expandable Memory up to 1024MB, based on 128/256/512MB SODIMM Module	. 2x 200-pin SODIMM sockets, supporting DDR200/266 . Expandable Memory up to 1024MB, based on 128/256/512MB SODIMM Module
Video Controller	. ATi Mobility Radeon 9000 high performance chip . Supporting AGP™ 4X / Supporting SXGA+ resolution . Integrated 128-bit 2D/3D Graphics Accelerator . External Memory up to 64MB DDR SGRAM on board . Dual-view Display Monitor	. High performance 256-bit 3D engine . Supporting SXGA+ Resolution
Storage	. 3.5" 3-mode FDD . Changeable CD-ROM / DVD-ROM / CD-RW / Combo / DVD-RW Drive 12.7mm(H) . Changeable 2.5" HDD 9.5/12.7mm(H) . Supporting Master IDE mode, supporting IDE mode 4/ATA- 33/66/100/133 (Ultra DMA)	
Keyboard	. Compliant with Win Keyboard, Multi-Language . Built-in Touchpad with scrolling function	
Sound System	. AC'97 2.1 Compliant . 3D stereo enhanced sound system . Sound-Blaster PRO™ compatible . S/PDIF Digital output . 2x Built-in Speakers / 1x Built-in Microphone	
I/O Ports	. 3x USB 2.0/1.1 ports / 1x Mini IEEE1394 port . 1x S-Video jack for TV output . 1x Serial port / 1x Parallel port (LPT1), supporting ECP/EPP . 1x External CRT monitor port / 1x PS/2 port . 1x Headphone jack / 1x Microphone jack / 1x Internal Microphone jack . 1x RJ-45 for LAN / 1x RJ-11 for MDC Modem / 1x Wireless device on/off switch . 1x S/PDIF jack / 1x DC-In jack . Infrared File Transfer, IrDA 1.1 FIR/SIR/ASKIR . 3x Built-in instant keys: www, E-mail and Applications Keys	
PCMCIA	. 1x Type II 3.3V/5V PCMCIA socket, supporting CardBus	
Communication	. Infrared Transfer : 115.2Kbps SIR/4Mbps FIR, 1cm~1M operating distance . Built in 10/100Mb Ethernet . 802.11b Wireless LAN (factory option) / Bluetooth Module (factory option) . Video Camera Module (factory option) . 56K MDC Modem with V.90/V.92 compliant	
Power Management	. Full Range AC adapter - AC input 100~240V, 50~60Hz, DC Output 20V, 6A . Standard Smart Lithium-ion battery (8 cells)	. Full Range AC adapter - AC input 100~240V, 50~60Hz, DC Output 20V, 5A . Standard Smart Lithium-ion battery (8 cells)
Security	. Kensington® Lock	
Dimension	. 329(W) x 275(D) x 36.5(H)mm, 13.0"(W) x 10.8"(D) x 1.4"(H) . 3.1Kg with 8 cells Lithium-ion battery	
Options	. CD-ROM / DVD-ROM / CD-RW / Combo / DVD-RW Drive . Software DVD Player . Bluetooth (factory option) . 802.11b Wireless LAN (factory option) . Video Camera Module (factory option)	

2003/11 Version