


D400S
D400E
D400H

Superior Performance and Outstanding Style



CLEVO[®]

Broadband Mobile Wireless infotainment

D400S/D400E/D400H Specification

Model	D400S	D400E	D400H	
CPU	<ul style="list-style-type: none"> Intel Pentium 4, Northwood 2.0~2.8GHz(u0.13) Intel Celeron 1.7/1.8GHz uFC-PGA 478 Package 	<ul style="list-style-type: none"> Intel Pentium 4, Northwood 2.0~2.8GHz Intel Pentium 4, Northwood 3.06GHz(with H.T. Technology) Intel Celeron 1.7~2.2GHz(0.18u) Intel mobile Pentium 4 (portability), 2.4/2.66/2.8/3.06GHz uFC-PGA 478 Package 	<ul style="list-style-type: none"> Intel Pentium 4, Northwood 2.0~2.8GHz(u0.13) Intel Celeron 1.7~2.2GHz(0.18u) uFC-PGA 478 Package 	
Core Logic	. SIS M650+SIS962	. SIS M645DX+962 chipset	. SIS M650+962	
Display	. 14.1"XGA/15.0"XGA/15.0"SXGA+ TFT	. 14.1"XGA/15.0"XGA/15.0"SXGA+ TFT	. 14.1"XGA/15.0"XGA/15.0"SXGA+ TFT	
Memory (RAM)	<ul style="list-style-type: none"> Expandable memory up to 1GB, depend on 128/256/512MB SODIMM Module 2x200pin SO-DIMM sockets, support DDR200/266 	<ul style="list-style-type: none"> Expandable memory up to 1GB, depend on 128/256/512MB SODIMM Module 2x200pin SO-DIMM sockets, support DDR200/266/333 	<ul style="list-style-type: none"> Expandable memory up to 512MB, depend on 128/256/512MB SODIMM Module 1x200pin SO-DIMM sockets, support DDR200/266 	
Display Memory	. Share Memory Architecture(SMA)	. 64MB DDR SGRAM on board	. Share Memory Architecture(SMA)	
Video Controller	<ul style="list-style-type: none"> High performance 256-bit 3D engine -Advanced HW Acceleration for DVD Playback -Fully DirectX8 Compliant Graphics Engine Support SXGA+ resolution up to 1400x1050 	<ul style="list-style-type: none"> ATI Mobility Radeon 9000 high performance chip Support AGP 4X Integrated 128-bit 2D/3D Graphics Accelerator -Advanced HW Acceleration for DVD Playback -Fully DirectX8 with Hardware Dual-view Display Monitor Support SXGA+ resolution up to 1400x1050 	<ul style="list-style-type: none"> High performance 256-bit 3D engine -Advanced HW Acceleration for DVD Playback -Fully DirectX8 Compliant Graphics Engine Support SXGA+ resolution up to 1400x1050 	
Storage	<ul style="list-style-type: none"> 3.5" 3-mode FDD 2.5" 9.5mm/12.7mm(h)HDD Changeable DVD-ROM/CD-ROM/CD-RW/Combo Support Ultra DMA 33/66/100/133 	<ul style="list-style-type: none"> 3.5" 3-mode FDD Changeable 12.7mm(h) DVD-ROM/CD-ROM/Combo drive/CD-RW/DVD-RW Easy changeable 2.5" 9.5/12.7mm(h) HDD Support Ultra DMA 33/66/100/133 	<ul style="list-style-type: none"> Changeable 12.7mm(h) DVD-RW/CD-RW/Combo drive/CD-RW Changeable 2.5" 9.5/12.7mm (h) HDD Support Ultra DMA 33/66/100/133 	
Keyboard	<ul style="list-style-type: none"> Winkey, Multi-Language Built in 3 Instant keys, www,email, and applications Built in touch pad (scroll functionality included) 			
PCMCIA	<ul style="list-style-type: none"> One PCMCIA 3.3V/5V sockets, one type II Support CardBus 			
Sound System	<ul style="list-style-type: none"> AC'97 2.1 Compliant Interface 3D stereo enhanced sound system Compatible Sound-Blaster PRO S/PDIF Digital output (5.1CH) microphone and 2 speakers 			
I/O Ports	USB 2.0/1.1	3	3	3
	IEEE1394	1(mini)	1 (mini)	
	S-Video jack	1	1	1
	Serial port	1	1	1
	Parallel port	1, support ECP/EPP	1, support ECP/EPP	1, support ECP/EPP
	IrDA	IrDA 1.1 FIR/SIR/ASKIR	IrDA 1.1 FIR/SIR/ASKIR	
	CRT monitor	External CRT monitor	External CRT monitor	External CRT monitor
	PS/2	1	1	1
	Headphone jack	1	1	1
	Microphone jack	1	1	1
	RJ-11	1	1	1
	RJ-45	1	1	1
	S/PDIF	1	1	1
DC-in	1	1	1	
wireless device on/off switch	1	1	1	
Communication	<ul style="list-style-type: none"> 10/100Mb Ethernet LAN 802.11b wireless LAN (Option) Bluetooth module (Option) Video camera module (Option) 56K v.90/v.92 modem Infrared transfer: IrDA1.1, FIR/SIR 	<ul style="list-style-type: none"> 10/100Mb Ethernet LAN 802.11b wireless LAN (Option) Bluetooth module (Option) Video camera module (Option) 56K v.90/v.92 modem Infrared transfer: IrDA1.1, FIR/SIR 	<ul style="list-style-type: none"> 10/100Mb Ethernet LAN 802.11b wireless LAN (Option) Bluetooth module (Option) Video camera module (Option) 56K v.90/v.92 modem 	
Power Management	<ul style="list-style-type: none"> Full Range AC adapter- AC Input 100-240V, 50~60Hz, 4.5A Changeable smart Li-Ion battery 	<ul style="list-style-type: none"> Full Range AC adapter- AC Input 100-240V, 50~60Hz, 6A Changeable smart Li-Ion battery 	<ul style="list-style-type: none"> Full Range AC adapter- AC Input 100-240V, 50~60Hz, 4.5A Changeable smart Li-Ion battery 	
Security	. Kensington [®] Lock			
Dimension	. 329(W)x275(D)x36.5(H)mm, 3.3kg with battery			
optional	<ul style="list-style-type: none"> DVD-ROM driver module CD-RW driver module Combo driver module Software DVD player Wireless LAN module Bluetooth module Video Camera module DVD-RW driver module 			