

D410P
D410V



Everywhere, Any time with your D410P/D410V!

Break through the time & space limitations!

People travel from time to time!

You can't be at your partner's award presentation in New York because you have a Sales meeting in Shanghai the day before! Clevo's **D410P** and **D410V** combine the powerful Pentium 4 3.2GHz with HT Technology(FSB800) CPU (for D410V), sharp 15" TFT LCD, Video Camera, ATi Mobility Radeo 9600 PRO (for D410V), and popular communications like Bluetooth, Wireless LAN, and Gigabit Ethernet (for D410V).

Your partner will be able to feel your cares at all times!



CLEVO[®]

Broadband Mobile Wireless infotainment

Intel, the Intel Inside logo, Pentium, and Intel Pentium 4 Processor are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

D410P / D410V Specification



CLEVO®

Model	D410P	D410V
CPU	<ul style="list-style-type: none"> Intel® Pentium® 4 Processor 2.0/2.2/2.4/2.6GHz (400MHz FSB, 0.13u) Intel® Pentium® 4 Processor 2.26/2.53/2.66/2.8GHz (533MHz FSB, 0.13u) Intel® Pentium® 4 Processor 2.66/2.8/3.06GHz with HT Technology (533MHz FSB, 0.13u) Intel® Desktop Celeron Processor 1.7/1.8GHz (400MHz FSB, 0.18u) Intel® Desktop Celeron Processor 2.0/2.2GHz (400MHz FSB, 0.13u) Intel® Mobile Pentium® 4 (Portability) Processor, 2.66/2.8/3.06GHz with HT Technology (533MHz FSB) Intel® Mobile Pentium® 4 (Portability) Processor, 2.66/2.8/3.06GHz (533MHz FSB) CPU package supports uFC-PGA478 	<ul style="list-style-type: none"> Intel® Pentium® 4 Processor 3.06GHz with HT Technology(0.13u, 533MHz FSB) Intel® Pentium® 4 Processor 2.26/2.53/2.66/2.8/3.06GHz (0.13u, 533MHz FSB) Intel® Pentium® 4 Processor 2.6/2.8/3.0/3.2GHz with HT Technology (0.13u, 800MHz FSB) Intel® Mobile Pentium® 4 (Portability) Processor 2.66/2.8/3.06GHz with HT Technology(0.13u,533MHz FSB) Intel® Mobile Pentium® 4 (Portability) Processor 2.26/2.4/2.66/2.8/3.06GHz (0.13u,533MHz FSB) CPU package supports uFC-PGA478
Core Logic	SiS M650	SiS 648FX
Display	14.1" XGA / 15.0" XGA / 15.0" SXGA+ TFT	15.0" XGA / 15.0" SXGA+ TFT
Memory (RAM)	<ul style="list-style-type: none"> 2x 200-pin SODIMM sockets, supporting DDR200/266/333 Expandable Memory up to 1GB, based on 128/256/512MB SODIMM Module 	<ul style="list-style-type: none"> 2x 200-pin SODIMM sockets, supporting DDR333/400 Expandable Memory up to 1GB, based on 128/256/512MB SODIMM Module
Video Controller	<ul style="list-style-type: none"> High performance 256-bit 3D engine Dual-view Display Monitor Supporting SXGA+ resolution up to 1400x1050 	<ul style="list-style-type: none"> ATi Mobility Radeon 9600 PRO high performance chip Supporting AGP™ / Supporting SXGA+ resolution Integrated 128-bit 2D/3D Graphics Accelerator External Memory up to 128MB DDR SGRAM on board Dual-view Display Monitor
Storage	<ul style="list-style-type: none"> Bay 1: 3.5" 3-mode FDD Bay 2: changeable CD-ROM / DVD-ROM / CD-RW / Combo Drive 12.7mm(H) Changeable 2.5" HDD 9.5/12.7mm(H) Supporting Master IDE mode, supporting PIO mode 4/ATA- 33/66/100/133 (Ultra DMA) 	<ul style="list-style-type: none"> Fixed 6-in-1 Card Reader Changeable CD-ROM / DVD-ROM / CD-RW / Combo / DVD-RW Drive 12.7mm(H) Changeable 2.5" HDD 9.5/12.7mm(H) Supporting Master IDE mode, supporting PIO mode 4/ATA- 33/66/100/133 (Ultra DMA)
Keyboard	<ul style="list-style-type: none"> Compliant with Win Keyboard, Multi-Language Built-in Touchpad with scrolling function 	
Sound System	<ul style="list-style-type: none"> AC'97 2.1 Compliant 3D stereo enhanced sound system Sound-Blaster PRO™ compatible S/PDIF Digital output (5.1CH) 2x Built-in Speakers / 1x Built-in Microphone 	
I/O Ports	<ul style="list-style-type: none"> 3x USB 2.0/1.1 ports / 1x Mini IEEE1394 port 1x S-Video jack for TV output 1x Serial port / 1x Parallel port (LPT1), supporting ECP/EPP 1x External CRT monitor port / 1x PS/2 port 1x Headphone jack / 1x Microphone jack / 1x Internal Microphone jack 1x RJ-45 for LAN / 1x RJ-11 for MDC Modem / 1x Wireless device on/off switch 1x S/PDIF jack / 1x DC-In jack Infrared File Transfer, IrDA 1.1 FIR/SIR/ASKIR, 1cm~1M operating distance 3x Built-in instant keys: www, E-mail and Applications Keys 	<ul style="list-style-type: none"> 2x USB 2.0/1.1 ports / 1x Mini IEEE1394 port 1x S-Video jack for TV output 1x Serial port / 1x Parallel port (LPT1), supporting ECP/EPP 1x External CRT monitor port / 1x PS/2 port 1x Headphone jack / 1x Microphone jack / 1x Internal Microphone jack 1x RJ-45 for LAN / 1x RJ-11 for MDC Modem 1x S/PDIF jack / 1x DC-In jack / 1x Wireless device on/off switch Infrared File Transfer, IrDA 1.1 FIR/SIR/ASKIR 3x Built-in instant keys: www, E-mail and Applications Keys
PCMCIA	<ul style="list-style-type: none"> 1x Type II 3.3V/5V PCMCIA socket, supporting CardBus 	
Communication	<ul style="list-style-type: none"> Infrared Transfer : 115.2Kbps SIR/4Mbps FIR, 1cm~1M operating distance Built in 10/100Mb Ethernet 802.11b Wireless LAN (factory option) / Bluetooth Module (factory option) Video Camera Module (factory option) 56K MDC Modem with V.90/V.92 compliant 	<ul style="list-style-type: none"> Infrared Transfer : 115.2Kbps SIR/4Mbps FIR, 1cm~1M operating distance Built in Gigabit Ethernet 802.11b Wireless LAN (factory option) / Bluetooth Module (factory option) Video Camera Module (factory option) 56K MDC Modem with V.90/V.92 compliant
Power Management	<ul style="list-style-type: none"> Full Range AC adapter - AC input 100~240V, 50~60Hz, DC Output 20V, 6A Standard Smart Lithium-ion battery (8 cells) 	
Security	<ul style="list-style-type: none"> Kensington® Lock 	
Dimension	<ul style="list-style-type: none"> 329(W) x 275(D) x 36.5(H)mm, 13.0"(W) x 10.8"(D) x 1.4"(H) 3.1Kg with 8 cells Lithium-ion battery 	
Options	<ul style="list-style-type: none"> CD-ROM / DVD-ROM / CD-RW / Combo / DVD-RW Drive Software DVD Player Bluetooth (factory option) 802.11b Wireless LAN (factory option) Video Camera Module (factory option) 	

2003/12 Version