

D41ES



Everywhere, Any time with your D41ES!

Break through the time & space limitations!

People travel from time to time!

You can't be at your partner's award presentation in New York because you

had a Sales meeting in Shanghai the other day! Clevo's **D41ES**

combine the powerful Pentium 4 CPU, 15" TFT LCD, Video Camera,

and popular communications like Bluetooth, Wireless LAN, and Ethernet .

Your partner will be able to feel your cares at all times!



CLEVO®

D41ES Specification



CLEVO®

Model	D41ES
CPU	- Intel® Pentium® 4 Processor 2.26/2.40/2.53/2.66/2.80GHz (130nm, FSB533, 512 KB L2 cache, mPGA478) - Intel® Celeron® D Processor 2.00/2.20/2.40/2.60/2.80GHz (130nm, FSB533, 128 KB L2 cache, mPGA478) - Intel® Celeron® D Processor 320/325/330/335(2.40~2.80GHz, 90nm, FSB533, 256 KB L2 cache, mPGA478)
Core Logic	SIS M650 + 962
Display	14.1" XGA TFT (1024x768) / 15.0" XGA TFT (1024x768) / 15.0" SXGA+ TFT (1400x1050)
Memory	64-bit wide DDR data channel - Two 200-pin SODIMM sockets, supporting DDR266/333 - Expandable Memory up to 1024MB, based on 128/256/512MB SODIMM Module
Video Controller	- SIS M650 integration - Shared Memory Architecture with 16/32/64MB 128 bit graphic engine - Ultra AGP 4X - Fully DirectX 8.1 support
Storage	- One Fixed 3.5" FDD - One changeable 2.5" 9.5/12.7mm(H) HDD Drive - One changeable 12.7mm(H) CD-ROM / DVD-ROM / Combo / DVD-Dual Drive - Supporting Master IDE mode ATA- 33/66/100/133 (Ultra DMA)
Keyboard	- A4 size keyboard, Multi-Language support - Built-in Touchpad with scrolling function
Sound System	- AC'97 2.2 Compliant Interface 3D stereo enhanced sound system - Sound-Blaster PRO™ compatible - S/PDIF Digital output (5.1 CH) 1x Built-in Microphone 2x Built-in Speakers
I/O Ports	3x USB 2.0 ports 1x Mini IEEE1394a port 1x S-Video jack for TV output 1x Serial port 1x Parallel port (LPT1), supporting ECP/EPP 1x Infrared File Transfer port 1x External CRT monitor port 1x PS/2 port 1x Headphone jack 1x Microphone jack 1x S/PDIF jack 1x RJ-45 port for LAN 1x RJ-11 port for Modem 1x DC-In jack
PCMCIA	1x Type II PCMCIA socket
Communication	- Infrared File Transfer : 115.2Kbps SIR/4Mbps FIR, IrDA 1.1 compliant 10/100BASE-TX Fast Ethernet on board - Integrated V.90/56K MDC Modem (V.92 compliant) (Option) 802.11b Wireless LAN module, USB interface (Option) Bluetooth 1.1 Module, USB interface (Factory option) 300K-pixel Video Camera module
Power	- Full Range 100W AC adapter - AC input 100~240V, 50~60Hz, DC output 20V, 6A - Changeable 8-cell Smart Li-ion battery pack, 4400mAh
Security	Kensington® Lock
Dimension	329(W) x 275(D) x 36.5(H)mm, 13.0"(W) x 10.8"(D) x 1.4"(H) 3.1Kg with 8 cells Lithium-ion battery
Options	- One changeable 12.7mm(H) CD-ROM / DVD-ROM / Combo / DVD-Dual Drive - Software DVD Player 802.11b Wireless LAN module, USB interface - Bluetooth 1.1 Module, USB interface (Factory option) 300K-pixel Video Camera module

2004/09 Version