

D43ES



Everywhere, Any time with your D43ES!

Break through the time & space limitations!

People travel from time to time!

You can't be at your partner's award presentation in New York because you

had a Sales meeting in Shanghai the other day! Clevo's **D43ES**

combine the powerful Pentium 4 CPU, 15" TFT LCD, Video Camera,

and popular communications like Bluetooth, Wireless LAN, and Ethernet .

Your partner will be able to feel your cares at all times!



CLEVO[®]

D43ES Specification



CLEVO[®]

Model

D43ES

CPU

- . Intel[®] Pentium[®] 4 Processor 2.26/2.40/2.53/2.66/2.80GHz (130nm, FSB533, 512 KB L2 cache, mPGA478)
- . Intel[®] Celeron[®] D Processor 2.00/2.20/2.40/2.60/2.80GHz (130nm, FSB533, 128 KB L2 cache, mPGA478)
- . Intel[®] Celeron[®] D Processor 320/325/330/335(2.40~2.80GHz, 90nm, FSB533, 256 KB L2 cache, mPGA478)

Core Logic

- . SIS M650 + 962

Display

- . 14.1" XGA TFT (1024x768) / 15.0" XGA TFT (1024x768) / 15.0" SXGA+ TFT (1400x1050)

Memory

- . 64-bit wide DDR data channel
- . Two 200-pin SODIMM sockets, supporting DDR266/333
- . Expandable Memory up to 1024MB, based on 128/256/512MB SODIMM Module

Video Controller

- . SIS M650 integration
- . Shared Memory Architecture with 16/32/64MB
- . 128 bit graphic engine
- . Ultra AGP 4X
- . Fully DirectX 8.1 support

Storage

- . One Fixed 3.5" FDD
- . One changeable 2.5" 9.5/12.7mm(H) HDD Drive
- . One changeable 12.7mm(H) CD-ROM / DVD-ROM / Combo / DVD-Dual Drive
- . Supporting Master IDE mode ATA- 33/66/100/133 (Ultra DMA)

Keyboard

- . A4 size keyboard, Multi-Language support
- . Built-in Touchpad with scrolling function

Sound System

- . AC'97 2.2 Compliant Interface
- . 3D stereo enhanced sound system
- . Sound-Blaster PRO[™] compatible
- . S/PDIF Digital output (5.1 CH)
- . 1x Built-in Microphone
- . 2x Built-in Speakers

I/O Ports

- . 3x USB 2.0 ports
- . 1x Mini IEEE1394a port
- . 1x S-Video jack for TV output
- . 1x Serial port
- . 1x Parallel port (LPT1), supporting ECP/EPP
- . 1x Infrared File Transfer port
- . 1x External CRT monitor port
- . 1x PS/2 port
- . 1x Headphone jack
- . 1x Microphone jack
- . 1x S/PDIF jack
- . 1x RJ-45 port for LAN
- . 1x RJ-11 port for Modem
- . 1x DC-In jack

PCMCIA

- . 1x Type II PCMCIA socket

Communication

- . Infrared File Transfer : 115.2Kbps SIR/4Mbps FIR, IrDA 1.1 compliant
- . 10/100BASE-TX Fast Ethernet on board
- . Integrated V.90/56K MDC Modem (V.92 compliant)
- . (Option) 802.11b Wireless LAN module, USB interface
- . (Option) Bluetooth 1.1 Module, USB interface
- . (Factory option) 300K-pixel Video Camera module

Power

- . Full Range 100W AC adapter - AC input 100~240V, 50~60Hz, DC output 20V, 6A
- . Changeable 8-cell Smart Li-ion battery pack, 4400mAh

Security

- . Kensington[®] Lock

Dimension

- . 329(W) x 275(D) x 36.5(H)mm, 13.0"(W) x 10.8"(D) x 1.4"(H)
- . 3.1Kg with 8 cells Lithium-ion battery

Options

- . One changeable 12.7mm(H) CD-ROM / DVD-ROM / Combo / DVD-Dual Drive
- . Software DVD Player
- . 802.11b Wireless LAN module, USB interface
- . Bluetooth 1.1 Module, USB interface
- . (Factory option) 300K-pixel Video Camera module

2004/09 Version