

D47EV

WIDEN YOUR PERSPECTIVE **BROADEN YOUR MIND**



Communcation

1000BASE-T (Gigabit) LAN on board
(10/100 BASE-T compliant)

Display

17.0" WSXGA+ TFT

CPU

Intel Pentium 4 Processor

Video Controller

ATi Mobility Radeon 9700

CLEVO[®]



D47EV Specification

Model	D47EV
CPU	- Intel® Pentium® 4 Processor 520/530/540 with HT Technology (2.80~3.20GHz, 90nm, FSB800, 1 MB L2 cache, uPGA478) - Intel® Pentium® 4 Processor with HT Technology 2.40/2.60/2.80/3.00/3.20GHz (130nm, FSB800, 512 KB L2 cache, uPGA478) - Mobile Intel® Pentium® 4 Processor with HT Technology 2.80/3.06/3.20GHz (130nm, FSB533, 512 KB L2 cache, uPGA478)
Core Logic	SIS 648FX +963
Display	17.0" WXGA (1440x900) TFT / 17.0" WSXGA+ (1680x1050) TFT
Memory	64-bit DDR data channel - Two 200-pin SODIMM sockets, supporting DDR333/400 - Expandable Memory up to 1GB, based on 128/256/512MB SODIMM Module
Video Controller	- ATi Mobility Radeon 9700 High performance graphic chip 128MB DDR Video RAM on board 128 bit graphic engine - UltraAGP 8X - Fully DirectX® 9.0 support
Storage	- One changeable 2.5" 9.5/12.7mm(H) HDD - One changeable 12.7mm(H) CD-ROM / DVD-ROM / Combo / DVD-Dual Drive - Supporting Master mode IDE , supporting PIO mode 4/ATA-33/66/100/133 (Ultra DMA)
Keyboard	- Full size keyboard, Multi-Language support - Built-in Touchpad with scrolling function
Sound System	- AC'97 2.2 Compliant Interface 3D stereo enhanced sound system - Sound-Blaster PRO™ Compatible - S/PDIF Digital output (5.1 CH) 1x Built-in Microphone 2x Built-in Speakers (Factory Option) 1x Sub woofer
I/O Ports	2x USB 2.0 ports 1x Mini IEEE1394a port 1x S-Video jack for TV output 1x Serial port 1x Parallet Port (LPT1), supporting ECP/EPP 1x Infrared Transfer port 1x External CRT monitor output 1x PS/2 port 1x Headphone jack 1x Microphone jack 1x S/PDIF output jack 1x RJ-45 port for LAN 1x RJ-11 port for Modem 1x DC-In jack 1x S-Video jack for Video input (Option with TV Tuner module) 1x Line-in jack for Audio input (Option with TV Tuner module)
Card Reader	Built-in 7-in-1 Card Reader (MS/SD/MS Pro/MMC/CF/SM/MicroDrive)
PCMCIA	1x Type II PCMCIA socket
Communication	- Infrared Transfer : 115.2Kbps SIR/4Mbps FIR, IrDA 1.1 compliant 10/100/1000BASE-TX Fast Ethernet on board - Integrated V.90/56K MDC Modem (V.92 compliant) (Option) 802.11b Wireless LAN, USB interface ** (Option) Bluetooth 1.1, USB interface (Factory Option) 300K-pixel Video Camera module
Power	- Full Range 150W AC adapter - AC input 100~240V, 50~60Hz, DC output 20V, 7.5A - Changeable Standard 8-cell Smart Li-ion battery pack, 4400mAh
Security	Kensington® Lock
Dimension	393(W) x 275(D) x 37.5(H)mm, 15.5"(W) x 10.8"(D) x 1.5"(H) 4.2Kg with 8 cells Lithium-ion battery
Options	- One changeable 12.7mm(H) CD-ROM / DVD-ROM / Combo / DVD-Dual Drive - Software DVD Player (Option) 802.11b Wireless LAN, USB interface (Option) Bluetooth 1.1, USB interface ** (Option) TV Tuner module (Factory Option) 1x Sub Woofer (Factory Option) 300K-pixel Video Camera module

****Don't try to use Bluetooth & TV-Tuner at the same time. As this way, system may cause configuration conflicts.**
The specifications in gray are not available yet.
The content is subject to change without notice. Other brand and product names are trademarks and/or registered trademarks of their respective companies.