

M360C

The Powerful mix of Technology & Mobility



CLEVO[®]

Broadband Mobile Wireless infotainment

M360C Specifiaction

Model	M360C
CPU	<ul style="list-style-type: none"> Intel® Pentium® M Processor 1.3/1.4/1.5/1.6/1.7GHz uFC-PGA package
Core Logic	<ul style="list-style-type: none"> Intel 855GM (Montara-GM)
Display	<ul style="list-style-type: none"> 14.1" XGA TFT 1024x 768
Memory (RAM)	<ul style="list-style-type: none"> 2xDDR 200/266 sockets Expandable Memory up to 1 GB, depend on 128/256/512 MB DDR Module
Video Controller	<ul style="list-style-type: none"> Integrated 128-bit 2D/3D Graphics Engine Motion Compensation for DVD Accelerator Fully DirectX 7/8 Compliant Graphics Engine Support VESA DDC1, DDC2B and DDC 3.0 Specification
HDD	<ul style="list-style-type: none"> Changeable 12.7mm(h) optical Drive Changeable 2.5" 9.5mm(h) HDD, support LBA mode Support Master IDE/ PIO mode 4/ ATA- 33/66/100
Keyboard	<ul style="list-style-type: none"> A4 sizes Win 95 Keyboard Built-in Touchpad with Scrolling Function
Sound System	<ul style="list-style-type: none"> AC'97 2.2 Compliant Advanced Wavetable Synthesizer Direct Sound™ 3D Accelerator Virtual AC3, Full Duplex Built-in 2 speakers Built-in Microphone
I/O Ports	<ul style="list-style-type: none"> 1x External CRT Monitor Port 2x USB 2.0 Ports 1x RJ45 for LAN 1x RJ11 Jack for Plug& Play Fax Modem 1x mini IEEE 1394 port DC-in jack 1x TV-Out Jack/ 1x Jack for Headphone 1x Microphone Jack/ S/PDIF Output Jack
PCMCIA	<ul style="list-style-type: none"> 1x Type-II PCMCIA 3.3V/5V socket
Communication	<ul style="list-style-type: none"> CMOS camera with USB interface INTEL PRO/Wireless LAN 2100 module with Mini-PCI interface Bluetooth 1.1 with MDC interface (Option) 10/100Mb Fast Ethernet 56K Plug & Play Fax/ Modem V.90/V.92 compliant
Power Management	<ul style="list-style-type: none"> Full Range AC adapter 65W AC in 100~240V, 47~63Hz. 1st smart Lithium-Ion battery(6 cells) 2nd smart Lithium-Ion battery(12 cells) Support ACPI 2.0 Soft Off by system Power button, support suspend to disk, support suspend to RAM,and Battery low suspend. Resume from alarm time, Resume from modem ring and Wake on LAN.
Security	<ul style="list-style-type: none"> Kensington® Lock
Dimension	<ul style="list-style-type: none"> 312(w)x273(d)x27.5(h)mm Min. 2.2Kg without battery
Options	<ul style="list-style-type: none"> Standard Smart Lithium-Ion Battery Pack , 48Watt 802.11b module with Mini-PCI interface Bluetooth 1.1 + MDC Module 2.5" 12.5/12.7mm height HDD Option smart Lithium-Ion battery pack, 96Watt

