

M375E

The Powerful mix of Technology & Mobility

- ATi Mobility Radeon 9600 PRO 
- Gigabit Ethernet
- 15.4" and 16:10 Wide Screen
- 4-in-1 Card Reader
- 4x Surrounding Speakers
- USB PC Camera



CLEVO[®]

M375E Specification



Model	M375E
CPU	<ul style="list-style-type: none"> . Intel® Banias Processor 1.3/1.4/1.5/1.6/1.7GHz (400MHz FSB, u0.13) . Intel® Dothan Processor 1.7A/1.8/2.0GHz (400MHz FSB, u0.09)
Core Logic	<ul style="list-style-type: none"> . Intel® 855PM
Display	<ul style="list-style-type: none"> . 15.4" WXGA / 15.4" WSXGA+ / 15.4" WUXGA and 16:10 wide screen
Memory (RAM)	<ul style="list-style-type: none"> . 2x 200-pin SODIMM sockets, supporting DDR266 / 333 . Expandable Memory up to 2GB, based on 128/256/512/1024MB SODIMM Module
Video Controller	<ul style="list-style-type: none"> . ATI Mobility Radeon 9600 PRO (M10-P) high performance chip . Dual-view Display monitor . Integrated 64-bit 2D/3D Graphics Accelerator . External memory 64MB DDR SGRAM on board . External Display resolution up to 1600x1200 . support UXGA resolution
Storage	<ul style="list-style-type: none"> . Changeable CD-ROM / DVD-ROM / CD-RW / Combo / DVD-RW / DVD-dual 12.7mm(H) . Changeable 2.5" 9.5mm(H) HDD, supporting LBA mode . Supporting Master IDE, and PIO mode 4/ATA-33/66/100
Keyboard	<ul style="list-style-type: none"> . A4 sizes Win 95 Keyboard, Multi-Language . Built-in Touchpad with scrolling function
Sound System	<ul style="list-style-type: none"> . AC'97 2.2 Compliant . Advanced Wavetable Synthesizer . Direct Sound™ 3D Accelerator . 1x Built-in microphone / 4x Built-in speakers . S/PDIF Digital output . Full-duplex
I/O Ports	<ul style="list-style-type: none"> . 1x External CRT Monitor port . 1x Built-in 4-in-1 Card Reader (SD/MMC/MS/MS Pro) . 3x USB 2.0 ports / 1x Mini IEEE1394 port . 1x RJ-45 for 10/100/1000Mb Ethernet . 1x RJ-11 for Fax Modem . 1x S-Video jack (TV-Out) / 1x Serial port . 1x Headphone jack / 1x Microphone jack . 1x DC-In jack / 1x S/PDIF Output jack . Infrared Transfer, IrDA 1.1 FIR/SIR/ASKIR
PCMCIA	<ul style="list-style-type: none"> . 1x Type II PCMCIA 3.3V/5V socket
Communication	<ul style="list-style-type: none"> . Infrared Transfer, IrDA 1.1 FIR/SIR/ASKIR . 56K Fax Modem v.90/92 compliant . 10/100/1000Mb Ethernet . Intel® Pro/Wireless 2100 or Intel® Pro/Wireless 2200BG (option) . USB VGA CMOS Camera module (factory option) . Bluetooth 1.1 with MDC interface (factory option)
Power Management	<ul style="list-style-type: none"> . Full Range AC Adapter 65W AC in 100~240V, 47~63Hz . Standard Smart Lithium-ion battery (6 cells)
Security	<ul style="list-style-type: none"> . Kensington® Lock
Dimension	<ul style="list-style-type: none"> . 360(W) x 273(D) x 29.5(H)mm, 14.2"(W) x 10.7"(D) x 1.2"(H) . 3.15Kg with 6 cells Lithium-ion battery
Options	<ul style="list-style-type: none"> . Changeable CD-ROM / DVD-ROM / CD-RW / Combo / DVD-RW / DVD-dual drive . Software DVD Player . Bluetooth 1.1 + Fax Modem module (factory option) . Intel® Pro/Wireless 2100 or Intel® Pro/Wireless 2200BG . USB VGA CMOS Camera module (factory option)