

M385C Specification



Model	M385C
CPU	<ul style="list-style-type: none"> . Intel® Pentium® M Processor 1.3/1.4/1.5/1.6/1.7GHz . uFC-PGA package
Core Logic	<ul style="list-style-type: none"> . Intel 855GM (Montara-GM)
Display	<ul style="list-style-type: none"> . 15.4" and 16:10 wide screen
Memory (RAM)	<ul style="list-style-type: none"> . 2x DDR200 / 266 sockets . Expandable Memory up to 1GB/2GB, based on 128/256/512/1024MB DDR Module
Video Controller	<ul style="list-style-type: none"> . Intel® Dynamic Video Memory Technology . 128-bit 2D/3D Graphics Engine . Motion Compensation for DVD Accelerator . Fully DirectX 7/8 GPU . Supporting VSEA DDC1, DDC2B and DDC3.0 specifications
Storage	<ul style="list-style-type: none"> . Changeable CD-ROM / DVD-ROM / CD-RW / Combo / DVD-RW 12.7mm(H) . Changeable 2.5" 9.5mm(H) HDD, supporting LBA mode . Supporting Master IDE/PIO mode 4/ATA- 33/66/100
Keyboard	<ul style="list-style-type: none"> . Full sizes Win 95 Keyboard . Built-in Touchpad with scrolling function
Sound System	<ul style="list-style-type: none"> . AC'97 2.2 Compliant . Advanced Wavetable Synthesizer . Direct Sound™ 3D Accelerator . S\PDIF Digital output (5.1CH) . 5x Built-in speakers . 1x Built-in microphone
I/O Ports	<ul style="list-style-type: none"> . 1x External CRT Monitor port . 1x USB 1.1 port . 2x USB 2.0 ports . 1x RJ-45 for LAN . 1x RJ-11 for Fax Modem . 1x IEEE1394 port / 1x DC in jack . 1x TV-Out jack / 1x Headphone jack . 1x S\PDIF Output jack / 1x Microphone jack
PCMCIA	<ul style="list-style-type: none"> . 1x Typell PCMCIA 3.3V/5V socket
Communication	<ul style="list-style-type: none"> . CMOS camera with USB interface . 802.11b module with MiniPCI interface (option) . 802.11g module with MiniPCI interface (option) . Bluetooth 1.1 with MDC interface (option) . 10/100MB LAN on board . 56K Modem with V.90/V.92 compliant
Power Management	<ul style="list-style-type: none"> . Full Range AC Adapter 65W-AC in 100~240V, 47~63Hz . Supporting ACPI 2.0 . Soft Off by system Power button . Supporting suspend to RAM and suspend to Disk . Battery Low Suspend, Wake on LAN . Resume from Modem Ring, Resume from Alarm time, . 1x Smart Lithium-ion (6 cells) or 1x Smart Lithium-ion (12 cells)
Security	<ul style="list-style-type: none"> . Kensington® Lock
Dimension	<ul style="list-style-type: none"> . 360(W) x 273(D) x 27.5(H)mm, 14.2"(W) x 10.7"(D) x 1.1"(H) mm . 2.8Kg with 6 cells Lithium-ion battery
Options	<ul style="list-style-type: none"> . 802.11b module with MiniPCI interface . 802.11g module with MiniPCI interface . Bluetooth 1.1+ MDC module . 2.5" 9.5mm(H) or 12.7mm(H) . Smart Lithium-Ion battery pack, 48 Watt (6 cells) . Smart Lithium-Ion battery pack, 96 Watt (12 cells)