

# Product Specifications

# ActionNote™ 4SLC/25

<b>Processor</b>	486SLC /25MHz
Math CoProcessor Support	Optional Cyrix Cx 387SLC or Intel 387SX multifrequency numeric coprocessor
Cache Memory	1KB internal
<hr/>	
<b>Memory</b>	
ROM	128KB system and video BIOS
Shadow RAM	Yes
SETUP Program	Stored in ROM
Standard RAM	4MB
Maximum RAM	8MB (on system board)
<hr/>	
<b>Video RAM</b>	256KB DRAM
<hr/>	
<b>Clock/Calendar</b>	Real-time clock, calendar, and CMOS RAM; backed up by built-in Dallas® clock chip (DS 1287)
<hr/>	
<b>Option Slots</b>	One internal modem
<hr/>	
<b>Integrated Ports</b>	
Serial	Two RS-232C, programmable, asynchronous, 9-pin D-sub male connector
Parallel/external FDD	25-pin, D-sub, female connector
Mouse/keyboard	6-pin, mini-DIN connector for a PS/2-type pointing device or for mouse/keyboard adapter
CRT	15-pin, D-sub, female connector
Modem	RJ-11 connector for internal fax/modem phone jack
<hr/>	
<b>Speaker</b>	Built-in ISA compatible speaker controller; internal
<hr/>	
<b>Keyboard</b>	84 keys (USA); embedded numeric keypad; inverted "T" cursor controls
<hr/>	
<b>Mass Storage</b>	
Internal FDD	3.5" 1.44MB/720KB
Hard disk drive	80MB or 120MB
<hr/>	
<b>Video</b>	
Diagonal size	10"
Video model supported	VGA, EGA, CGA
Resolution	640 x 480
Dot Size	.3mm
Simultaneous LCD/CRT display	Yes
Disable internal video	Yes
Display type	Paper-white, 2 film CCFT backlit monochrome LCD
Gray scales	64 (320 x 200); 32 (640 x 480)
Brightness/contrast	Individually adjustable

<b>Power Supply</b>	
AC adapter	+15.5VDC, 2.4A continuous AC adapter with international voltage input, 50/60 Hz
Battery pack	One rechargeable, internal NiCad battery pack; 8-cell, 9.6 volt, 1.7AH, 16.3W
Battery life	2 hours (normal usage)
Battery recharge time	3 hours

<b>Physical Dimensions</b>	
Height	42 mm (1.6 in)
Width	280 mm (11.0 in)
Depth	225 mm (8.7 in)
Weight	2.5 kg (5.5 lbs) (w/battery pack installed)

<b>Environmental Requirements</b>	
Temperature	
Operating	5° to 35°C (41° to 95°F)
Non-operating	-20° to 60°C (-4° to 140°F)
Humidity	
Operating	30% to 90% (non-condensing)
Non-operating	5% to 95% (non-condensing)
Altitude	
Operating	-61 to 3,048 m (-200 to 10,000 feet)
Non-operating	-261 to 10,668 m (-200 to 35,000 feet)
Acoustical noise	-35dB max. @ 1 meter

<b>Software</b>	Current versions of MS-DOS and Windows preloaded on hard drive; WinFax Lite™ and BitCom® software preloaded on configurations with modem
-----------------	--

<b>Standard Accessories</b>	Logitech Trackman trackball Mouse/keyboard adapter
-----------------------------	---

<b>Options</b>	6MB memory expansion module NiCad battery pack Internal 2400/9600 data/fax/modem with WinFax Lite and BitCom software Adapter for an automobile cigarette lighter External PS/2-compatible keyboard
----------------	---

<b>Warranty</b>	One-year limited warranty and free On-Site service in the U.S.
-----------------	--

<b>Support</b>	Technical Support: 800-922-8911 Faxback System: 310-782-4214 Electronic Bulletin Board: 310-782-4531
----------------	--

# EPSON®

USA: Call 1-800-289-3776 for the nearest dealer location

Epson America, Inc. 20770 Madrona Avenue, Torrance, CA 90509-2843

Canada: Call 1-800-463-7766 Epson Canada, Ltd.

95 Mural Street Richmond Hill, Ontario L4B 3G3 Fax 416-881-5765

Latin America: Call 1-305-265-0092 Epson Latin American Trading, Inc.

6103 Blue Lagoon Drive, Suite 230 Miami, Florida 33126 Fax 305-265-0097

Specifications are subject to change without notice. Epson is a registered trademark of Seiko Epson Corporation. ActionNote is a trademark of Epson America Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.

© Copyright 1993 Epson America, Inc. CPD-1369 200M 5.93 SCG

 Printed on Recycled Paper