

Product Specifications

ActionNote™ 4SLC/33

Processor	486SLC / 33MHz
Math CoProcessor Support	Optional Cyrix® Cx 387SLC or Intel® 387SX multifrequency numeric coprocessor
Cache Memory	1KB internal
Memory	
ROM	128KB system and video BIOS
Shadow RAM	Yes
SETUP Program	Stored in ROM
Standard RAM	4MB
Maximum RAM	8MB
Video RAM	256KB DRAM
Clock/Calendar	Real-time clock, calendar, and CMOS RAM; backed up by built-in clock chip (DS 1287)
Option Slots	One internal modem
Integrated Ports	
Serial	Two RS-232C, programmable, asynchronous, 9-pin D-sub male connectors
Parallel/external FDD	25-pin, D-sub, female connector
Mouse/keyboard	6-pin, mini-DIN connector for a PS/2-type pointing device or for mouse/keyboard adapter
CRT	15-pin, D-sub, female connector
Modem	RJ-11 connector for internal fax/modem phone jack
Speaker	Built-in ISA compatible speaker controller; internal
Keyboard	84 keys (USA); embedded numeric keypad; inverted "T" cursor controls
Mass Storage	
Internal FDD	3.5" 1.44MB/720KB
Hard disk drive	80MB, 120MB or 180MB
Video	
Diagonal size	10"
Video model supported	VGA, EGA, CGA
Resolution	640 × 480
Dot Size	.3mm
Simultaneous LCD/CRT display	Yes
Disable internal video	Yes
Display type	Paper-white, 2 film CCFT backlit monochrome LCD
Gray shades	64 (320 × 200); 32 (640 × 480)
Brightness/contrast	Individually adjustable

Power Supply	
AC adapter	+15.5VDC, 2.4A continuous AC adapter with international voltage input, 50/60 Hz
Battery pack	One rechargeable, internal NiCad battery pack; 8-cell, 9.6 volt, 1.7AH, 16.3W
Battery life	2 hours (normal usage)
Battery recharge time	3 hours

Physical Dimensions	
Height	42 mm (1.6 in)
Width	280 mm (11.0 in)
Depth	225 mm (8.7 in)
Weight	2.5 kg (5.5 lbs) (w/battery pack installed)

Environmental Requirements	
Temperature	
Operating	5° to 35°C (41° to 95°F)
Non-operating	-20° to 60°C (-4° to 140°F)
Humidity	
Operating	30% to 90% (non-condensing)
Non-operating	5% to 95% (non-condensing)
Altitude	
Operating	-61 to 3,048 m (-200 to 10,000 feet)
Non-operating	-61 to 10,668 m (-200 to 35,000 feet)
Acoustical noise	35dB max. @ 1 meter

Software	Current versions of MS-DOS and Windows preloaded on hard drive; WinFax® Lite and BitCom® software preloaded on configurations with modem
-----------------	--

Standard Accessories	Logitech Trackman trackball Mouse/keyboard adapter Carrying case
-----------------------------	--

Options	6MB memory expansion module NiCad battery pack Internal 2400/9600 data/fax modem with WinFax Lite and BitCom software Internal 9600/9600 data/fax modem with WinFax Lite and BitCom software Adapter for an automobile cigarette lighter External PS/2-compatible keyboard
----------------	---

Warranty	One-year limited warranty including On-Site service in the U.S.
-----------------	---

Support	Technical Support: 800-922-8911 Faxback System: 310-782-4214 Electronic Bulletin Board: 310-782-4531
----------------	--

EPSON®

USA: Call 1-800-289-3776 for the nearest dealer location

Epson America, Inc. 20770 Madrona Avenue, Torrance, CA 90509-2843

Canada: Call 1-800-463-7766 Epson Canada, Ltd.

95 Mural Street Richmond Hill, Ontario L4B 3C3 Fax 416-881-5765

Latin America: Call 1-305-265-0092 Epson Latin American Trading, Inc.

6103 Blue Lagoon Drive, Suite 230 Miami, Florida 33126 Fax 305-265-0097

Specifications are subject to change without notice. Epson is a registered trademark of Seiko Epson Corporation. ActionNote is a trademark of Epson America Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.

© Copyright 1993 Epson America, Inc. CPD-1374 150M 6.93 SCG

♻️ Printed on Recycled Paper