

Product Specifications

ActionNote™ 500C

Processor	486SLC2-50 MHz (clock-doubled)
Math Coprocessor Support	Optional numeric coprocessor
Cache Memory	1KB internal
Memory	
Standard RAM	4MB
Maximum RAM	8MB
ROM	128KB system and video BIOS
Shadow RAM	Yes
SETUP program	Stored in ROM
Video RAM	512KB DRAM
Option Slots	One internal modem
Clock/Calendar	Real-time clock, calendar, and CMOS RAM; backed up by built-in clock chip
Integrated Ports	
Serial	RS-232C, programmable, asynchronous, 9-pin, D-sub male connector
Bidirectional parallel	25-pin, D-sub, female connector
Mouse	6-pin, mini-DIN connector for a PS/2®-type pointing device
Keyboard	6-pin, mini-DIN connector for external keyboard
CRT	15-pin, D-sub, female connector
Modem	RJ-11 connector for internal fax/modem phone jack
Speaker	Built-in ISA compatible speaker controller; internal
Keyboard	84 keys (USA); embedded numeric keypad; inverted T cursor controls
Mass Storage	
Internal FDD	3.5" 1.44MB/720KB
Hard disk drive	80MB, 120MB or 180MB
Video	
Diagonal size	8.2"
Video modes supported	VGA, EGA, CGA
Resolution	640 × 480 (LCD)
Dot size	0.26 mm
LCD/CRT support	Autosense; SimulScan support
Display type	CCFT backlit STN color LCD
Colors	256
Brightness/contrast	Individually adjustable
External video support	640 × 480 × 256 colors 800 × 600 × 256 colors 1024 × 768 × 16 colors
Physical Dimensions	
Height	42 mm (1.6 in)
Width	280 mm (11.0 in)
Depth	225 mm (8.7 in)
Weight	2.5 kg (5.5 lbs) (w/battery pack installed)

Power Supply	
AC adapter	+15.5VDC, 2.4A continuous AC adapter with international voltage input, 50/60 Hz
Battery pack	One rechargeable, internal NiCAD battery pack; 8-cell, 9.6 volt
Battery life	NiCad: 2-3 hrs. (w/power management) NiMH: 2.5-3.5 hrs. (w/power management)
Battery recharge time	3 hours

Environmental Requirements

Temperature	
Operating	5° to 35° C (41° to 95° F)
Non-operating	-20° to 60° C (-4° to 140° F)
Humidity	
Operating	30% to 90% (non-condensing)
Non-operating	5% to 95% (non-condensing)
Altitude	
Operating	-61 to 3,048 m (-200 to 10,000 feet)
Non-operating	-61 to 10,668 m (-200 to 35,000 feet)
Acoustical noise	35dB max. @ 1 meter

Software	Current versions of MS-DOS and Windows preloaded on hard drive; WinFax™ Lite and BitCom® software preloaded on configurations with modem
-----------------	--

Standard Accessories	Logitech TrackMan trackball Carrying case
-----------------------------	--

Optional Accessories

A881251	4MB memory expansion module
A880451	NiCad battery pack
A881181	NiMH battery pack
A880471	Internal 2400/9600 data/fax modem with WinFax Lite and BitCom software
A881141	Internal 14.4/14.4 data/fax modem with WinFax Lite and BitCom software
A880461	Adapter for automobile cigarette lighter
A880252	External PS/2-compatible keyboard
A881331	External numeric keypad

Warranty	One-year limited warranty including On-Site service in the U.S.
-----------------	---

Support

Technical Support	
U.S.	800-922-8911
Canada	800-463-7766
Faxback System	310-782-4214
Electronic Bulletin Board	310-782-4531

EPSON®

USA: Call 1-800-289-3776 for the nearest dealer location
Epson America, Inc., 20770 Madrona Avenue, Torrance, CA 90503

Canada: Call 1-800-463-7766 Epson Canada, Ltd.
550 McNicoll Ave, Willowdale, Ontario M2H 2E1 Fax: 416-479-8571

Latin America: Call 1-305-265-0092 Epson Latin America, Inc.
6303 Blue Lagoon Drive, Suite 390, Miami, Florida 33126 Fax: 305-265-0097

Europe: Call (39)-2-262331 Epson PC Operations (Italy)
Fax: (39)-2-2440641

Specifications are subject to change without notice. EPSON is a registered trademark of Seiko Epson Corporation. ActionNote is a trademark of Epson America, Inc. EPSON Connection is a service mark of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. EPSON disclaims any and all rights in these marks. © Copyright 1994 Epson America, Inc. CPD-1573 175M 1.94 GAC