



RocketBrick2 - Specifications

Processor	CPU/Speed	Intel® Pentium® III 1.20/1.13/1 GHz and Celeron™ 1GHz, 900MHz Processors (fcPGA)
Controller/BIOS		SiS SIS630B / AMI
Cache	Secondary	256KB on-die L2 cache
Memory (SDRAM)	Standard Maximum	0MB on board - Support PC-133/100 Type 512MB, by 64/128/256MB 144-Pin 3.3v SODIMM in 2 Slots
Data Storage	HDD FDD DVD/CD-ROM	Choice of 40/30/20/10 GB Enhanced IDE (Ultra DMA/66) 9.5mm Internal 3.5-inch 1.44MB Drive Choice of internal 8X DVD-ROM, 24X CD-ROM Drive, 4X CD-RW, or Combo DVD/CD-RW
Display	Type/Size	Choice of 12.1", 14.1" or 15" Active Matrix Color TFT LCD
Video	Video RAM Version Resolution Features	Up to 32MB NVRAM SiS 630 1024 x 768 AGP 4X 3D Windows Accelerator Support 15/16/24bbp True Color on LCD DualView function and Simultaneous display on LCD / CRT
Modem/LAN		Internal 56K V.90 data/fax modem with 10/100BT Ethernet combo card
Audio	Controller Internal Connectors	SiS 630B 3D Stereo Sound/hardware wave-table/Full-duplex, Stereo speakers, microphone Headphone-out/Microphone-in
PCMCIA	Type Chipset Support	One Type II or one Type III O2Micro OZ 6812 /6912 32-Bit Cardbus and ZV supported
Interface Ports	Serial Parallel Ext. CRT KB/Mouse InfraRed MIC-in Headphone-out USB Port RJ-11 RJ-45	High Speed (16550A) Enhanced (ECP and EPP) XGA Out PS/2 Fast IR (4Mbps), IrDA and ASK Compliant Yes Yes Yes For 56K modem For 10/100BT Ethernet
System Bus		133Mhz Front Side Bus

Pointing Device	Type	Synaptics Touchpad with 2 buttons
Keyboard	Keys Hot Keys	87 keys with 101/102 key emulation Embedded numeric keypad, 12 Function Keys and Windows 98 Keys Various for system control
Battery	Type Average Life Recharge Time	Li-Ion battery (47.4Wh) 2 Hrs (approximate only) 1 to 2 Hours System Off or Suspended and 8 to 10 hours System On
Power Management		Suspend/Resume, Global Standby, CPU Standby; Suspend to Disk & RAM, Low Battery Warning Light and Alarm, Battery "Gas Gauge"
System Status Indicators		Caps, Num, Scroll, Pad lock LEDs Power, suspend status LEDs IDE activity LEDs
AC Adapter		Universal 90-264V AC, 47-63Hz, 45W w/19V DC output
Software	OS Compatible Application	Windows XP Pro (WXP Home, W2K, WME, W98) <u>Notebook Essentials 2002 Suite Software Package</u>
Dimensions	Size Weight	12.4"(W) x 10.1"(D) x 1.6"(H) 6.5 lb
Security Features Y2K Compliant		Password protection for system, Kensington Key Lock Yes
Limited Warranty		One Year Parts & Labor Warranty Lifetime Free Technical Support
Optional Accessories		Spare Li-Ion battery, 24x CD-ROM, 8x DVD-ROM, 4X CD-RW, Combo DVD/CD-RW, Car power adapter, Spare AC adapter, spare 20/10 GB hard drive modules & 64/128/256/512MB upgrade memory modules