



the **BRICK** computer co.

RocketBrick2A Specifications

| | | |
|------------------------|---|---|
| Processor | CPU/Speed | AMD Mobile Athlon AXP 1500-2200 |
| Controller/BIOS | | VIA Twister K VT8362 |
| Cache | Secondary | 256KB on-die L2 cache |
| Memory (SDRAM) | Standard Maximum | 0MB on board - Support PC-133/100 Type 512MB, by 64/128/256MB 144-Pin 3.3v SODIMM in 2 Slots |
| Data Storage | HDD FDD DVD/CD-ROM | Choice of 40/30/20/10 GB Enhanced IDE (Ultra DMA/66) 9.5mm Internal 3.5-inch 1.44MB Drive Choice of internal 8X DVD-ROM, 24X CD-ROM Drive, 4X CD-RW, or Combo DVD/CD-RW |
| Display | Type/Size | 14.1" Active Matrix Color TFT LCD |
| Video | Video RAM Version Resolution Features | Up to 32MB NVRAM SiS 630 1024 x 768 AGP 4X 3D Windows Accelerator Support 15/16/24bbp True Color on LCD Simultaneous display on LCD / CRT |
| Modem/LAN | | Internal 56K V.90 data/fax modem with 10/100BT Ethernet combo card |
| Audio | Controller Internal Connectors | VIA VT8231 3D Stereo Sound/hardware wave-table/Full-duplex, Stereo speakers, microphone Headphone-out/Microphone-in |
| PCMCIA | Type Chipset Support | One Type II or one Type III O2Micro OZ 6812 /6912 32-Bit Cardbus and ZV supported |
| Interface Ports | Serial Parallel Ext. CRT KB/Mouse InfraRed MIC-in Headphone-out USB Port RJ-11 RJ-45 | High Speed (16550A) Enhanced (ECP and EPP) XGA Out PS/2 Fast IR (4Mbps), IrDA and ASK Compliant Yes Yes Yes Yes For 56K modem For 10/100BT Ethernet |

| | | |
|---|---------------------------------|--|
| | 1394 FireWire | Yes |
| System Bus | | |
| | | 133Mhz Front Side Bus |
| Pointing Device | Type | Synaptics Touchpad with 2 buttons |
| Keyboard | Keys | 87 keys with 101/102 key emulation Embedded numeric keypad, 12 Function Keys and Windows 98 Keys |
| | Hot Keys | Various for system control |
| Battery | Type | Li-Ion battery 1800mAH |
| | Average Life | 2+ Hrs (approximate only) |
| | Recharge Time | 1 to 2 Hours System Off or Suspended and 8 to 10 hours System On |
| Power Management | | |
| Suspend/Resume, Global Standby, CPU Standby; Suspend to Disk & RAM, Low Battery Warning Light and Alarm, Battery "Gas Gauge" | | |
| System Status Indicators | | |
| Caps, Num, Scroll, Pad lock LEDs Power, suspend status LEDs IDE activity LEDs | | |
| AC Adapter | | |
| Universal 90-264V AC, 47-63Hz, 45W w/19V DC output | | |
| Software | OS Compatible Application | Windows XP Home (WXP Pro, W2K, WME, W98) PC Works Suite |
| Dimensions | Size Weight | 12.4"(W) x 10.1"(D) x 1.2"(H) 6.5 lb |
| Security Features Y2K Compliant | | |
| Password protection for system, Kensington Key Lock Yes | | |
| Limited Warranty | | |
| One Year Parts & Labor Warranty Lifetime Free Technical Support | | |
| Optional Accessories | | |
| Spare Li-Ion battery, 24x CD-ROM, 8x DVD-ROM, 8X CD-RW, Combo DVD/CD-RW, Car power adapter, Spare AC adapter, spare 20/10 GB hard drive modules & 64/128/256/512MB upgrade memory modules | | |