

# Brick Model 478 Pentium IV Portable

---

<b>Structure</b>	Intel 845 Chipset L2 256KB cache
<b>Microprocessor</b>	Intel Pentium 4 Processors with OLGA Package, mPGA 478 Socket Support up to P4 2.0GHz 400MHz System Bus
<b>Memory (RAM)</b>	Expandable to 512MB (PC-133) 2 x 144-pin SDRAM SO-DIMM sockets
<b>Video</b>	ATI Mobility M6-M (integrated 8MB DDR VRAM) Support AGP 4X Support Multi Monitor
<b>Display</b>	1024 x 768 XGA TFT 14.1"
<b>PCMCIA Slots</b>	1 x Type II CardBus Slot
<b>Storage</b>	2.5" (9.5mm) HDD with Ultra DMA100 supported Support 10GB/20GB/30GB/40GB capacities 12.7mm DVD-ROM Support External USB FDD
<b>Input Devices</b>	19mm pitch/3.0mm stroke 1 x Windows Logo Key, 1 x Application Key, 1 x Mail Received Button, 5 x Easy Start Buttons Glide pad with 2 x buttons and 1 x scroll button
<b>Sound System</b>	Sound Blaster Pro compatible Support AC97 2.1 Built-in mono microphone 2 x Speakers
<b>I/O Ports</b>	1 x Bi-Directional, ECP/EPP Parallel Port 2 x USB Port 1 x RJ-11 Port 1 x RJ-45 Port 1 x DC input 1 x VGA Port 1 x Audio-out (SPIDF) 1 x Mic-in 1 x IEEE 1394 port 1 x S-Video Out Port (NTSC/PAL)
<b>Communication</b>	Built-in 56Kbps V.90 MDC modem Built-in 10/100 based-T LAN
<b>Battery</b>	9 cells, Li-ion (1800mAH/2000mAH/3.7V) User swappable 2 hours battery run time
<b>Power Management</b>	Universal AC Adapter, 100-240V AC, 50-60Hz
<b>Dimension</b>	12.32" x 10.35" x 1.50" 7.13lb. includes battery