

# IBM ThinkPad® 240X - withdrawn

<b>IBM® ThinkPad®</b>				
Processor	<b>Intel® Mobile Celeron™ 450MHz<sup>1</sup> or Intel Mobile Pentium® III 500MHz / 100MHz system bus</b>			
L2 cache	<i>Celeron: 128KB / onboard (at processor speed); Pentium III: 256KB / onboard (at processor speed)</i>			
Diskette drive	External 3.5" 1.44MB / connects to left side with FDD port / includes case and cable			
CD-ROM	<i>Option: External via USB port or via Portable Drive Bay 2000 and 24X-10X<sup>5</sup> CD-ROM Ultrabay 2000 Drive</i>			
LS-120 and CD-RW	<i>Option: External via Portable Drive Bay 2000 and drive option / no support for DVD in the Portable Drive Bay</i>			
Type-model	<b>2609-51U</b>	<b>2609-52U</b>	<b>2609-61U</b>	<b>2609-62U</b>
Processor	<b>Celeron 450MHz</b>	<b>Celeron 450MHz</b>	<b>Pentium III 500MHz</b>	<b>Pentium III 500MHz</b>
Disk - size / ms	<b>6.0GB<sup>2</sup> / 13ms read / Ultra DMA/33 or PIO Mode 4</b>		<b>12.0GB / 12ms read / ATA-66 or PIO4</b>	
Preload (see side)	<b>Windows 98<sup>7</sup> SE</b>	<b>Windows 2000</b>	<b>Windows 98<sup>7</sup> SE</b>	<b>Windows 2000</b>
Available date	June 2000	June 2000	June 2000	June 2000
Display - size and type	<b>10.4" TFT color (264.16mm) / Active Matrix</b>			
Display - technology	<b>SVGA / 800x600 / 15ms refresh (typical) / 50 to 110 nits</b> 16.7 million simultaneous colors / 150 to 1 contrast (typical)			
Graphics - controller	<b>Silicon Motion® Lynx EM+ SM712G™ / DDC2B / 2MB / SGRAM (embedded) / color space conversion / multiple monitor support<sup>26</sup> for Windows 98</b>			
Graphics - features	Simultaneous LCD and CRT <sup>26</sup> / 180 degree tilt / external SVGA to 1024x768 with 65,536 colors			
Memory - std / max	<b>64MB / 192MB<sup>33</sup></b>			
Memory - features	SDRAM / non-parity / <b>100MHz / 3.3 volt / 64-bit</b> 1 available socket for JEDEC 144-pin SO DIMM / std memory soldered to motherboard / socket accessed by removing three screws and keyboard			
Disk controller / disk	EIDE / PCI 2.1 / supports one internal disk / customer can remove disk for upgrade (by removing three screws on base)			
Keyboard	Keyboard palm rest / 95% size of current standard ThinkPad keyboards / 18mm key pitch			
Pointing	TrackPoint® / Press-to-Select / Release-to-Select / dragging / click pace / sensitivity / spare caps			
Dimensions	10.2 x 8.0 x 1.05" (86 cubic inches) / 260mm x 202mm x 26.6mm			
Weight <sup>2</sup>	51U/52U: approximately 2.98 lbs (1.35 kg) with battery and disk 61U/62U: approximately 3.28 lbs (1.49 kg) with battery and disk			
Case material	IBM ThinkPad UltraCarbon™ casing / Top: carbon-fiber reinforced plastic; Bottom: glass-fiber reinforced plastic			
Battery - type	51U/52U: Li-Ion (3 cell); 61U/62U: Li-Ion (6 cell); All: intelligent / left side			
Battery - life <sup>10</sup>	51U/52U: 2.1 hrs      61U/62U: 4.2 hrs 51U/52U: Optional 6 cell battery for 4.2 hrs			
Charge time <sup>10</sup>	3.5 hrs on / 3.0 hrs off			
Architecture	<b>Intel 440MX PCiset (82443MX)</b> / combines Host Bridge and PIIX4 in single chip / TI1211 PCMCIA controller / NS PC97338 (FDC, IR, I/O) / PCI 2.1 / 32-bit / 33MHz (EIDE, graphics, PCMCIA, USB, audio, modem) ISA (diskette, serial, parallel, infrared)			
Docking station	None			
Port replicator	None (all standard ports already on back of system)			
PC Card Std slots	1 Type II or 1 Type I / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video support			
USB / serial / parallel	One USB / one 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)			
Other features	72 watt AC adapter			
Video (TV) out	None			
Data/fax modem	<b>56K<sup>37</sup> V.90 / Mini PCI Type IIIb / Lucent 1646</b>			
Audio	16-bit SoundBlaster Pro™ support / CS4281 PCI audio / CS4297A AC97 codec			
Speaker	One internal speaker (.5 watt)			
Audio features	Internal microphone / Fn+Insert and Fn+Delete volume control with mute			
Audio in/out jacks	Microphone jack (mono) / headphone jack (stereo) / line-in jack (stereo)			
Infrared ports	Infrared port on right side / IrDA 1.1 compatible / up to 4Mbps			
Security	Power-on password / setup password / disk password / security keyhole			
Limited warranty <sup>11</sup>	<b>1 year</b> - carry-in or ThinkPad EasyServ™ <sup>31</sup> (door-to-door depot repair service)			
Service options <sup>15</sup>	Service upgrades available based on specific ThinkPad purchased			

### WINDOWS 98 PRELOAD<sup>16</sup>

- Microsoft® Windows® 98 Second Edition
- Online User's Guide
- ThinkPad Configuration Program
- ThinkPad Utilities
- Access ThinkPad
- IBM Update Connector
- PC-Doctor
- ConfigSafe®
- Norton AntiVirus™ (OEM Version)
- Universal Manageability Services (web)
- ◆ Software Selections CD
- ◆ Lotus® SmartSuite® Millennium CD
- ◆ Recovery CD-ROM (Windows 98)
- ◆ Recovery CD-ROM (Windows 95)<sup>7</sup>

### WINDOWS 2000 PRELOAD<sup>16</sup>

- Windows 2000® Professional
- ThinkPad Utilities
- Online User's Guide
- ThinkPad Configuration Program
- PC-Doctor
- ConfigSafe
- Norton AntiVirus™ (OEM Version)
- IBM Update Connector
- Universal Manageability Services (web)
- ◆ Software Selections CD
- ◆ Lotus® SmartSuite® Millennium CD
- ◆ Recovery CD-ROM (Windows 2000)
- ◆ Recovery CD-ROM (Windows NT)<sup>40</sup>

Color depth LCD		External Monitor				OPTIONS		FEATURES	
Resolution	TFT	60Hz	70Hz	75Hz	85Hz				
640x480	16M	16M	--	16M	16M	- 32MB SO DIMM 100MHz NP SDRAM	20L0253	Toll-free hardware support during the warranty period Personalized web-based support Wired for Management 1.1a compliant DMI 2.0-compliant PC 99-compliant ACPI ready (APM enabled) Setup Guide, User's Reference, Windows OS manual, and Quick Reference Card System Status Indicators Reset switch on bottom Plug and Play 1.0a Standby, suspend, redisafe, and hibernation modes ENERGY STAR compliant International Warranty Service <sup>14</sup> IBM SystemXtra®. <sup>35</sup> 24 hour / 7 day <sup>30</sup> telephone, fax, electronic, and Internet (www.ibm.com/pc/us) support	
800x600	16M	16M	--	16M	16M	- 64MB SO DIMM 100MHz NP SDRAM	20L0254		
1024x768*	64K	64K	64K	64K	--	- 128MB SO DIMM 100MHz NP SDRAM	20L0255		
1280x1024	--	--	--	--	--	- 12GB disk, 12ms read, ATA-66	05K9245		
						- High capacity 6-cell Li-Ion Battery	02K6580		
* Virtual screen mode on 10.4" LCD						- Ultraslim 72 watt AC Adapter	02K6699		
All models: - C: drive is FAT16 of 2GB - D: drive is FAT32 of remaining space						- DC Auto Adapter	02K3381		
						- V.90 56K Intern Modem with GSM	02K4280		
Pressing F1 during startup brings up IBM BIOS Setup Utility						- 10/100 EtherJet™ CardBus Adapter	34L5301		
						- IBM 16/4 Token-Ring CardBus Adap	34L4801		
Disks are S.M.A.R.T. <sup>29</sup> compliant						- Smart Card Security Kit	33L5075		
						- IBM Portable Drive Bay 2000	19K4480		
- ThinkPad Proven™ solutions <sup>12</sup> (visit www.ibm.com/pc/us/thinkpad/proven)						- IBM MultiPort USB Hub	00N8215		
						- IBM 340MB microdrive	00N8073		
						- IBM USB Portable CD-ROM Drive	33L5151		
						- IBM USB Mobile Mouse	33L3243		
						- IBM USB Numeric Keypad	33L3225		