

# IBM ThinkPad 345 (non-US) - withdrawn

<b>IBM® ThinkPad®:</b>	⊗ <b>345CS</b> dual scan color	⊗ <b>345C</b> TFT color	<b>ThinkPad 345 is a fast, lightweight, full function, TFT or dual scan color notebook at a very attractive price point</b>	
Processor type	<b>IntelDX4</b>		⊕ <b>Entry priced ThinkPad</b>	
Processor speed	<b>75/25 MHz / 3.3 volt</b>		⊕ <b>Large color 10.4" dual scan or TFT display</b>	
Memory cache	16 KB internal (no L2 cache)		⊕ <b>Fast IntelDX4 75/25 MHz</b>	
Coprocessor socket	Integrated in DX4		⊕ <b>Lightweight (5.2 or 5.5 pounds)</b>	
Processor / L2 upgrade	None		⊕ <b>TrackPoint III</b>	
Diskette drive	3.5" 1.44 MB (not removable)			
Removable CD-ROM	None			
Price	\$	\$	\$	\$
Type - model	2610-EYF	2610-EYG	2610-FYF	2610-FYG
IDE disk - size	<b>360 MB</b>	<b>540 MB</b>	<b>360 MB</b>	<b>540 MB</b>
Hard drive - speed	13 ms	13 ms	13 ms	13 ms
Avail / withdrawn date	Sep 1995 / Jan 1996		Sep 1995 / Apr 1996	
Display - type	<b>VGA color / 640 x 480</b>		<b>VGA color / 640 x 480</b>	
Display - colors	256 simultaneous colors		256 simultaneous colors	
Display - technology	<b>Dual Scan</b> - passive matrix		<b>Black Matrix TFT - active matrix</b>	
Display - diagonal size	<b>10.4 inch</b>		<b>10.4 inch</b>	
Display - contrast ratio	20 to 1		100 to 1	
180 degree display tilt	Yes		Yes	
Graphics - controller	WD90C24A Rev C with 1 MB DRAM			
Graphics - vendor	Western Digital / External SVGA to 1024 x 768 with 256 colors (up to 60 Hz)			
Graph - arch/data path	VL-Bus local bus / 32 bit / Simultaneous LCD and CRT			
Memory - std / max	4 MB / 20 MB 70 ns / non-parity / 5 volt		Memory upgraded via	
Mem - sockets empty	1 socket		1 open socket for IC DRAM	
Mem - options available	4, 8, 16 MB IC DRAM		memory card for 20 MB max	
Keyboard / # of keys	Full size alp/num / 85 keys / quiet keyboard			
Fn key functions	7 (in any appl)			
Keyboard slope	None			
Mouse/pointing	<b>TrackPoint III™</b> (no drag lock)			
Ext keyboard support	Yes (with optional cable)			
Dimensions	11.7 x 8.3 x 1.9"		11.7 x 8.3 x 2.0"	
Cubic inches	184 inches		194 inches	
Color	Black		Black	
Weight (with battery)	5.2 pounds		5.5 pounds	
Battery - type	Nickel hydride (NiMH) / non-intelligent			
Batt - life (per battery)	2.5 to 5 hours			
Charge time - on / off	2 hrs / 1.5 hr			
Architecture	AT bus (ISA)			
Docking Station	None			
Port replicator	None			
PCMCIA™ 2.1 slots	1 Type I or 1 Type II or 1 Type III			
Serial / parallel ports	Yes (one 9 pin) 16550A / Yes (EPP)			
Other features	APM-aware BIOS / Selectable boot AC adapter, 35 watts, worldwide, 3 pin, not wallmount			
Audio support	Audio beep only			
Security	Power-on password Locking device keyhole (Kensington™ MicroSaver™ cablelock)			
Preinstalled software	IBM DOS 7.0, Windows™ 3.11, and all appls listed to right:			
Warranty	1 year - ThinkPad EasyServ only			
Warranty options	None			

<p><b>PREINSTALLED APPLICATIONS</b></p> <ul style="list-style-type: none"> <li>- IBM PC DOS 7.0</li> <li>- Windows 3.11</li> <li>- IBM PC Card Director for PCMCIA</li> <li>- IBM ThinkPad Demo</li> <li>- ThinkPad features; Diskette Factory</li> <li>1. Lotus® cc:Mail, for the IBM Global® network,</li> <li>2. Lotus Organizer 1.12</li> <li>3. Lotus ScreenCam 1.0,</li> <li>4. Triton CoSession™ Host,</li> <li>5. PRODIGY®,</li> <li>6. SofNet FaxWorks™ 3.0</li> <li>7. AlphaNet™ FollowFax™</li> <li>8. Sedona REPRINT™</li> <li>9. Video for Windows™ 1.1 Runtime</li> </ul>
---

<p>The ThinkPad 345 family has the same physical design as the ThinkPad 340</p>	<p>Options for 345:</p> <ul style="list-style-type: none"> <li>- 4 MB IC DRAM 70 ns Parity 92G7232</li> <li>- 8 MB IC DRAM 70 ns Parity 92G7233</li> <li>- 16 MB IC DRAM 70 ns Parity 92G7234</li> <li>- 4 MB IC DRAM 70 ns non-Parity 92G7236</li> <li>- 8 MB IC DRAM 70 ns non-Parity 92G7237</li> <li>- 16 MB IC DRAM 70 ns non-Parity 92G7424</li> <li>- NiMH Battery Pack (Worldwide) 85G7637</li> <li>- NiMH Battery Pack (Japan) 95G7638</li> <li>- NiMH Battery Pack (EMEA) 85G7605</li> <li>- 35 watt AC Adapter (Worldwide) 85G6680</li> <li>- 35 watt AC Adapter (Japan) 85G6682</li> <li>- 35 watt AC Adapter (EMEA) 85G6683</li> </ul>	<p><b>FEATURES OF 345 FAMILY</b></p> <p>3 power saving modes: standby, suspend, and hibernation</p> <p>Personalized nameplate in molded indentation</p> <p>Battery life indicator</p> <p>Non-disruptive battery exchange</p> <p>US EPA Energy Star compliant</p>
<p>PC Card Director™ (EasyPlaying) is preinstalled and on the utility diskette for DOS, Windows and OS/2. It provides:</p> <ol style="list-style-type: none"> <li>① automatic config of many PCMCIA cards;</li> <li>② visual/audible confirmation of insertion/removal of cards;</li> <li>③ ability to automatically launch an appl (e.g. async emulation) when card inserted;</li> <li>④ status and info on PCMCIA cards installed.</li> </ol>	<p>IC DRAM parity memory from the above options will work but without parity</p>	<p><b>HELPPWARE</b></p> <p><b>International Warranty Service</b>  <b>24 hour / 7 day telephone, bulletin board, fax, and electronic support</b>  <b>IBM or dealer warranty/service</b>  <b>Online Housecall (remote diagnostics)</b>  <b>30 day money back guarantee</b></p>
<p>Easy-Setup is entered by holding F1 when turning on. Easy-Setup, BIOS, and diagnostics are located in flash memory.</p>		
<p>Hard disk and diskette drive are not removable. Keyboard does not lift up.</p>		

**ThinkPad EasyServ™:** customer calls 1-800-565-3344 in Canada, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround).  
 □ = Upgradeable; ○ = Removable; ⊗ = Withdrawn from marketing

All trademarks are the property of their respective owners  
 No warranties are expressed or implied in this summary  
 (345) Compiled by Roger Dodson, IBM. May 1996