

IBM ThinkPad 365ED - withdrawn

IBM® ThinkPad®: > 365ED 10.4" dual scan - CD-ROM		ThinkPad 365 (CD-ROM models) strengths ⇨ Entry-priced CD-ROM notebook ⇨ Integrated audio, microphone, speaker ⇨ Simultaneous external diskette ⇨ Joystick/MIDI port ⇨ Infrared port ⇨ MPC2 compliant	
Processor IBM 5x86c™ 100/33 MHz (Cyrix) / integrated math coprocessor Processor upgrade None Memory cache 16 KB in 5x86c (write-back) / no L2 cache Diskette (not internal) External 3.5" 1.44 MB (connects to back of system) / use simultaneously w/ CD-ROM CD-ROM (not remove) 5.25" CD-ROM / 4 x speed / multi-session / XA / front loaded / ATAPI			
Price Type - model 2625-W9G Preload (see side) Windows 95 Disk - capacity 540 MB Disk - ms / interface 13 ms / EIDE / PIO Mode 3 Available date May 1996 Withdrawn date October 1996		WINDOWS 95 PRELOAD - Microsoft Windows 95 - Online Users Guide - Diskette Factory - PC Card Director 1.4 1. Triton CoSession™ Host 2. Puma TranXit™ 3. NetFinity for Windows 4. CompuServ™ for Windows	
Display - diagonal size 10.4" Dual scan Display - type VGA color / 640 x 480 Display - color 256 simultaneous colors Display - contrast 30 to 1			
Graphics - controller Chips and Technologies™ 65545 with 1 MB DRAM Graphics - external External SVGA to 1024 x 768 w/ 256 colors up to 70 Hz Graph - arch/data path VL-Bus 2.0 local bus / 32 bit / Simultaneous LCD and CRT / 180 degree tilt			
Memory - std / max 8 MB / 24 MB 70 ns / non-parity / 3.3 volt / fast page Mem - upgrade 1 socket for one JEDEC 72 pin SO DIMM of 4 or 16 MB			
Keyboard / # of keys Full size alp/num / 85 (8 Fn key functions) Keyboard slope Yes (legs pop out) Pointing TrackPoint III™ Ext keyboard support Yes (with option cable or Port Replicator)			Liftable (pop-up) keyboard to access and remove battery (and upgrade memory and disk); CD-ROM is not removable
Dimensions (cubic in) 11.7 x 8.3 x 2.0" (194 cubic inches) Weight (with battery) 6.4 pounds Battery - type NiMH / non-intelligent Battery - life 2.3 hours Charge time - on / off 6 hrs / 2 hrs			
Architecture ISA (audio, PCMCIA, diskette, serial, parallel, 240 pin external expansion) Docking Station None Port replicator Port Replicator and Charger (with built-in battery charger and palm rest) PCMCIA™ 2.1 slots 2 Type I or 2 Type II or 1 Type III Serial / parallel ports One 9 pin; 16550A / one (IEEE P1284, EPP, ECP, bidirectional) Other features APM-aware BIOS / Universal AC adapter (35 watts) / Phoenix™ BIOS			
MPEG decoder None Data/fax modem None Audio support 16 bit audio chip / 18 voice MIDI FM Synthesis / ESS1688 with OPL3 Internal speaker / .5 watt / dial volume control / internal microphone Audio in/out jacks Input jack (stereo) / microphone jack / output jack (stereo) Joystick/MIDI port (includes Joystick/MIDI cable)			
Infrared ports Infrared port in back / IrDA 1.0 compatible / up to 115 Kbps			
Security Power-on password / Supervisor password / Locking device keyhole (Kensington™ MicroSaver™ cable lock) / keyboard lock (requires Kensington)			
Preinstalled software Windows 95 with utilities and applications (listed to right) Warranty 1 year - ThinkPad EasyServ (optional Overnight Repair Option) or carry-in			
The Port Replicator and Charger provide cable management, a battery charger for an optional second battery, a palm rest when installed on the system, and has complete port replication. The Port Replicator can charge a battery whether or not a ThinkPad is connected to it. When the ThinkPad is attached to the Port Replicator, it will attempt to recharge the battery in ThinkPad first (if there is one) before charging the battery in the Port Replicator. Port Replicator and Charger connectors: - Serial (RS-232, 9 pin) - Parallel (EPP, ECP, 25 pin) - External display (15 pin) - Keyboard - Mouse - Diskette drive (26 pin) - Game with MIDI support (15 pin) - Audio in (3.5 mm) - Audio out (3.5 mm) - DC input connector - Spare battery connector (to charge 2nd battery)		Options for ThinkPad 365: - 4 MB SO DIMM 3.3v non-parity 72 pin 92G7287 - 16 MB SO DIMM 3.3v non-parity 72 pin 92G7293 - 810 MB EIDE HDD 13 ms Mode 4 42H4012 - 1.08 GB EIDE HDD 13 ms Mode 4 69H7956 - Port Replicator and Charger (old) 38H6303 replaced by 75H7529 - NiMH Battery Pack 38H6304 - 35 watt AC Adapter - 2 pin 85G6719 Setup is entered by Ctrl + Alt + F11 from any full-screen DOS prompt Fn + F2 = Battery guage Fn + F3 = Standby Fn + F4 = Suspend Fn + F7 = LCD/CRT/Simultaneous Fn + F8 = Reverse video Fn + F11 = Power mgmt Fn + F12 = Hibernation PgUp = Speaker enable PgDn = Speaker disable System enters hibernation mode when keyboard is lifted up Disk is not removable (like 755/760 systems), but it can be upgraded via a screwdriver	
		FEATURES OF 365 MODELS Product Map LED indicator panel Plug and Play 1.0a Non-disruptive battery exchange Doze, standby, suspend, safe suspend, and hibernation modes US EPA Energy Star compliant Personalized nameplate in indentation Personalization screen at startup International Warranty Service 24 hour / 7 day telephone, bulletin board, fax, electronic, and Internet (http://www.pc.ibm.com) support IBM and dealer warranty/service Online Housecall (remote diagnostics)	

ThinkPad EasyServ™: customer calls IBM HelpCenter, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround).

All trademarks are the property of their respective owners
 No warranties are expressed or implied in this summary
 (365ED) Compiled by Roger Dodson, IBM. October 1996