

IBM ThinkPad 365X (Fall 1996 models) - withdrawn

IBM® ThinkPad®: >= 365X		
10.4" SVGA TFT or 11.3" SVGA DSTN color		
Processor type	Pentium® 120/60 or 133/66MHz / 64-bit transfer to memory	
Processor upgrade	None	
L2 cache	None (not upgradeable)	
Diskette drive	Internal 3.5" 1.44MB m (not removable)	
External FDD port	External FDD port (used if purchase CD-ROM upgrade)	
Internal CD-ROM	None standard / 4 x or 8 x CD-ROM option available which includes an external diskette drive (not customer install)	
Price		
Type - model	2625-3E9	2625-2E9
Preload (see side)	Windows 95	Windows 95
Avail / withdrawn date	October 1996 / July 1997	October 1996 / October 1997
Pentium speed	120/60MHz	133/66MHz
Disk - size / ms	810MB / 13ms ○ / PIO Mode 4	1.08GB / 13ms ○ / PIO Mode 4
Disk controller	EIDE / busmaster / PCI 2.1 / supports one internal disk	
Display - size and type	10.4 inch TFT color	11.3 inch DSTN color
Display - technology	SVGA / 640x480 or 800x600 Black Matrix TFT - active matrix 65,536 simultaneous colors / 100 to 1	SVGA / 640x480 or 800x600 Dual scan 256 simultaneous colors / 30 to 1 contrast ratio
Graphics - controller	Trident™ CYBER9320 / 32-bit SVGA accelerator / 1 MB fast page DRAM / 70ns	
Graph - arch/data path	PCI 2.1 / 32-bit / external SVGA to 1024x768 w/ 256 colors	
Graphics - features	Simultaneous LCD and CRT / 180 degree tilt	
Memory - std / max	8MB / 40MB	
Memory - features	70ns / non-parity / 3.3 volt / EDO / 1 socket for one JEDEC 144 pin EDO SO DIMMs of 8, 16, or 32MB	
Keyboard / # of keys	Full size alp/num / 85 (6 Fn key functions)	
Keyboard slope	Yes (legs pop out)	
Pointing / palm rest	TrackPoint III™ / external keyboard support (w/ option cable or Port Replicator)	
Dimensions	11.7 x 8.3 x 1.9" (185 cu in)	
Weight	6.1 pounds (2.76 kg)	5.9 pounds (2.67 kg)
Battery - type	NiMH / non-intelligent	Liftable (pop-up) keyboard to access and remove battery (and upgrade memory and disk); diskette drive is not removable
Battery - life	2.5 hours	
Charge time - on / off	1.5 hrs / 1.2 hrs	
Architecture	ISA (audio, PCMCIA, diskette, serial, parallel, infrared) PCI 2.1 / 32-bit / 33MHz (EIDE, graphics)	
Docking Station	None	
Port replicator	Port Replicator and Charger (with built-in battery charger and palm rest)	
PCMCIA™ 2.1 slots	2 Type I or 2 Type II or 1 Type III	
Serial / parallel ports	One 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)	
Other features	APM-aware BIOS / Universal AC adapter 3 prong (35 watts) / Selectable boot	
Video in/out	None	
MPEG decoder	None	
Data/fax modem	None	
Audio support	16-bit audio chip / 18 voice MIDI FM Synthesis / ESS1688 One internal speaker / .5 watt / dial volume control / internal microphone	
Audio in/out jacks	Input jack (stereo) / microphone jack / output jack (stereo) / no joystick port	
Infrared ports	Infrared port in back / IrDA 1.0 compatible / up to 115Kbps	
Security	Power-on pwd / Hard disk pwd / Supervisor pwd / Security keyhole (requires cable) / keyboard lock (requires cable)	
Preinstalled software	Microsoft Windows 95 wth applications (listed on right)	
Warranty	1 year - ThinkPad EasyServ (optional Overnight Repair Option) or carry-in	
<p>The Port Replicator and Charger provide cable management, a battery charger for an optional second battery, a palm rest when installed on the system, and has complete port replication.</p> <p>The Port Replicator can charge a battery whether or not a ThinkPad is connected to it. When the ThinkPad is attached to the Port Replicator, it will attempt to recharge the battery in ThinkPad first (if there is one) before charging the battery in the Port Replicator.</p> <p>Port Replicator and Charger connectors:</p> <ul style="list-style-type: none"> - Serial (RS-232, 9 pin) - Parallel (EPP, ECP, 25 pin) - External display (15 pin) - Keyboard - Mouse - Diskette drive (26 pin) - Game with MIDI support (15 pin) - Audio in (3.5 mm) - Audio out (3.5 mm) - DC input connector - Spare battery connector (to charge 2nd battery) 		<p>Options for ThinkPad 365X:</p> <ul style="list-style-type: none"> - 8MB SO DIMM 3.3v NP EDO 64-bit 92G7340 - 16MB SO DIMM 3.3v NP EDO 64-bit 92G7341 - 32MB SO DIMM 3.3v NP EDO 64-bit 92G7342 - 810MB EIDE HDD 13ms 42H4012 - 1.08GB EIDE HDD 13ms 69H7956 - 1.4GB EIDE HDD 3L 12.5 mm 82H8161 - 2.1GB HDD 13ms 82H8175 - Port Replicator and Charger 75H7529 - NiMH Battery Pack 38H6304 - 35 watt AC Adapter (2 pin barrel) 85G6719 - 35 watt AC Adapter (slim, 2 pin) 76H0139 - 365X 4 x CD-ROM Drive 73H7225 - 8 x CD-ROM 83H6726 <p>Fn + F2 = Battery guage Fn + F3 = Standby Fn + F4 = Suspend Fn + F7 = LCD/CRT/Simultaneous Fn + F11 = Power mgmt Fn + F12 = Hibernation</p> <p>Disk is not removable (like 755/760 systems), but it can be upgraded via a screwdriver</p>
		<p>WINDOWS 95 PRELOAD</p> <ul style="list-style-type: none"> - Microsoft Windows 95 - Online User's Guide - ThinkPad Features - PC Card Director 4.0 - Diskette Factory 1. Triton CoSession™ Host 2. Compuserv for Windows 3. NetFinity for Windows 95 4. Puma TranXit™ - Lotus SmartSuite 96 CD-ROM
		<p>Easy-Setup is entered by holding F1 when turning on.</p> <p>810MB = DMA Mode 2 or PIO Mode 4 1.08GB = DMA Mode 2 or PIO Mode 4</p>
		<p>FEATURES OF 365 MODELS</p> <p>Quick Setup Guide LED indicator panel Plug and Play 1.0a Doze, standby, suspend, safe suspend, and hibernation modes US EPA Energy Star compliant Personalized nameplate in indentation Personalization screen at startup International Warranty Service 24 hour / 7 day telephone, bulletin board, fax, electronic, and Internet (http://www.pc.ibm.com) support IBM and dealer warranty/service Online Housecall (remote diagnostics)</p>

ThinkPad EasyServ™: customer calls 1-800-772-2227, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). Overnight repair option in US available for \$99.
○ = Removable

All trademarks are the property of their respective owners
No warranties are expressed or implied in this summary
(365X96) Compiled by Roger Dodson, IBM. May 1999