

# IBM ThinkPad 365XD - withdrawn

<b>IBM® ThinkPad®:</b> <b>365XD</b>		Key differences between 365ED and 365XD:	
10.4" SVGA DSTN / 10.4" SVGA TFT / 11.3" SVGA DSTN			
Processor type	<b>Pentium® 100/66 or 120/60MHz</b> / 64-bit transfer to memory	<b>365ED</b>	<b>365XD</b>
Processor upgrade	None	5x86c 100/33MHz	Pentium 100, 120, 133
L2 cache	None (not upgradeable)	8MB fast page (to 24MB)	8MB EDO (to 40MB)
Diskette drive	External 3.5" 1.44MB (connects to back of system) / enclosed in a case with a cable / use simultaneously with CD-ROM	VL-Bus graphics and disk	PCI graphics and disk
External FDD port	External FDD port (works with standard external diskette; no kit reqd)	10.4" VGA 640 x 480 LCD	10.4" or 11.3" SVGA
CD-ROM (not remove)	<b>5.25" CD-ROM / 4 x speed</b> / multi-session / XA / front loaded / ATAPI	540MB disk standard	810MB, 1.08, 1.35GB
Price		Phoenix BIOS	IBM BIOS
Type - model	≈ 2625-6E3	≈ 2625-DEF	≈ 2625-DEE
Preload (see side)	<b>Windows 95</b>	<b>Windows 95</b>	<b>OS/2 Warp Connect</b>
Avail / withdrawn date	May 1996 / January 1997	May 96 / Jan 97	July 1996 / Jan 1997
Pentium speed	<b>100/66MHz</b>	<b>120/60MHz</b>	<b>120/60MHz</b>
Disk - size / ms	<b>810MB</b> / 13ms ○ / PIO Mode 4	<b>1.08GB</b> / 13ms ○ / PIO Mode 4	<b>1.08GB</b> / 13ms ○ / PIO Mode 4
Disk controller	EIDE / busmaster / PCI 2.1 / supports one internal disk		
Display - size and type	<b>10.4 inch DSTN color</b>	<b>10.4 inch TFT color</b>	<b>11.3 inch DSTN color</b>
Display - technology	<b>SVGA</b> / 640x480 or 800x600 <b>Dual scan</b> 256 sim colors / 25 to 1 contrast ratio	<b>SVGA</b> / 640x480 or 800x600 <b>Black Matrix TFT</b> - active matrix 65,536 sim col / 100 to 1 contrast ratio	<b>SVGA</b> / 640x480 or 800x600 <b>Dual scan</b> 256 sim colors / 30 to 1 contrast ratio
Graphics - controller	Trident™ CYBER9320 / 32-bit SVGA accelerator / 1MB fast page DRAM / 70ns		
Graph - arch/data path	PCI 2.1 / 32-bit / external SVGA to 1024x768 w/ 256 colors		
Graphics - features	Simultaneous LCD and CRT / 180 degree tilt		
Memory - std / max	<b>8MB</b> / 40MB		
Memory - features	70ns / non-parity / 3.3 volt / EDO / 1 socket for one JEDEC 144 pin EDO SO DIMMs of 8, 16, or 32 MB		
Keyboard / # of keys	Full size alp/num / 85 (6 Fn key functions)		
Keyboard slope	Yes (legs pop out)		
Pointing / palm rest	<b>TrackPoint III™</b> / external keyboard support (w/ option cable or Port Replicator)		
Dimensions	11.7 x 8.3 x 1.9" (185 cubic inches)		
Weight	6.4 pounds (2.9 kg)		
Battery - type	NiMH / non-intelligent	<b>Liftable (pop-up) keyboard to access and remove battery (and upgrade memory and disk); CD-ROM is not removable</b>	
Battery - life	2.5 hours		
Charge time - on / off	1.5 hrs / 1.2 hrs		
Architecture	ISA (audio, PCMCIA, diskette, serial, parallel, infrared) PCI 2.1 / 32-bit / 33MHz (EIDE, graphics)		
Docking Station	None		
Port replicator	Port Replicator and Charger (with built-in battery charger and palm rest)		
PCMCIA™ 2.1 slots	2 Type I or 2 Type II or 1 Type III		
Serial / parallel ports	One 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)		
Other features	APM-aware BIOS / Universal AC adapter 3 prong (35 watts) / Selectable boot		
Video in/out	None		
MPEG decoder	None		
Data/fax modem	None		
Audio support	<b>16-bit audio chip / 18 voice MIDI FM Synthesis / ESS1688</b> <b>One internal speaker / .5 watt / dial volume control / internal microphone</b>		
Audio in/out jacks	Input jack (stereo) / microphone jack / output jack (stereo) / no joystick port		
Infrared ports	<b>Infrared port in back / IrDA 1.0 compatible / up to 115Kbps</b>		
Security	Power-on pwd / Hard disk pwd / Supervisor pwd / Locking device keyhole (Kensington™ MicroSaver™ cable lock) / keyboard lock (requires Kensington)		
Preinstalled software	Microsoft Windows 95 wth applications (listed on right)		
Warranty	<b>1 year</b> - ThinkPad EasyServ (optional Overnight Repair Option) or carry-in		
<p>The <b>Port Replicator and Charger</b> provide cable management, a battery charger for an optional second battery, a palm rest when installed on the system, and has complete port replication.</p> <p>The Port Replicator can charge a battery whether or not a ThinkPad is connected to it. When the ThinkPad is attached to the Port Replicator, it will attempt to recharge the battery in ThinkPad first (if there is one) before charging the battery in the Port Replicator.</p> <p>Port Replicator and Charger connectors:</p> <ul style="list-style-type: none"> <li>- Serial (RS-232, 9 pin)</li> <li>- Parallel (EPP, ECP, 25 pin)</li> <li>- External display (15 pin)</li> <li>- Keyboard</li> <li>- Mouse</li> <li>- Diskette drive (26 pin)</li> <li>- Game with MIDI support (15 pin)</li> <li>- Audio in (3.5 mm)</li> <li>- Audio out (3.5 mm)</li> <li>- DC input connector</li> <li>- Spare battery connector (to charge 2nd battery)</li> </ul>		<p>Options for ThinkPad 365XD:</p> <ul style="list-style-type: none"> <li>- <b>8MB SO DIMM 3.3v NP EDO 64-bit</b>    <b>92G7340</b></li> <li>- <b>16MB SO DIMM 3.3v NP EDO 64-bit</b>    <b>92G7341</b></li> <li>- <b>32MB SO DIMM 3.3v NP EDO 64-bit</b>    <b>92G7342</b></li> <li>- 810MB EIDE HDD 13ms                    42H4012</li> <li>- 1.08GB EIDE HDD 13ms                   69H7956</li> <li>- 1.4GB EIDE HDD 3L 12.5 mm            82H8161</li> <li>- 2.1GB HDD 13ms                            82H8175</li> <li>- Port Replicator and Charger            75H7529</li> <li>- NiMH Battery Pack                        38H6304</li> <li>- 35 watt AC Adapter (2 pin barrel)      85G6719</li> <li>- 35 watt AC Adapter (slim, 2 pin)      76H0139</li> <li>- 8 x CD-ROM                                 83H6726</li> </ul> <p>Fn + F2 = Battery gauge Fn + F3 = Standby Fn + F4 = Suspend Fn + F7 = LCD/CRT/Simultaneous Fn + F11 = Power mgmt Fn + F12 = Hibernation</p> <p>Disk is not removable (like 755/760 systems), but it can be upgraded via a screwdriver</p>	
		<p>Easy-Setup is entered by holding F1 when turning on.</p> <p>810MB = DMA Mode 2 or PIO Mode 4 1.08GB = DMA Mode 2 or PIO Mode 4</p>	
		<p><b>FEATURES OF 365 MODELS</b></p> <p>Quick Setup Guide LED indicator panel Plug and Play 1.0a Doze, standby, suspend, safe suspend, and hibernation modes US EPA Energy Star compliant Personalized nameplate in indentation Personalization screen at startup <b>International Warranty Service</b> <b>24 hour / 7 day telephone, bulletin board, fax, electronic, and Internet</b> (<a href="http://www.pc.ibm.com">http://www.pc.ibm.com</a>) support <b>IBM and dealer warranty/service</b> <b>Online Housecall (remote diagnostics)</b></p>	

**ThinkPad EasyServ™:** customer calls 1-800-772-2227, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). Overnight repair option in US available for \$99.  
○ = Removable

All trademarks are the property of their respective owners  
No warranties are expressed or implied in this summary  
(365XD) Compiled by Roger Dodson, IBM. May 1999

# IBM ThinkPad 365XD (Fall 1996+ models) - withdrawn

<b>IBM® ThinkPad®:</b> >= 365XD		10.4" SVGA TFT / 11.3" SVGA DSTN / 11.3" SVGA TFT - CD-ROM	
Processor type	Pentium® 120/60 or 133/66MHz / 64-bit transfer to memory		
Processor upgrade	None		
L2 cache	None (not upgradeable)		
Diskette drive	External 3.5" 1.44MB (connects to back of system) / enclosed in a case with a cable / use simultaneously with CD-ROM		
External FDD port	External FDD port (works with standard external diskette; no kit required)		
CD-ROM (not remove)	5.25" CD-ROM / 4 x speed   5.25" CD-ROM / 6 x speed (all systems upgradeable to 8 x CD-ROM)		
CD-ROM features	Multi-session / XA / front loaded / ATAPI / not bootable / upgradeable		
Type - model (code)	2625-4E9 (Clark 4)	2625-GE9 (Clark 4.5)	2625-1E9 (Clark 4)
Preload (see side)	Windows 95	Windows 95 OSR2	Windows 95
Avail / withdrawn date	October 1996 / July 1997	Feb 1997 / July 1997	October 1996 / October 1997
Pentium speed	120/60MHz	120/60MHz	133/66MHz
Disk - size / ms	810MB / 13ms ○	1.08GB / 13ms ○	1.35 GB / 13ms ○ / PIO Mode 4
Disk controller	EIDE / busmaster / PCI 2.1 / supports one internal disk		
Display - size and type	10.4 inch TFT color		11.3 inch TFT color
Display - technology	SVGA / 640x480 or 800x600 Black Matrix TFT - active matrix 65,536 sim col / 100 to 1 contrast ratio		SVGA / 640x480 or 800x600 Black Matrix TFT - active matrix Dual scan 256 sim colors / 30 to 1 contrast ratio
Graphics - controller	Trident™ CYBER9320 / 32-bit SVGA accelerator / 1 MB fast page DRAM / 70 ns		
Graph - arch/data path	PCI 2.1 / 32-bit / external SVGA to 1024x768 w/ 256 colors		
Graphics - features	Simultaneous LCD and CRT / 180 degree tilt		
Memory - std / max	8MB / 40MB		
Memory - features	70ns / non-parity / 3.3 volt / EDO / 1 socket for one JEDEC 144 pin EDO SO DIMMs of 8, 16, or 32 MB		
Keyboard / # of keys	Full size alp/num / 85 (6 Fn key functions)		
Keyboard slope	Yes (legs pop out)		
Pointing / palm rest	TrackPoint III™ / external keyboard support (w/ option cable or Port Replicator)		
Dimensions	11.7 x 8.3 x 1.9" (185 cubic inches)		
Weight	6.4 pounds (2.9 kg)	6.1 pounds (2.77 kg)	6.2 pounds (2.79 kg)
Battery - type	NiMH / non-intelligent	<b>Liftable (pop-up) keyboard to access and remove battery (and upgrade memory and disk); CD-ROM is not removable</b>	
Battery - life	2.0 hours		
Charge time - on / off	1.5 hrs / 1.2 hrs		
Architecture	ISA (audio, PCMCIA, diskette, serial, parallel, infrared) PCI 2.1 / 32-bit / 33MHz (EIDE, graphics)		
Docking Station	None		
Port replicator	Port Replicator and Charger (with built-in battery charger and palm rest)		
PCMCIA™ 2.1 slots	2 Type I or 2 Type II or 1 Type III		
Serial / parallel ports	One 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)		
Other features	APM-aware BIOS / Universal AC adapter 3 prong (35 watts) / Selectable boot		
Video in/out	None		
MPEG decoder	None		
Data/fax modem	None		
Audio support	<b>16-bit audio chip / 18 voice MIDI FM Synthesis / ESS1688</b> <b>One internal speaker / .5 watt / dial volume control / internal microphone</b>		
Audio in/out jacks	Input jack (stereo) / microphone jack / output jack (stereo) / no joystick port		
Infrared ports	<b>Infrared port in back / IrDA 1.0 compatible / up to 115Kbps</b>		
Security	Power-on pwd / Hard disk pwd / Supervisor pwd / Security keyhole (requires cable) / keyboard lock (requires cable)		
Preinstalled software	Microsoft Windows 95 wth applications (listed on right)		
Warranty	<b>1 year</b> - ThinkPad EasyServ (optional Overnight Repair Option) or carry-in		
<p>The <b>Port Replicator and Charger</b> provide cable management, a battery charger for an optional second battery, a palm rest when installed on the system, and has complete port replication.</p> <p>The Port Replicator can charge a battery whether or not a ThinkPad is connected to it. When the ThinkPad is attached to the Port Replicator, it will attempt to recharge the battery in ThinkPad first (if there is one) before charging the battery in the Port Replicator.</p> <p>Port Replicator and Charger connectors:</p> <ul style="list-style-type: none"> <li>- Serial (RS-232, 9 pin)</li> <li>- Parallel (EPP, ECP, 25 pin)</li> <li>- External display (15 pin)</li> <li>- Keyboard</li> <li>- Mouse</li> <li>- Diskette drive (26 pin)</li> <li>- Game with MIDI support (15 pin)</li> <li>- Audio in (3.5 mm)</li> <li>- Audio out (3.5 mm)</li> <li>- DC input connector</li> <li>- Spare battery connector (to charge 2nd battery)</li> </ul>		<p>Options for ThinkPad 365XD:</p> <ul style="list-style-type: none"> <li>- <b>8MB SO DIMM 3.3v NP EDO 64-bit</b>    <b>92G7340</b></li> <li>- <b>16MB SO DIMM 3.3v NP EDO 64-bit</b>    <b>92G7341</b></li> <li>- <b>32MB SO DIMM 3.3v NP EDO 64-bit</b>    <b>92G7342</b></li> <li>- 810MB EIDE HDD 13ms                    42H4012</li> <li>- 1.08GB EIDE HDD 13ms                   69H7956</li> <li>- 1.4GB EIDE HDD 3L 12.5 mm            82H8161</li> <li>- 2.1GB HDD 13ms                            82H8175</li> <li>- Port Replicator and Charger            75H7529</li> <li>- NiMH Battery Pack                        38H6304</li> <li>- 35 watt AC Adapter (2 pin barrel)      85G6719</li> <li>- 35 watt AC Adapter (slim, 2 pin)      76H0139</li> <li>- 8 x CD-ROM                                83H6726</li> <li>- 2.1GB HDD 13ms 4000 rpm              82H8175</li> </ul> <p>Fn + F2 = Battery guage Fn + F3 = Standby Fn + F4 = Suspend Fn + F7 = LCD/CRT/Simultaneous Fn + F11 = Power mgmt Fn + F12 = Hibernation</p> <p>Disk is not removable (like 755/760 systems), but it can be upgraded via a screwdriver</p>	
		<p><b>WINDOWS 95 PRELOAD MODELS 4E9 and 1E9</b></p> <ul style="list-style-type: none"> <li>- Microsoft Windows 95</li> <li>- Online User's Guide</li> <li>- ThinkPad Features Program</li> <li>- PC Card Director 4.0</li> <li>- Diskette Factory</li> <li>1. Triton CoSession™ Host</li> <li>2. Compuerv for Windows</li> <li>3. NetFinity for Windows 95</li> <li>4. Puma TranXit™</li> <li>- Lotus SmartSuite 96 CD-ROM</li> </ul> <p><b>WINDOWS 95 PRELOAD MODELS GE9 and FE9</b></p> <ul style="list-style-type: none"> <li>- Microsoft Windows 95 OSR2</li> <li>- Online User's Guide</li> <li>- ThinkPad Features Program</li> <li>- PC Card Director 4.0</li> <li>- Diskette Factory</li> <li>1. Triton CoSession™ Host</li> <li>2. Compuerv for Windows</li> <li>3. NetFinity for Windows 95</li> <li>4. Puma TranXit™</li> <li>5. IntelliLink Connect</li> <li>6. IBM Anti-Virus</li> <li>7. IGN/Netscape Internet</li> <li>8. IntelliQuest Registration Mailer</li> <li>9. Ergonomics</li> <li>- Lotus SmartSuite 96 CD-ROM</li> </ul>	
		<p>Easy-Setup is entered by holding F1 when turning on.</p> <p>810MB = DMA Mode 2 or PIO Mode 4 1.08GB = DMA Mode 2 or PIO Mode 4 1.35GB = DMA Mode 2 or PIO Mode 4</p> <p><b>FEATURES OF 365 MODELS</b></p> <p>Quick Setup Guide LED indicator panel Plug and Play 1.0a Doze, standby, suspend, safe suspend, and hibernation modes US EPA Energy Star compliant Personalized nameplate in indentation Personalization screen at startup <b>International Warranty Service</b> <b>24 hour / 7 day telephone, bulletin board, fax, electronic, and Internet (http://www.pc.ibm.com) support</b> <b>IBM and dealer warranty/service</b> <b>Online Housecall (remote diagnostics)</b></p>	

**ThinkPad EasyServ™:** customer calls 1-800-772-2227, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). Overnight repair option in US available for \$99.  
○ = Removable

All trademarks are the property of their respective owners  
No warranties are expressed or implied in this summary  
(365XD96) Compiled by Roger Dodson, IBM. May 1999