

IBM ThinkPad 370C (non-US) - withdrawn

IBM® ThinkPad®:		≧ 370C TFT color		ThinkPad 370C is positioned between the ThinkPad 360 and ThinkPad 755 family	
Processor type		IntelDX4		Advantages over ThinkPad 360CE	
Processor speed		75/25 MHz / 3.3 volt		⊕ DX4 75/25 MHz (vs DX2 50/25)	
Memory cache		16 KB internal (no L2 cache)		⊕ 10.4" color TFT (vs 8.4" color TFT)	
Coprocessor socket		Integrated in DX4		⊕ Black Matrix TFT (vs not Black Matrix)	
Processor / L2 upgrade		None		⊕ 36 MB max mem (vs 20 MB max memory)	
Removable diskette		3.5" 1.44 MB ○ / supports internal 2.88 MB diskette			
Removable CD-ROM		None			
Price				ALL 370C MODELS	
Type - model		9545-QPC	9545-QPD	84G2152	Liftable (pop-up) keyboard to access and remove diskette drive, disk, battery, and memory
Removable disk - size		340 MB □ ○	540 MB □ ○	84G6539	
Hard drive - speed		14 ms	14 ms	84G2153	
Available date		May 1995	May 1995	92G7232	
Withdrawn date		May 1996	May 1996	92G7233	
Display - type		VGA color / 640 x 480		92G7234	<p>The removed diskette drive can be used externally via the optional 'FDD External Kit' (includes cable and enclosure) to the Port Replicator Model I and II and Dock I and II.</p> <p>Diskette drive can be removed</p> <ol style="list-style-type: none"> to reduce weight to insert cellular modem (CDPD) to insert TV Tuner (for on screen TV and VCR playback) to insert 2.88 MB diskette to add other third party options
Display - colors		256 simultaneous colors		92G7236	
Display - technology		Black Matrix TFT - active matrix		92G7237	
Display - diagonal size		10.4 inch / 100 to 1 contrast ratio / 180 degree tilt		92G7424	
Graphics - controller		WD90C24A Rev B with 1 MB DRAM			
Graphics - vendor		Western Digital / External SVGA to 1024 x 768 with 256 colors (up to 75 Hz)			
Graph - arch/data path		VL-Bus local bus / 32 bit / Simultaneous LCD and CRT			
Memory - std / max		4 MB / 36 MB 70 ns / non-parity / 5 volt			
Mem - sockets empty		1 socket			
Mem - options available		2, 4, 8, 16 MB ICs or 4, 8, 16 MB DIMMs that work on optional Memory Module Adapter			
Keyboard / # of keys		Full size alp/num / 85 keys			
Fn key functions		8 (in any appl)			
Keyboard slope		Yes (legs pop out)			
Mouse/pointing		TrackPoint II™			
Ext keyboard support		Yes (with optional cable)			
Dimensions		11.7 x 8.3 x 2.0"			
Cubic inches		194 inches			
Color		Black			
Weight (with battery)		6.3 pounds			
Battery - type		Nickel hydride (NiMH) / intelligent			
Batt - life (per battery)		2.9 to 8 hours			
Charge time - on / off		2 hrs / 1.5 hr			
Architecture		AT bus (ISA)			
Docking Station		Dock I and II			
Port replicator		Port Replicator I and II			
PCMCIA™ 2.1 slots		2 Type I or 2 Type II or 1 Type III			
Serial / parallel ports		Yes (one 9 pin) 16550B / Yes (EPP)			
Other features		APM-aware BIOS / Selectable boot AC adapter, 35 watts, worldwide, 3 pin, not wallmount			
Audio support		Audio beep only			
Security		Power-on password / Hard disk password / Supervisor Password / Hardware security loop (secures unit and prevents opening keyboard) / PCMCIA card lock / Optional Security Base			
Preinstalled software		IBM DOS 7.0, Windows™ 3.11, and all appls listed to right:			
Warranty		1 year - ThinkPad EasyServ only			
Warranty options		Onsite via special bid only			

<p>The ThinkPad 370 family has the same physical design as the ThinkPad 360, 750, and 755 family.</p> <p>PC Card Director™ (EasyPlaying) is preinstalled and on the utility diskette for DOS, Windows and OS/2. It provides:</p> <ol style="list-style-type: none"> automatic config of many PCMCIA cards; visual/audible confirmation of insertion/removal of cards; ability to automatically launch an appl (e.g. async emulation) when card inserted; status and info on PCMCIA cards installed. <p>Easy-Setup is entered by holding F1 when turning on. Easy-Setup, BIOS, and diagnostics are located in flash memory.</p>		<p>Compatible in all 360 family, 370 family, 750 family, and 755 family:</p> <ul style="list-style-type: none"> - Disks: 170 MB IDE 66G2847 250 MB IDE 84G2391 340 MB IDE 66G2849 540 MB IDE 84G2150 810 MB IDE 84G8250 1.2 GB IDE 85G8562 - Dock I (1 slot / 1 bay) 3545001 - Dock II (2 slot / 2 bay) 3546001 - Port Replicator I (w/ PCMCIA) 66G3510 - Port Replicator II 66G3520 - 1.44 MB diskette std in newer - 2.88 MB diskette 66G0108 <p>Options for 370C:</p> <ul style="list-style-type: none"> - TV Tuner 66G3689 - CDPD Mobile module 71G2560 - Car Battery Adapter 49G2167 - FDD External Attachment Kit 66G3618 <p>IC DRAM memory from ThinkPad 700, 720, 750, and 755 will work but without parity</p>		<p>FEATURES OF 370C FAMILY</p> <p>3 power saving modes: standby, suspend, and hibernation</p> <p>Personalized nameplate in molded indentation</p> <p>External VGA is ISO capable (75 Hz)</p> <p>Upgradeable disks: 170 MB, 250 MB, 340MB, 540 MB, 810 MB, 1.2 GB (all 2.5 inch)</p> <p>Battery life indicator</p> <p>Non-disruptive battery exchange</p> <p>US EPA Energy Star compliant</p>	
<p>ThinkPad 370C supported batteries:</p> <ul style="list-style-type: none"> - 750 NiMH battery 66G2846 - 750 Quick Charger 66G2843 		<p>HELPWARE</p> <p>International Warranty Service 24 hour / 7 day telephone, bulletin board, fax, and electronic support IBM or dealer warranty/service Online Housecall (remote diagnostics) 30 day money back guarantee</p>			

ThinkPad EasyServ™: customer calls 1-800-565-3344 in Canada, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround).
 □ = Upgradeable; ○ = Removable; ≧ = withdrawn from marketing

All trademarks are the property of their respective owners
 No warranties are expressed or implied in this summary
 (370) Compiled by Roger Dodson, IBM. June 1996