

# IBM ThinkPad® 390X - withdrawn

IBM® ThinkPad®						
Processor	Intel® Mobile Celeron™ 400MHz <sup>1</sup> or Mobile Pentium® II 400MHz / 66MHz system bus					
Processor features	No upgrade / processor, L2 cache, and MTXC (North Bridge) on Intel Mobile Module (MMC2)					
L2 cache	Celeron: 128KB; Pentium II: 256KB; All: onboard (full speed) / sync pipelined burst / ECC / write-back					
Diskette drive	Internal 3.5" 1.44MB / removable from UltraBay™ FX / on right side / integrated with CD-ROM / no external diskette port					
CD-ROM	CD-ROM / 24X-10X <sup>5</sup> speed / ATAPI / bootable / removable from UltraBay FX / on right side / integrated with diskette drive					
DVD-ROM	Option: Removable UltraBay FX option / 4X-1X <sup>6</sup> DVD integrated with a diskette drive					
Type - model	2626-F0U	2626-H0U	2626-HNU	2626-J0U	2626-JNU	
Processor / MHz	Celeron 400	Pentium II 400	Pentium II 400	Pentium II 400	Pentium II 400	
Disk - size / read ms	4.8GB <sup>4</sup> / 13ms	6.4GB / 12ms	6.4GB / 12ms	6.4GB / 12ms	6.4GB / 12ms	
Preload (see side)	Windows 98	Windows 98	NT 4.0	Windows 98	NT 4.0	
Avail / withdrawn date	Sept 99 / Jul 00	Sept 99 / Jul 00	Sept 99 / Jul 00	Sept 99 / Jul 00	Sept 99 / Jul 00	
Display (diagonal)	12.1" TFT SVGA	14.1" TFT XGA	14.1" TFT XGA	15" TFT XGA	15" TFT XGA	
Display - size and type	12.1" TFT color 308mm / Active Matrix SVGA / 800x600 / 20 to 30ms / 150 nits		14.1" TFT color 358mm / Active Matrix XGA / 1024x768 / 20 to 30ms / 120 nits		15.0" TFT color 381mm / Active Matrix XGA / 1024x768 / 10 to 30ms / 120 nits	
Display - technology	16.7 million colors / 150 to 1 contrast		16.7 million colors / 150 to 1 contrast		16.7 million colors / 150 to 1 contrast	
Graphics controller	NeoMagic™ MagicMedia256AV™ (NM2200) / 128-bit engine, 256-bit memory interface / 1X AGP / DDC2B / 2.5MB / SGRAM (embedded) / motion compensation / color space conversion / interpolation in X and Y axis Simultaneous LCD and CRT <sup>26</sup> / 150 degree tilt / multiple-monitor support <sup>26</sup>					
Memory - std / max	64MB / 512MB <sup>33</sup>					
Memory - features	SDRAM / non-parity / 100MHz / PC100-compliant / 3.3 volt / 64-bit / 2 sockets for JEDEC 144-pin SO DIMMs / one socket used by std memory / Sockets accessed from bottom via removing cover held by phillips-head screw					
Disk controller	EIDE / PCI 2.1 / one internal disk / disk can be removed to upgrade by customer / supports two internal disks / 13ms read / 14ms write / S.M.A.R.T. <sup>29</sup>					
Keyboard	Full-size 85-key (7 Fn key functions) / palm rest / keyboard slope with tilt feet					
Pointing	TrackPoint® / Press-to-Select / Release-to-Select / dragging / click pace / center button for scrolling (Internet Scroll Bar) or magnifying glass / spare caps					
Dimensions	12.1"/14.1": 12.4 x 10.1 x 1.8" (225 cu in) 15": 12.9 x 10.6 x 1.8" (246 cu)					
Weight <sup>2</sup> (with batt/disk)	12.1" and 14.1" models: 7.5 lbs (3.4 kg) 15" models: 7.9 lbs (3.6 kg)					
Case material	PC/ABS plastic					
Battery - type	F0U: NiMH / intelligent / left side Others: Li-Ion / intelligent / left side					
Battery - life <sup>10</sup> (1 batt)	F0U: 2.5 hrs Gxx/Hxx: 3.67 hrs Jxx: 3.5 hrs					
Charge time <sup>10</sup>	F0U/Hxx: 5 hrs on / 2.5 hrs off Jxx: 6 hrs on / 3 hrs off					
Architecture	Intel 440BX AGPset / Intel PIIX4E (EIDE, PCI to ISA bridge, USB) Texas Instruments® TI1251B PCMCIA controller / NS PC97338 (FDC, IR, I/O) PCI 2.1 / 32-bit / 33MHz (EIDE, graphics, PCMCIA, USB, audio, modem) ISA (diskette, serial, parallel, infrared)					
Docking station	None					
Port replicator	ThinkPad Port Replicator with Advanced EtherJet™ / Basic Port Replicator					
PC Card Std slots	2 Type I, 2 Type II, or 1 Type III / CardBus 32-bit / PCMCIA 2.1 / Zoomed video					
USB / serial / parallel	One USB / one 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)					
Other features	APM-aware BIOS / Ultralim AC adapter, barrel, 3-prong, 56 watts					
Video (TV) out	S-Video out connector on side (does not require cable) / Chrontel Ch7004C-T					
MPEG decoder	None (W98 support for MPEG-2 because 300MHz with motion compensation)					
Data/fax modem	56K <sup>22</sup> V.90 / integrated in system / PCI / Lucent 1646 / not voice-capable / conforms to earlier draft specs similar to Mini PCI Type IIIb					
Audio	16-bit SoundBlaster Pro™ support / ESS 1946 / PCI / full duplex					
Speakers	Two Altec Lansing® stereo speakers (1 watt) on display (on front for 15" mod)					
Audio features	Dial volume control (right side) / internal microphone					
Audio in/out jacks	Microphone jack (stereo) / headphone jack (stereo) / line-in jack					
Infrared ports	Infrared port on left side / IrDA 1.1 compatible / up to 4Mbps					
Security	Power-on password / setup password / disk password / security keyhole / security screw for UltraBay FX					
Limited warranty <sup>11</sup>	1 year - carry-in or ThinkPad EasyServ™ <sup>31</sup> (door-to-door depot repair service)					
Service options <sup>15</sup>	On-site <sup>32</sup> , M-F, 8-5, next bus day (72 cities) / serv up to 5 yrs from purchase date					
<b>Color depth</b>	<b>LCD</b>	<b>External Monitor</b>			<b>OPTIONS</b>	
<b>Resolution</b>	<b>TFT</b>	<b>60Hz</b>	<b>75Hz</b>	<b>85Hz</b>		
640x480	16M	16M	16M	16M	- 32MB SO DIMM 100MHz NP SDRAM 20L0253	
800x600	16M	16M	16M	16M	- 64MB SO DIMM 100MHz NP SDRAM 20L0254	
1024x768	16M	16M	16M	16M	- 128MB SO DIMM 100MHz NP SDRAM 20L0255	
1280x1024	--	256	--	--	- 256MB SO DIMM 100MHz NP SDRAM 33L3069	
All models:	- C: drive is FAT16 of 2GB					
	- D: drive is FAT32 of remaining space					
The right bay (UltraBay FX) has a device lock on the bottom of the system and a bay LED which should be off to safely remove a device; it supports:	<ul style="list-style-type: none"> <li>standard diskette/CD-ROM (warm swap with Windows 98)</li> <li>optional DVD/CD-ROM (warm swap; W98)</li> <li>optional second battery (hot swap; W98/NT); same battery as main one</li> <li>optional second disk (cold swap)</li> <li>optional ThinkPad Proven™ solutions<sup>12</sup></li> </ul>					
	<ul style="list-style-type: none"> <li>Basic (ThinkPad 560) Port Replicator 46H4209</li> <li>Port Replicator w/ Advanced EtherJet 05K4872</li> <li>ThinkPad 390/i Series Li-Ion Battery 02K6513</li> <li>Ultralim 56 watt AC Adapter (3-prong) 02K6545</li> <li>6.4GB disk with UltraBay FX adapter 05K8923</li> <li>10GB disk with UltraBay FX adapter 05K8983</li> <li>12GB disk with UltraBay FX adapter 05K9268</li> <li>4X-1X DVD/Diskette (for UltraBay FX) 05K9129</li> <li>CD/Diskette (for UltraBay FX) 05K8986</li> <li>10/100 EtherJet Ready Port CardBus Adapter with 56K modem 34L1301</li> <li>10/100 Ethernet CardBus PC Card 08L3147</li> <li>IBM Portable Drive Bay 37L1511</li> </ul>					
	Pressing F1 during startup brings up IBM BIOS Setup Utility					
<b>WINDOWS 98 PRELOAD<sup>16</sup></b>						
<ul style="list-style-type: none"> <li>Microsoft® Windows® 98</li> <li>Access ThinkPad</li> <li>Online User's Guide</li> <li>ThinkPad Configuration Program</li> <li>ThinkPad Utilities</li> <li>IBM Update Connector</li> <li>RingCentral Fax</li> <li>Ergonomics</li> <li>Intelliquest Registration</li> <li>Puma IntelliSync 97 (infrared)</li> <li>IBM Global Network Dialer</li> <li>Netscape Communicator</li> <li>Lotus® SmartSuite® Millennium<sup>20</sup></li> <li>PC-Doctor</li> <li>ConfigSafe®</li> <li>Norton AntiVirus™ (OEM Version)</li> <li>Universal Management Services</li> <li>Software Selections CD</li> <li>Lotus SmartSuite Millennium CD-ROM</li> <li>Recovery CD-ROM (Windows 98)</li> <li>Recovery CD-ROM (Windows 95)<sup>7</sup></li> </ul>						
<b>WINDOWS NT PRELOAD<sup>16</sup></b>						
<ul style="list-style-type: none"> <li>Microsoft Windows NT® 4.0</li> <li>Service Pack 4</li> <li>ThinkPad Utilities</li> <li>Online User's Guide</li> <li>ThinkPad Configuration Program</li> <li>Ergonomics</li> <li>Intelliquest Registration</li> <li>Puma IntelliSync 97 (infrared)</li> <li>IBM Global Network Dialer</li> <li>Netscape Communicator</li> <li>ConfigSafe</li> <li>Norton AntiVirus (OEM Version)</li> <li>IBM Update Connector</li> <li>SystemSoft CardWizard</li> <li>Universal Management Services</li> <li>Software Selections CD-ROM</li> <li>Lotus SmartSuite Millennium CD-ROM</li> <li>Recovery CD-ROM (Windows NT)</li> </ul>						
<b>FEATURES</b>						
<ul style="list-style-type: none"> <li>Wired for Management 1.1a-compliant</li> <li>DMI 2.0-compliant</li> <li>PC 98-compliant</li> <li>ACPI ready (APM enabled)</li> <li>Wake on LAN® support<sup>28</sup></li> <li>Setup Guide, User's Reference, Windows OS manual, and Quick Reference Card</li> <li>System Status Indicators</li> <li>Plug and Play 1.0a</li> <li>Standby, suspend, and hibernation modes</li> <li>ENERGY STAR-compliant</li> <li>International Warranty Service<sup>14</sup></li> <li>IBM SystemXtra®<sup>35</sup></li> <li>24 hour / 7 day<sup>30</sup> telephone, bulletin board, fax, electronic, and Internet (www.ibm.com/pc/us) support</li> </ul>						

# IBM ThinkPad® 390X (Pentium III) - withdrawn

<b>IBM® ThinkPad®</b>					
Processor	<b>Intel® Mobile Mobile Pentium® III 450 or 500MHz<sup>1</sup> / 100MHz system bus</b>				
Processor features	No upgrade / processor, L2 cache, and memory controller (North Bridge) on Intel Mobile Module (MMC2)				
L2 cache	<b>256KB</b> / at processor speed / sync pipelined burst / ECC / write-back				
Diskette drive	Internal 3.5" 1.44MB / removable from UltraBay™ FX / on right side / integrated with CD-ROM / no external diskette port				
CD-ROM	<b>CD-ROM / 24X-10X<sup>5</sup> speed</b> / ATAPI / bootable / removable from UltraBay FX / on right side / integrated with diskette drive				
DVD-ROM	<i>Option:</i> Removable UltraBay FX option / 4X-1X <sup>6</sup> DVD integrated with a diskette drive				
Type - model	≈ <b>2626-L0U</b>	≈ <b>2626-LNU</b>	≈ <b>2626-L2U</b>	≈ <b>2626-M0U</b>	≈ <b>2626-MNU</b>
Processor / MHz	<b>Pentium III 450MHz</b>	<b>Pentium III 450MHz</b>	<b>Pentium III 450MHz</b>	<b>Pentium III 500MHz</b>	<b>Pentium III 500MHz</b>
Disk - size / read ms	<b>12.0GB<sup>4</sup> / 12ms</b>	<b>12.0GB / 12ms</b>	<b>12.0GB / 12ms</b>	<b>12.0GB / 12ms</b>	<b>12.0GB / 12ms</b>
Preload (see side)	<b>Windows 98 SE</b>	<b>NT 4.0</b>	<b>Windows 2000</b>	<b>Windows 98 SE</b>	<b>NT 4.0</b>
Avail / withdrawn date	Dec 1999 / Oct 2000	Dec 1999 / Oct 2000	Feb 2000 / Oct 2000	Dec 1999 / Jan 2001	Dec 1999 / Jan 2001
Display (diagonal)	<b>14.1" TFT XGA</b>	<b>14.1" TFT XGA</b>	<b>14.1" TFT XGA</b>	<b>15" TFT XGA</b>	<b>15" TFT XGA</b>
Display - size and type	<b>14.1" TFT color 358mm / Active Matrix</b>			<b>15.0" TFT color 381mm / Active Matrix</b>	
Display - technology	<b>XGA / 1024x768 / 20 to 30ms / 120 nits</b>			<b>XGA / 1024x768 / 10 to 30ms / 120 nits</b>	
	<b>16.7 million colors / 150 to 1 contrast</b>			<b>16.7 million colors / 150 to 1 contrast</b>	
Graphics controller	<b>NeoMagic™ MagicMedia256AV™ (NM2200) / 128-bit engine, 256-bit memory interface / 1X AGP / DDC2B / 2.5MB / SGRAM (embedded) / motion compensation / color space conversion / interpolation in X and Y axis / simultaneous LCD and CRT<sup>26</sup> / 150 degree tilt / multiple-monitor support<sup>26</sup></b>				
Memory - std / max	<b>64MB / 512MB<sup>33</sup></b>				
Memory - features	<b>SDRAM</b> / non-parity / 100MHz / PC100-compliant / 3.3 volt / 64-bit / 2 sockets for JEDEC 144-pin SO DIMMs / one socket used by std memory / sockets accessed from bottom via removing cover held by phillips-head screw				
Disk controller	EIDE / PCI 2.1 / one internal disk / disk can be removed to upgrade by customer / supports two internal disks / 13ms read / 14ms write / S.M.A.R.T. <sup>29</sup>				
Keyboard	Full-size 85-key (7 Fn key functions) / palm rest / keyboard slope with tilt feet				
Pointing	TrackPoint® / Press-to-Select / Release-to-Select / dragging / click pace / center button for scrolling (Internet Scroll Bar) or magnifying glass / spare caps				
Dimensions <sup>36</sup>	<b>14.1" mod:</b> 12.4 x 10.2 x 1.8" (228 cu in) <b>15" mod:</b> 12.9 x 10.6 x 1.8" (246 cu)				
Weight <sup>2</sup> (with batt/disk)	<b>14.1" models:</b> 7.7 lbs (3.5 kg) <b>15" models:</b> 7.9 lbs (3.6 kg)				
Case material	PC/ABS plastic				
Battery - type	Li-Ion / intelligent / left side				
Battery - life <sup>10</sup> (1 batt)	<b>14.1" models:</b> 3.7 hrs <b>15" models:</b> 3.3 hrs				
Charge time <sup>10</sup>	<b>14.1" models:</b> 5 hrs on / 2.5 hrs off <b>15" models:</b> 6 hrs on / 3 hrs off				
Architecture	<b>Intel 440BX AGPset / Intel PIIX4E (EIDE, PCI to ISA bridge, USB) / Texas Instruments® T11251B PCMCIA controller / NS PC97338 (FDC, IR, I/O) PCI 2.1 / 32-bit / 33MHz (EIDE, graphics, PCMCIA, USB, audio, modem) ISA (diskette, serial, parallel, infrared)</b>				
Docking station	None				
Port replicator	ThinkPad Port Replicator with Advanced EtherJet™ / Basic Port Replicator				
PC Card Std slots	2 Type I, 2 Type II, or 1 Type III / CardBus 32-bit / PCMCIA 2.1 / Zoomed video				
USB / serial / parallel	<b>One USB</b> / one 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)				
Other features	APM-aware BIOS / Ultrasmil AC adapter, barrel, 3-prong, 56 watts				
Video (TV) out	S-Video out connector on side (does not require cable) / Chrontel Ch7004C-T				
MPEG decoder	None (W98 support for MPEG-2 because 300MHz with motion compensation)				
Data/fax modem	<b>56K<sup>37</sup> V.90</b> / integrated in system / PCI / Lucent 1646 / not voice-capable / conforms to earlier draft specs similar to Mini PCI Type IIIb				
Audio	16-bit SoundBlaster Pro™ support / ESS 1946 / PCI / full duplex				
Speakers	Two Altec Lansing® stereo speakers (1 watt) on display (on front for 15" mod)				
Audio features	Dial volume control (right side) / internal microphone				
Audio in/out jacks	Microphone jack (stereo) / headphone jack (stereo) / line-in jack				
Infrared ports	Infrared port on left side / IrDA 1.1 compatible / up to 4Mbps				
Security	Power-on password / setup password / disk password / security keyhole / security screw for UltraBay FX				
Limited warranty <sup>11</sup>	<b>1 year</b> - carry-in or ThinkPad EasyServ™ <sup>31</sup> (door-to-door depot repair service)				
Service options <sup>15</sup>	On-site <sup>32</sup> , M-F, 8-5, next bus day (72 cities) / serv up to 5 yrs from purchase date				

Color depth	LCD	External Monitor			OPTIONS	
Resolution	TFT	60Hz	75Hz	85Hz		
640x480	16M	16M	16M	16M	- 32MB SO DIMM 100MHz NP SDRAM	20L0253
800x600	16M	16M	16M	16M	- 64MB SO DIMM 100MHz NP SDRAM	20L0254
1024x768	16M	16M	16M	16M	- 128MB SO DIMM 100MHz NP SDRAM	20L0255
1280x1024	--	256	--	--	- 256MB SO DIMM 100MHz NP SDRAM	33L3069
					- Basic (ThinkPad 560) Port Replicator	46H4209
					- Port Replicator w/ Advanced EtherJet	05K4872
					- ThinkPad 390 Li-Ion Battery	02K6513
					- Ultrasmil 56 watt AC Adapter (3-prong)	02K6545
					- 6.4GB disk with UltraBay FX adapter	05K8923
					- 10GB disk with UltraBay FX adapter	05K8983
					- 12GB disk with UltraBay FX adapter	05K9268
					- 4X-1X DVD/Diskette (for UltraBay FX)	05K9129
					- CD/Diskette (for UltraBay FX)	05K8986
					- 10/100 EtherJet Ready Port CardBus Adapter with 56K modem	34L1301
					- 10/100 Ethernet CardBus PC Card	08L3147
					- Smart Card Security Kit	33L5075
					- IBM Portable Drive Bay	37L1511
					- IBM MultiPort USB Hub	00N8215

The right bay (UltraBay FX) has a device lock on the bottom of the system and a bay LED which should be off to safely remove a device; it supports:

- standard diskette/CD-ROM (warm swap with Windows 98)
- optional DVD/CD-ROM (warm swap; W98)
- optional second battery (hot swap; W98/NT); same battery as main one
- optional second disk (cold swap)
- optional ThinkPad Proven™ solutions<sup>12</sup>

Windows 2000 model:  
- C: drive is FAT32 of entire disk

- WINDOWS 98 PRELOAD<sup>16</sup>**
- Microsoft® Windows® 98 Second Edition
  - Access ThinkPad
  - Online User's Guide
  - ThinkPad Configuration Program
  - ThinkPad Utilities
  - IBM Update Connector
  - RingCentral Fax
  - ThinkPad on the Net
  - Intelliquest Registration
  - IBM Global Network Dialer
  - Netscape Communicator
  - Lotus® SmartSuite® Millennium<sup>20</sup>
  - PC-Doctor
  - ConfigSafe®
  - Norton AntiVirus™ (OEM Version)
  - Universal Management Services (web)
  - ◇ Software Selections CD
  - ◇ Lotus SmartSuite Millennium CD-ROM
  - ◇ Recovery CD-ROM (Windows 98)
  - ◇ Recovery CD-ROM (Windows 95)<sup>7</sup>
- WINDOWS 2000 PRELOAD<sup>16</sup>**
- Windows 2000® Professional
  - ThinkPad Utilities
  - Online User's Guide
  - ThinkPad Configuration Program
  - IBM Registration
  - PC-Doctor
  - RingCentral Fax
  - Netscape Communicator
  - ConfigSafe
  - IBM Update Connector
  - SystemSoft CardWizard
  - Norton AntiVirus™ (OEM Version)
  - Universal Management Services (web)
  - ◇ Lotus SmartSuite Millennium CD
  - ◇ Software Selections CD-ROM
  - ◇ Recovery CD-ROM (Windows 2000)
  - ◇ Recovery CD-ROM (Windows NT)<sup>40</sup>

- FEATURES**
- Wired for Management 1.1a-compliant
  - DMI 2.0-compliant
  - PC 98-compliant
  - ACPI ready (APM enabled)
  - Wake on LAN® support<sup>28</sup>
  - Setup Guide, User's Reference, Windows OS manual, and Quick Reference Card
  - System Status Indicators
  - Plug and Play 1.0a
  - Standby, suspend, and hibernation modes
  - ENERGY STAR-compliant
  - International Warranty Service<sup>14</sup>
  - IBM SystemXtra®.<sup>35</sup>
  - 24 hour / 7 day<sup>30</sup> telephone, bulletin board, fax, electronic, and Internet (www.ibm.com/pc/us) support

All trademarks are the property of their respective owners  
≈ = Withdrawn from marketing

No warranties are expressed or implied in this summary  
(390X2) © IBM Corp. January 2001