

IBM ThinkPad 560 (1997 models) - withdrawn

IBM® ThinkPad®:	≧ 560 11.3" Dual Scan SVGA color	≧ 560 12.1" TFT SVGA color	ThinkPad 560 key features: <ul style="list-style-type: none"> ⊕ Next generation ultraportable notebook ⊕ Slim: 1.2 inches ⊕ Lightweight: 4.1 pounds ⊕ Full size keyboard ⊕ Pentium 133/66 MHz ⊕ 11.3" Dual Scan SVGA or 12.1" TFT SVGA ⊕ PCI bus ⊕ 8 MB EDO memory
Processor type	Pentium® 133/66 MHz / 64 bit to transfers to memory		
Processor upgrade	None		
L2 cache	None		
Diskette drive	External 3.5" 1.44 MB (connects to left side) / includes case with a cable		
External FDD port	External FDD port (works with standard external diskette; no kit reqd)		
CD-ROM drive	None (CD-ROM drive as OEM option via PCMCIA or parallel port)		
Code name	Kinzie 3		
Price			
Type - model	2640-10U	2640-20U	
Preload (see side)	Windows 95 OSR2		
Avail / withdrawn date	February 1997 / January 1998		
Disk - size / ms	2.1 GB / 14 ms / DMA Mode 2 or PIO Mode 4		
Disk controller	EIDE / busmaster / PCI 2.1 / supports one internal disk		
Display - size and type	11.3" Dual Scan SVGA color 12.1" TFT SVGA color		
Display - technology	11.3" SVGA color / 640 x 480 or 800 x 600 256 simultaneous colors / Dual Scan / 30 to 1 contrast ratio	12.1" SVGA color / 640 x 480 or 800 x 600 / 65,536 sim colors Black Matrix TFT - active matrix / 100 to 1 contrast ratio	
Graphics - controller	Trident™ CYBER9382 / 64 bit SVGA accelerator / 1 MB fast page DRAM / 70 ns		
Graph - arch/data path	PCI 2.1 / 32 bit / 32 bit path to memory / DCI, DirectDraw, EnDIVE support		
Graphics - features	Simultaneous LCD and CRT / 135 degree tilt		
Graphics - external	External SVGA to 1024 x 768 with 256 colors		
Memory - std / max	8 MB / 40 MB (72 MB w/ ThinkPad Proven option)		
Memory - features	70 ns / non-parity / 3.3 volt / EDO		
Memory - upgrade	1 socket for one JEDEC 144 pin EDO SO DIMM of 8, 16, or 32 MB		
Keyboard / # of keys	Full size alp/num / 85 keys (6 Fn key functions)		
Keyboard slope	Large palm rest / keyboard remains flat (no sloop) / opt P Replicator adds slope		
Pointing device	TrackPoint III™ / no drag lock keys		
Palm rest	Integrated palm rest / external keyboard support (with optional cable 54G0441)		
Dimensions	11.7 x 8.7 x 1.22" (124 cubic inches)		
Weight	4.12 pounds (1.87 kg)	4.10 pounds (1.86 kg)	
Battery - type	Lithium Ion / intelligent		
Battery - life (1 batt)	3 hours		
Charge time - on / off	2.5 to 3.5 hrs / 1.5 hrs		
Architecture	ISA (audio, diskette, serial, parallel, infrared) PCI 2.1 / 32 bit / 33 MHz (EIDE, graphics, PCMCIA) / Mobile Triton 82430MX		
Docking Station	None		
Port replicator	ThinkPad 560 Port Replicator		
PCMCIA™ 2.1 slots	2 Type I or 2 Type II or 1 Type III		
Serial / parallel ports	One 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)		
Other features	Universal AC Adapter 2 prong (35 watts) with barrel connector (slim) / APM-aware BIOS / Selectable boot IBM BIOS		
Video in/out	None		
MPEG decoder	None		
DSP function	None		
Data/fax modem	None		
Audio support	16 bit audio chip / 18 voice MIDI FM synthesis / ESS1688 Internal stereo speakers / .5 watt / rotary volume control / internal microphone		
Jacks	Input jack (3.5 mm) / Output jack (3.5 mm)		
Telephone	None		
Infrared ports	Infrared port (left side) / IrDA 1.0 compatible / up to 115 Kbps		
Security	Power-on password / hard disk password / Locking device keyhole on back (Kensington™ cable lock) / Personalization screen at startup		
Preinstalled software	Windows 95 with applications (listed on right)		
Warranty	1 year - ThinkPad EasyServ (optional Overnight Repair Option) or carry-in		
Easy-Setup is entered by holding F1 when turning on.			
Fn + F2 = Battery gauge			
Fn + F3 = Standby			
Fn + F4 = Suspend			
Fn + F7 = LCD/CRT/Simultaneous			
Fn + F11 = Power mgmt			
Fn + F12 = Hibernation			
Hardware acceleration of "Video for Windows™" is integrated into the 9382 graphics controller; interpolation in X and Y axis; color space conversion when DCI enabled			
System does not have non-disruptive battery exchange. Battery can be changed while system is off, in hibernation, or under AC power.			
	OPTIONS		
	<ul style="list-style-type: none"> - Disks: (365/760 IDE disks not supported) 1.08 GB HDD II EIDE 13 ms 46H4208 2.1 GB HDD 14 ms 45H8783 4.0 GB HDD 13 ms 02K0501 - ThinkPad 560 Port Replicator 46H4209 - ThinkPad 560 Li-Ion Battery Pack 46H4206 - 35 watt AC Adapter - barrel/3 prong 85G6719 - 35 watt AC Adapter (slim, 2 pin) 76H0139 - 8 MB SO DIMM 3.3v NP EDO 64 bit 92G7340 - 16 MB SO DIMM 3.3v NP EDO 64 bit 92G7341 - 32 MB SO DIMM 3.3v NP EDO 64 bit 92G7342 - 8-20 x Portable CD-ROM 1969010 - 8-20 x Portable Stereo CD-ROM 1969011 - Other options from ThinkPad Proven partners 		
	Disk is not removable (like 755/760 systems), but it can be upgraded via a dealer or service center (not customer installable).		
	FEATURES OF 560 MODELS		
	<ul style="list-style-type: none"> Quick Setup Guide Plug and Play 1.0a Standby, suspend, safe suspend, and hibernation modes US EPA Energy Star compliant Personalized nameplate indentation Personalization screen at startup International Warranty Service IBM System Care Program 24 hour / 7 day telephone, bulletin board, fax, electronic, and Internet (http://www.pc.ibm.com) support IBM and dealer warranty/service Online Housecall (remote diagnostics) 		

ThinkPad EasyServ™: customer calls 1-800-772-2227, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). Overnight repair option in US available for \$99.

All trademarks are the property of their respective owners
No warranties are expressed or implied in this summary
(56097) Compiled by Roger Dodson, IBM. December 1997