

IBM ThinkPad® 600 - September 1998 - withdrawn

IBM® ThinkPad®		WINDOWS 98 PRELOAD¹⁶																																																																							
Processor type/path	Intel® Mobile Pentium® II 300MHz ¹ / 66MHz system bus	<ul style="list-style-type: none"> - Microsoft® Windows® 98 • Online User's Guide • ThinkPad Utilities • ThinkPad Configuration Program • RingCentral • Ergonomics • IBM Product Registration • Puma IntelliSync 97 (infrared) • IBM Global Network Dialer • Netscape Navigator web browser • IBM Update Connector • Artisoft ConfigSafe • Norton AntiVirus ◇ Lotus® SmartSuite Millennium CD-ROM ◇ Customization Center CD-ROM ◇ Product Recovery CD-ROM (with boot diskette) 																																																																							
Processor features	No upgrade / processor, L2 cache, and mem cntr (North Bridge) on Mobile Module																																																																								
L2 cache	512KB / sync pipelined burst / ECC / 150MHz (half speed)																																																																								
Diskette (removable)	3.5" 1.44MB / use in UltralimBay / ships in external diskette enclosure with a cable																																																																								
External FDD port	External diskette port on right side (can use simultaneously with internal CD-ROM)																																																																								
CD-ROM (removable)	5.25" CD-ROM / 24X-10X ⁵ speed / bootable / warm swap																																																																								
DVD ¹⁹ (removable)	Option: 2X ⁵ DVD-ROM drive / removable UltralimBay option / warm swap																																																																								
SuperDisk (LS-120)	Option: Removable UltralimBay option / supports 1.44MB and 120MB diskette																																																																								
Type - model	2645-45U 2645-85U All models:																																																																								
Preload (see side)	Windows 98 Windows NT 4.0 - C: drive is FAT16 of 2GB																																																																								
Disk (removable)	5.1GB ⁴ / 12ms (read); 13ms (write) / upgradeable																																																																								
Avail / withdr date	September 1998 / June 1999																																																																								
Memory	64MB std / 288MB ²⁵ maximum / SDRAM / non-parity / 66MHz / 3.3v Two 144-pin sockets / 32MB on planar and 1 socket used by 32MB SO-DIMM / 1 socket available / sockets accessed by removing screw on bottom	WINDOWS NT PRELOAD¹⁶ <ul style="list-style-type: none"> - Windows NT® Workstation 4.0 • Online User's Guide • ThinkPad Utilities • ThinkPad Configuration Program • Puma IntelliSync 97 (infrared) • ConfigSafe • IBM Global Network Dialer • Netscape Navigator web browser • Norton AntiVirus (OEM Version) • Ergonomics • IBM Product Registration • SystemSoft CardWizard ◇ Lotus SmartSuite Millennium CD-ROM ◇ Customization CD-ROM (apps/drivers) ◇ Product Recovery CD-ROM (with boot diskette) 																																																																							
Display	13.3" (337.8mm) TFT color / Active Matrix / XGA / 75ms / 100 to 1 contrast ratio / 640x480 or 800x600 (16.7 million colors), 1024x768 (65,536 colors) / 150 nits (AC), 90 nits (battery) / 180 degree tilt																																																																								
Graphics - controller	NeoMagic™ MagicGraph128XD™ (NM2160B) / 128-bit SVGA accelerator																																																																								
Graphics - arch	2MB / iDRAM™ (embedded) / Zoomed Video support																																																																								
Graphics - features	Support for DirectX 5.0, DDC2B, color space conversion																																																																								
Graphics - external	External SVGA to 1024x768 with 65,536 colors (800x600 with 16.7 million colors)																																																																								
Disk	Left front / removable via coin screw or 2.5mm Allen wrench / SMART / upgradeable																																																																								
Disk controller	Enhanced IDE / busmaster / PCI 2.1 / South Bridge / PIIX4 DMA Mode 2, Ultra DMA/33, or PIO Mode 4 / supports 2nd disk inopt HDD adapter																																																																								
Keyboard / Fn keys	Full size alp/num keys / 9 Fn key functions / integrated palm rest																																																																								
Keyboard slope	Flat keyboard (does not lift up) / optional Port Replicator adds slope																																																																								
Pointing device	TrackPoint® / Press-to-Select / Release-to-Select / dragging / click pace / center click button for scrolling or magnifying glass / suspension top / spare caps																																																																								
Dimensions ³⁶	Approximately 11.8 x 9.4 x 1.4" (155 cubic inches); 300mm x 240mm x 36.5mm																																																																								
Weight ²	5.01 lbs (2.27 kg) with travel cover and battery only																																																																								
Battery - type	Lithium Ion / intelligent / remove from base / locked with latch																																																																								
Battery - life ¹⁰	3.0 hrs / no non-disruptive battery exchange																																																																								
Charge time - on / off	2 to 3 hrs / 1.5 to 2.5 hrs																																																																								
Architecture	Intel 440BX and PIIX4 (EIDE, ISA Bridge, USB) PCI 2.1 / 32-bit / 33MHz (EIDE, graphics, CardBus, USB, ext expansion) TI PCI1250A for CardBus / LM75 digital thermometer / PC97338 Super I/O / ISA (audio, modem, diskette, serial, parallel, infrared, ext expansion)	System does not have non-disruptive battery exchange. Battery can be changed while system is off, in hibernation, or under AC power. ThinkPad 600 supported disks: - 3.2GB 13ms read/14ms write 9.5 mm PIO Mode 4 or Ultra DMA/33 - 4.0GB 13ms read/14ms write 12.5 mm PIO Mode 4 or Ultra DMA/33 - 5.1GB 12ms read/13ms write 12.5 mm PIO Mode 4 or Ultra DMA/33 - 6.4GB 13ms read/14ms write 12.5 mm PIO Mode 4 or Ultra DMA/33																																																																							
Port replicator	SelectaBase 600 / PC Card Enabler ¹⁷ / PC Card Enabler with Advanced EtherJet ¹⁷																																																																								
Docking Station	SelectaDock III / SelectaDock I and II																																																																								
PC Card Std slots	2 Type I, 2 Type II, or 1 Type III / CardBus 32-bit / PCMCIA 2.1 / Zoomed Video																																																																								
USB / serial / parallel	One USB / one 9 pin serial; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)																																																																								
Other features	APM-aware BIOS / AC Adapter barrel, 3 prong (56 watts) / Selectable boot																																																																								
Video in/out	None																																																																								
MPEG decoder	None (software support for MPEG-1 in Windows 98)																																																																								
Data/fax modem	56K (x2, upgradeable to v.90 ⁹) / 14.4Kbps fax / telephony / voice-capable integrated Mwave® 3780i DSP / international programmable DAA / modem cable																																																																								
Audio support	CS4237B / 16-bit / SRS 3D audio / FM synthesis Int stereo speakers (front) / .5 watt / Fn+PgUp and PgDn (volume) / int microphone Input jack (3.5 mm) / Output jack (3.5 mm) / full duplex																																																																								
Jacks	Infrared port (on right) / IrDA 1.1 compatible / up to 4Mbps																																																																								
Infrared ports																																																																									
Security	Power-on password / hard disk password / supervisor password / security keyhole / personalization / phillips-head screw on base for memory / opt Allen screw for disk																																																																								
Limited warranty ¹¹	3 year - carry-in or ThinkPad EasyServ™ ³¹ Rapid Depot Repair (3 business day average turnaround)																																																																								
Service options ¹⁵	On-site ³² , M-F, 8-5, next bus day (72 cities) / service agreements up to 5 years from purchase date																																																																								
	<table border="0"> <tr> <td>- 56K PC Card Modem Kit</td> <td>04K0052</td> <td>- 6.4GB disk, 13ms, Ultra DMA/33</td> <td>02K0518</td> </tr> <tr> <td>- 56K PC Card Modem/Cellular capab</td> <td>02K4196</td> <td>- 10GB disk, 12ms, Ultra DMA/33</td> <td>36L9293</td> </tr> <tr> <td>- V.90 PC Card Modem with XJACK²⁴</td> <td>10L7393</td> <td>- SelectaBase 600</td> <td>12J2467</td> </tr> <tr> <td>- EtherJet PC Card Combo</td> <td>72H4534</td> <td>- PC Card Enabler¹⁷</td> <td>83H6741</td> </tr> <tr> <td>- IBM 10/100 EtherJet CardBus PC Cd</td> <td>08L3147</td> <td>- PC Card Enabler with EtherJet™¹⁷</td> <td>05K4820</td> </tr> <tr> <td>- UltralimBay HDD adapter (for 2nd disk)</td> <td>05K5336</td> <td>- SelectaDock I</td> <td>3547001</td> </tr> <tr> <td>- SuperDisk LS-120 (UltralimBay)</td> <td>20L1929</td> <td>- SelectaDock II</td> <td>3547002</td> </tr> <tr> <td>- 2X DVD Drive (UltralimBay)</td> <td>05K8890</td> <td>- SelectaDock III¹⁷</td> <td>3547003</td> </tr> <tr> <td></td> <td></td> <td>- 56 watt AC Adapter (barrel; 3 prong)</td> <td>83H6739</td> </tr> <tr> <td></td> <td></td> <td>- 24X-10X CD-ROM (UltralimBay; includes external diskette enclosure)</td> <td>12J2471</td> </tr> <tr> <td></td> <td></td> <td>- 16MB SO DIMM 3.3v NP SDRAM</td> <td>76H0293</td> </tr> <tr> <td></td> <td></td> <td>- 32MB SO DIMM 3.3v NP SDRAM</td> <td>76H0294</td> </tr> <tr> <td></td> <td></td> <td>- 64MB SO DIMM 3.3v NP SDRAM</td> <td>76H0295</td> </tr> <tr> <td></td> <td></td> <td>- 64MB SO DIMM 3.3v NP SDRAM</td> <td>20L0241</td> </tr> <tr> <td></td> <td></td> <td>- 128MB SO DIMM 3.3v NP SDRAM</td> <td>01K1150</td> </tr> <tr> <td></td> <td></td> <td>- ThinkPad 600 Li-Ion Battery</td> <td>12J2464</td> </tr> <tr> <td></td> <td></td> <td>- External Battery Charger</td> <td>02K6499</td> </tr> <tr> <td></td> <td></td> <td>- Zip 100MB UltralimBay Drive</td> <td>37L1504</td> </tr> </table>	- 56K PC Card Modem Kit	04K0052	- 6.4GB disk, 13ms, Ultra DMA/33	02K0518	- 56K PC Card Modem/Cellular capab	02K4196	- 10GB disk, 12ms, Ultra DMA/33	36L9293	- V.90 PC Card Modem with XJACK ²⁴	10L7393	- SelectaBase 600	12J2467	- EtherJet PC Card Combo	72H4534	- PC Card Enabler ¹⁷	83H6741	- IBM 10/100 EtherJet CardBus PC Cd	08L3147	- PC Card Enabler with EtherJet™ ¹⁷	05K4820	- UltralimBay HDD adapter (for 2nd disk)	05K5336	- SelectaDock I	3547001	- SuperDisk LS-120 (UltralimBay)	20L1929	- SelectaDock II	3547002	- 2X DVD Drive (UltralimBay)	05K8890	- SelectaDock III ¹⁷	3547003			- 56 watt AC Adapter (barrel; 3 prong)	83H6739			- 24X-10X CD-ROM (UltralimBay; includes external diskette enclosure)	12J2471			- 16MB SO DIMM 3.3v NP SDRAM	76H0293			- 32MB SO DIMM 3.3v NP SDRAM	76H0294			- 64MB SO DIMM 3.3v NP SDRAM	76H0295			- 64MB SO DIMM 3.3v NP SDRAM	20L0241			- 128MB SO DIMM 3.3v NP SDRAM	01K1150			- ThinkPad 600 Li-Ion Battery	12J2464			- External Battery Charger	02K6499			- Zip 100MB UltralimBay Drive	37L1504
- 56K PC Card Modem Kit	04K0052	- 6.4GB disk, 13ms, Ultra DMA/33	02K0518																																																																						
- 56K PC Card Modem/Cellular capab	02K4196	- 10GB disk, 12ms, Ultra DMA/33	36L9293																																																																						
- V.90 PC Card Modem with XJACK ²⁴	10L7393	- SelectaBase 600	12J2467																																																																						
- EtherJet PC Card Combo	72H4534	- PC Card Enabler ¹⁷	83H6741																																																																						
- IBM 10/100 EtherJet CardBus PC Cd	08L3147	- PC Card Enabler with EtherJet™ ¹⁷	05K4820																																																																						
- UltralimBay HDD adapter (for 2nd disk)	05K5336	- SelectaDock I	3547001																																																																						
- SuperDisk LS-120 (UltralimBay)	20L1929	- SelectaDock II	3547002																																																																						
- 2X DVD Drive (UltralimBay)	05K8890	- SelectaDock III ¹⁷	3547003																																																																						
		- 56 watt AC Adapter (barrel; 3 prong)	83H6739																																																																						
		- 24X-10X CD-ROM (UltralimBay; includes external diskette enclosure)	12J2471																																																																						
		- 16MB SO DIMM 3.3v NP SDRAM	76H0293																																																																						
		- 32MB SO DIMM 3.3v NP SDRAM	76H0294																																																																						
		- 64MB SO DIMM 3.3v NP SDRAM	76H0295																																																																						
		- 64MB SO DIMM 3.3v NP SDRAM	20L0241																																																																						
		- 128MB SO DIMM 3.3v NP SDRAM	01K1150																																																																						
		- ThinkPad 600 Li-Ion Battery	12J2464																																																																						
		- External Battery Charger	02K6499																																																																						
		- Zip 100MB UltralimBay Drive	37L1504																																																																						
	<p>The right bay (UltralimBay) has LED on release latch to provide status; supports warm swapping:</p> <ul style="list-style-type: none"> • std diskette and weight-saver bezel • std or optional CD-ROM • optional DVD drive¹⁹ • optional Zip 100MB drive (cold swap) • opt LS-120 SuperDisk drive (cold swap) • opt HDD adapter; second disk (cold swap) • optional ThinkPad Proven™ solutions¹² 	FEATURES Wired for Management 1.1a PC 97 compliant DMI 2.0 compliant DMI instrumentation (thermal monitoring) ACPI ready (APM enabled) Wake on LAN® support²⁸ C: is 1.99GB, D: is up to 1.99GB, etc. Setup Guide, User's Reference, Quick Reference and Service Information Card, Options by IBM Catalog, Windows 98 or NT manual Plug and Play 1.0a Standby, suspend, safe suspend, and hibernation modes ENERGY STAR compliant International Warranty Service ¹⁴ IBM SystemXtra³⁵ 24 hour / 7 day telephone ³⁰ , bulletin board, fax, electronic, and Internet (www.ibm.com/pc/us) support																																																																							

All trademarks are the property of their respective owners

No warranties are expressed or implied in this summary (60098) © IBM Corp. July 1999