

# IBM ThinkPad® 600E - withdrawn

<b>IBM® ThinkPad®</b>		<b>WINDOWS 98 PRELOAD<sup>16</sup></b>		
Processor	<b>Intel® Mobile Pentium® II 300MHz<sup>1</sup></b> / 66MHz system bus		<ul style="list-style-type: none"> <li>- Microsoft® Windows® 98</li> <li>• ThinkPad Utilities</li> <li>• Online User's Guide</li> <li>• ThinkPad Configuration Program</li> <li>• Ergonomics</li> <li>• IBM Registration</li> <li>• RingCentral Fax</li> <li>• Puma IntelliSync 97 (infrared)</li> <li>• IBM Global Network Dialer</li> <li>• Netscape Navigator web browser</li> <li>• ThinkPad on the Net (TCC CD)</li> <li>• ConfigSafe</li> <li>• Norton AntiVirus (OEM Version)</li> <li>• Mediamatics DVD Express</li> <li>• IBM Update Connector</li> <li>◇ Lotus SmartSuite Millennium CD-ROM</li> <li>◇ Customization Center CD-ROM</li> <li>◇ Recovery CD-ROM (with boot diskette)</li> </ul>	
Processor features	No upgrade / processor, L2 cache, and mem cntr (North Bridge) on Mobile Module			
L2 cache	<b>512KB</b> / sync pipelined burst / ECC / 150MHz (half speed)			
Diskette (removable)	3.5" 1.44MB / use in UltraslimBay™ / ships in external diskette enclosure with a cable			
External FDD port	External diskette port on right side (can use simultaneously with internal DVD)			
CD-ROM (removable)	Option: <b>CD-ROM / 24X-10X<sup>5</sup> speed</b> / bootable / warm swap			
DVD (removable)	EIDE (ATAPI) / PIO Mode 4 for W95; DMA Mode 2 for NT / use in UltraslimBay			
SuperDisk (LS-120)	Std or option: 2X <sup>5</sup> DVD-ROM / removable from UltraslimBay / warm swap			
Type - model	<b>2645-55U</b>	<b>2645-A5U (AAP)</b>		All models:
Preload (see side)	<b>Windows 98</b>	<b>Blank</b> (no disk)		- C: drive is FAT16 of 2GB
Disk (removable)	<b>6.4GB<sup>4</sup> / 13/14ms</b>	<b>None</b>	- D: drive is FAT32 of remaining space	
DVD-ROM drive	<b>DVD-ROM</b>	<b>None</b>		
Avail / withdr date	Nov 1998 / Mar 1999	Nov 1998 / Mar 1999		
Memory	<b>64MB</b> std / 288MB <sup>25</sup> max / <b>32MB</b> std / 288MB max			
	<b>SDRAM</b> / non-parity / 66MHz / 3.3v / sockets accessed by removing screw on base			
	Two 144-pin sockets / 32MB on planar / 1 or 2 sockets available / for 64MB model, one socket used by 32MB SO-DIMM			
Display	<b>13.3"</b> (337.8mm) <b>TFT color</b> / Active Matrix / XGA / 75ms / 100 to 1 contrast ratio / 640x480, 800x600, or 1024x768 (up to 16.7 million colors) / 150 nits (AC), 90 nits (battery) / 180 degree tilt			
Graphics - controller	<b>NeoMagic™ MagicMedia256AV™ (NM2200) / Accelerated Graphics Port 2.5MB</b> / SGRAM (embedded) / 128-bit engine, 256-bit memory interface / AGP-1x			
Graphics - features	<b>Motion compensation</b> / color space conversion / interpolation in X and Y axis			
Graphics - external	Multiple-monitor support <sup>26</sup> for Windows 98 / DDC2B / Direct3D			
Disk	External SVGA to 1024x768x16.7 million colors at 85Hz and 1280x1024x256 colors			
Disk controller	Left front / removable via coin screw or 2.5mm Allen wrench / SMART / upgradeable			
Keyboard / Fn keys	Enhanced IDE / busmaster / PCI 2.1 / South Bridge / PIIX4E			
Keyboard slope	DMA Mode 2, Ultra DMA/33, or PIO Mode 4 / supports 2nd disk in opt HDD adapter			
Pointing device	Full size alp/num keys / 10 Fn key functions / integrated palm rest			
Dimensions <sup>36</sup>	Flat keyboard (does not lift up) / optional Port Replicator adds slope			
Weight <sup>2</sup>	<b>TrackPoint®</b> / Press-to-Select / Release-to-Select / dragging / click pace / center click button for scrolling or magnifying glass / suspension top / spare caps			
Battery - type	Approximately 11.8 x 9.4 x 1.4" (155 cubic inches); 300mm x 240mm x 36.5mm			
Battery - life <sup>10</sup>	4.99 lbs (2.27 kg) with travel cover and battery only			
Charge time - on / off	Lithium Ion / intelligent / remove from base / locked with latch			
Architecture	3.0 hrs / no non-disruptive battery exchange / supports 2nd battery in UltraslimBay			
Port replicator	2 to 3 hrs / 1.5 to 2.5 hrs			
Docking Station	Intel <b>440BX AGPset</b> / Intel 82371EB <b>PIIX4E</b> (EIDE, ISA Bridge, USB) /			
PC Card Std slots	TI® PCI1251 for CardBus / AGP for graphics / LM75 digital thermometer			
USB / serial / parallel	PCI 2.1 / 32-bit / 33MHz (EIDE, CardBus, audio, USB, ext expansion)			
Other features	PC97338 Super I/O / ISA (audio, modem, diskette, serial, parallel, infrared, ext exp)			
Video out	<b>SelectaBase 600</b> / PC Card Enabler <sup>17</sup> / PC Card Enabler with Advanced EtherJet <sup>17</sup>			
MPEG decoder	<b>SelectaDock III</b> / SelectaDock I and II			
Data/fax modem	2 Type I, 2 Type II, or 1 Type III / CardBus 32-bit / PCMCIA 2.1 / Zoomed Video			
Audio support	One USB / one 9 pin serial; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)			
Jacks	APM-aware BIOS / AC Adapter barrel, 3 prong (56 watts) / Selectable boot			
Infrared ports	Video out (composite) / cable ships standard with RCA jack / Chrontel CH7004			
Security	None (W98 support for MPEG-2 because 300MHz with motion compensation)			
Limited warranty <sup>11</sup>	<b>56K</b> / v.90 <sup>22</sup> / 14.4Kbps fax / telephony / voice-capable / integrated Mwave® 3780i DSP / international programmable DAA / modem cable			
Service options <sup>15</sup>	CS4239: ISA / SRS 3D audio / FM synthesis / 16-bit playback and record			
	CS4610: PCI / decodes AC3 into stereo / MPEG-2 audio decoding / accel of DirectX			
	Int stereo speakers (front) / .5 watt / Fn+PgUp and PgDn (volume) / int microphone			
	Input jack (3.5 mm) / Output jack (3.5 mm) / full duplex			
	Infrared port (on right) / IrDA 1.1 compatible / up to 4Mbps			
	Power-on password / hard disk password / supervisor password / security keyhole / personalization / phillips-head screw on base for memory / opt Allen screw for disk			
	<b>3 year</b> - carry-in or ThinkPad EasyServ™ <sup>31</sup> Rapid Depot Repair (3 business day average turnaround			
	On-site <sup>32</sup> , M-F, 8-5, next bus day (72 cities) / serv up to 5 yrs from purchase date			
	- 56K PC Card Modem Kit	04K0052	- 6.4GB disk, 13ms, Ultra DMA/33	
	- 56K PC Card Modem/Cellular capab	02K4196	- 10GB disk, 12ms, Ultra DMA/33	
	- V.90 PC Card Modem with XJACK <sup>24</sup>	10L7393	- <b>SelectaBase 600</b>	
	- 10/100 EtherJet CardBus with 56K modem	08L3167	- PC Card Enabler <sup>17</sup>	
	- IBM 10/100 EtherJet CardBus PC Cd	08L3147	- PC Card Enabler with EtherJet™ <sup>17</sup>	
	- UltraslimBay HDD adapter (for 2nd disk)	05K5336	- SelectaDock I	
	- SuperDisk LS-120 (UltraslimBay)	20L1929	- SelectaDock II	
	- 2X DVD Drive (UltraslimBay)	05K8890	- <b>SelectaDock III<sup>17</sup></b>	
	- Zip 100MB UltraslimBay Drive	37L1504	- 56 watt AC Adapter (barrel; 3 prong)	
	- UltraslimBay Battery (600E only)	02K6504	- <b>24X-10X CD-ROM</b> (UltraslimBay; includes external diskette enclosure)	
	- ThinkPad 600 Li-Ion Battery	12J2464	- <b>32MB SO DIMM 3.3v NP SDRAM</b>	
	- External Battery Charger	02K6499	- <b>64MB SO DIMM 3.3v NP SDRAM</b>	
	- ThinkPad Proven™ solutions <sup>12</sup> (visit <a href="http://www.ibm.com/pc/us/thinkpad/proven">www.ibm.com/pc/us/thinkpad/proven</a> )		- <b>128MB SO DIMM 3.3v NP SDRAM</b>	
			<b>02K0518</b>	
			<b>36L9293</b>	
			<b>12J2467</b>	
			<b>83H6741</b>	
			<b>05K4820</b>	
			<b>3547001</b>	
			<b>3547002</b>	
			<b>3547003</b>	
			<b>83H6739</b>	
			<b>12J2471</b>	
			<b>76H0294</b>	
			<b>20L0241</b>	
			<b>01K1150</b>	
<b>FEATURES</b>				
<b>PC 97 compliant</b>				
<b>DMI 2.0 compliant</b>				
DMI instrumentation (thermal monitoring)				
<b>ACPI ready</b> (APM enabled)				
<b>Wired for Management 1.1a</b>				
<b>Wake on LAN™ support<sup>28</sup></b>				
Setup Guide, User's Reference, Quick Reference and Service Information Card, Options by IBM Catalog, Windows 98 manual				
Plug and Play 1.0a				
Standby, suspend, safe suspend, and hibernation modes				
ENERGY STAR compliant				
International Warranty Service <sup>14</sup>				
<b>IBM SystemXtra™<sup>35</sup></b>				
24 hour / 7 day telephone <sup>30</sup> , bulletin board, fax, electronic, and Internet ( <a href="http://www.ibm.com/pc/us">www.ibm.com/pc/us</a> ) support				

All trademarks are the property of their respective owners

No warranties are expressed or implied in this summary (600E) © IBM Corp. April 1999

# IBM ThinkPad® 600E (1999) - withdrawn

<b>IBM® ThinkPad®</b>		<b>WINDOWS 98 PRELOAD<sup>16</sup></b>				
Processor	Intel® Mobile Pentium® II 300PE or 366MHz <sup>1</sup> / 66MHz system bus					<ul style="list-style-type: none"> <li>Microsoft® Windows® 98</li> <li>ThinkPad Utilities</li> <li>Online User's Guide</li> <li>ThinkPad Configuration Program</li> <li>Ergonomics</li> <li>IBM Registration</li> <li>RingCentral</li> <li>Puma IntelliSync 97 (infrared)</li> <li>IBM Global Network Dialer</li> <li>Netscape Communicator</li> <li>Lotus SmartSuite Millennium<sup>20</sup></li> <li>Universal Management Agent</li> <li>ThinkPad on the Net</li> <li>ConfigSafe®</li> <li>Norton AntiVirus (OEM Version)</li> <li>Mediamatics DVD Express (5AU only)</li> <li>IBM Update Connector</li> <li>Access ThinkPad</li> <li>Software Selections CD-ROM</li> <li>Recovery CD-ROM (Windows 98)</li> <li>Recovery CD-ROM (Windows 95)<sup>7</sup></li> </ul>
Processor features	No upgrade / processor, L2 cache, and mem cntr (North Bridge) on Mobile Module					
L2 cache	256KB / onboard (full speed) / sync pipelined burst / write-back / ECC					
Diskette (removable)	3.5" 1.44MB / use in UltralimBay™ / ships in external diskette enclosure with a cable					
External FDD port	External diskette port on right side (can use simultaneously with internal CD/DVD)					
CD-ROM (removable)	Std or option: <b>CD-ROM / 24X-10X<sup>5</sup></b> speed / bootable / removable from UltralimBay					
DVD (removable)	Std or option: <b>DVD-ROM / bootable / removable from UltralimBay</b>					
Type - model	<b>2645-3AU</b>	<b>2645-4AU</b>	<b>2645-8AU</b>	<b>2645-5AU</b>	<b>2645-AAU</b>	
Processor	<b>PII 300PEMHz</b>	<b>PII 366MHz</b>	<b>PII 366MHz</b>	<b>PII 366MHz</b>	<b>PII 366MHz</b>	
Preload (see side)	<b>Windows 98</b>	<b>Windows 98</b>	<b>Windows NT</b>	<b>Windows 98</b>	<b>Blank (no disk)</b>	
CD or DVD-ROM	<b>CD-ROM</b>	<b>CD-ROM</b>	<b>CD-ROM</b>	<b>DVD-ROM</b>	<b>Optional</b>	
Disk (removable)	<b>4.0GB<sup>4</sup> / 13/14ms</b>	<b>6.4GB / 13/14ms</b>			<b>None</b>	
Avail / withdraw date	Mar 1999 / Dec 99	Mar 99 / Mar 00			Mar 99 / Feb 00	
Memory (std / max)	<b>32MB / 288MB</b> / <b>64MB</b> std / 288MB <sup>25</sup> max					
	SDRAM / non-parity / 66MHz / 3.3v / sockets accessed by removing screw on base					
	Two 144-pin sockets / 32MB on planar / 1 or 2 sockets available / for 64MB model, one socket used by 32MB SO-DIMM					
Display	<b>13.3"</b> (337.8mm) <b>TFT color</b> / Active Matrix / XGA / 75ms / 100 to 1 contrast ratio / 640x480, 800x600, or 1024x768 (up to 16.7 million colors) / 150 nits (AC), 90 nits (battery) / 180 degree tilt					
Graphics - controller	<b>NeoMagic™ MagicMedia256AV™</b> (NM2200) / <b>Accelerated Graphics Port</b>					
Graphics - features	<b>2.5MB</b> / SGRAM (embedded) / 128-bit engine, 256-bit memory interface / AGP 1X					
Graphics - external	<b>Motion compensation</b> / color space conversion / interpolation in X and Y axis					
	Multiple-monitor support <sup>26</sup> for Windows 98 / simultaneous LCD and CRT <sup>26</sup> / DDC2B					
Disk	External SVGA to 1024x768x16.7 million colors at 85Hz and 1280x1024x256 colors					
Disk controller	Left front / removable via coin screw or 2.5mm Allen wrench / SMART <sup>29</sup> / upgradeable					
Keyboard / Fn keys	Enhanced IDE / busmaster / PCI 2.1 / South Bridge / PIIX4E					
Keyboard slope	DMA Mode 2, Ultra DMA/33, or PIO Mode 4 / supports 2nd disk in opt HDD adapter					
Pointing device	Full size alp/num keys / 10 Fn key functions / integrated palm rest					
	Flat keyboard (does not lift up) / optional Port Replicator adds slope					
Dimensions <sup>36</sup>	<b>TrackPoint®</b> / Press-to-Select / Release-to-Select / dragging / click pace / center click button for scrolling or magnifying glass / suspension top / spare caps					
Weight <sup>2</sup>	Approximately 11.8 x 9.4 x 1.4" (155 cubic inches); 300mm x 240mm x 36.5mm					
Battery - type	4.99 lbs (2.26 kg) with travel cover and battery only					
Battery - life <sup>10</sup>	Lithium Ion / intelligent / remove from base / locked with latch					
Charge time - on / off	3.0 hrs / no non-disruptive battery exchange / supports 2nd battery in UltralimBay					
Architecture	2 to 3 hrs / 1.5 to 2.5 hrs					
Port replicator	<b>Intel 440BX AGPset</b> / Intel 82371EB <b>PIIX4E</b> (EIDE, ISA Bridge, USB) /					
Docking Station	TI® PCI1251 for CardBus / AGP for graphics / LM75 digital thermometer					
PC Card Std slots	PCI 2.1 / 32-bit / 33MHz (EIDE, CardBus, audio, USB, ext expansion)					
USB / serial / parallel	PC97338 Super I/O / ISA (audio, modem, diskette, serial, parallel, infrared, ext exp)					
Other features	<b>SelectaBase 600</b> / PC Card Enabler <sup>17</sup> / PC Card Enabler with Advanced EtherJet <sup>17</sup>					
Video (TV) out	<b>SelectaDock III<sup>17</sup></b> / SelectaDock 1 and II					
MPEG decoder	2 Type I, 2 Type II, or 1 Type III / CardBus 32-bit / PCMCIA 2.1 / Zoomed Video					
Data/fax modem	One USB / one 9 pin serial; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)					
Audio support	APM-aware BIOS / Ultralim 56 watt AC Adapter barrel, 3 prong / Selectable boot					
Jacks	5AU: Video out (composite) / cable ships standard with RCA jack / Chrontel CH7004					
Infrared ports	None (W98 support for MPEG-2 because 300MHz with motion compensation)					
Security	<b>56K<sup>22</sup> / V.90 / 14.4Kbps</b> fax / telephony / voice-capable /					
Limited warranty <sup>11</sup>	integrated Mwave <sup>®</sup> 3780i DSP / international programmable DAA / modem cable					
Service options <sup>15</sup>	CS4239: ISA / SRS 3D audio / FM synthesis / 16-bit playback and record					
	CS4610: PCI / decodes AC3 into stereo / MPEG-2 audio decoding / accel of DirectX					
	Int stereo speakers (front) / .5 watt / Fn+PgUp and PgDn (volume) / int microphone					
	Input jack (3.5 mm) / Output jack (3.5 mm) / full duplex					
	Infrared port (on right) / IrDA 1.1 compatible / up to 4Mbps					
	Power-on password / hard disk password / supervisor password / security keyhole / personalization / phillips-head screw on base for memory / opt Allen screw for disk					
	<b>3 year</b> - carry-in or ThinkPad EasyServ™ <sup>31</sup> Rapid Depot Repair (3 business day average turnaround)					
	On-site <sup>32</sup> , M-F, 8-5, next bus day (72 cities) / serv up to 5 yrs from purchase date					
	- ThinkPad 600 Li-Ion Battery	12J2464	- 6.4GB disk, 13ms, Ultra DMA/33	02K0518		
	- 10/100 EtherJet CardBus with 56K modem	08L3167	- 10GB disk, 12ms, Ultra DMA/33	36L9293		
	- IBM 10/100 EtherJet CardBus PC Card	08L3147	- SelectaBase 600	12J2467		
			- PC Card Enabler with EtherJet <sup>17</sup>	05K4820		
			- SelectaDock III <sup>17</sup>	3547003		
			- Ultralim 56 watt AC Adapter (3 prong)	02K6545		
			- 24X-10X <sup>5</sup> CD-ROM (UltralimBay; includes external diskette enclosure)	12J2471		
			- 32MB SO DIMM 3.3v NP SDRAM	76H0294		
			- 64MB SO DIMM 3.3v NP SDRAM	20L0241		
			- 128MB SO DIMM 3.3v NP SDRAM	01K1150		
			- UltralimBay HDD adapter (for 2nd disk)	05K5336		
			- SuperDisk LS-120 (UltralimBay)	20L1929		
			- 2X <sup>5</sup> DVD Drive (UltralimBay)	05K8890		
			- 6X-2X <sup>5</sup> DVD Drive (UltralimBay)	05K9169		
			- Zip 100MB UltralimBay Drive(570/600)	37L1507		
			- UltralimBay Battery (600E only)	02K6504		
<b>Color depth</b>	<b>LCD</b>	<b>External Monitor</b>				
<b>Resolution</b>	<b>TFT</b>	<b>60Hz</b>	<b>70Hz</b>	<b>75Hz</b>	<b>85Hz</b>	
640x480	16M	16M	--	16M	16M	
800x600	16M	16M	--	16M	16M	
1024x768	16M	16M	16M	16M	64K	
1280x1024	--	256	--	64K	64K	
All models:						
- C: drive is FAT16 of 2GB						
- D: drive is FAT32 (if W98) or FAT16 (if NT) of remaining space						
	<b>WINDOWS NT PRELOAD<sup>16</sup></b>					
	<ul style="list-style-type: none"> <li>Microsoft Windows NT® 4.0</li> <li>Service Pack 4a</li> <li>ThinkPad Utilities</li> <li>Online User's Guide</li> <li>ThinkPad Configuration Program</li> <li>Ergonomics</li> <li>IBM Registration</li> <li>Puma IntelliSync 97 (infrared)</li> <li>IBM Global Network Dialer</li> <li>Netscape Communicator</li> <li>Lotus SmartSuite Millennium<sup>20</sup></li> <li>Universal Management Agent</li> <li>ConfigSafe</li> <li>Norton AntiVirus (OEM Version)</li> <li>IBM Update Connector</li> <li>Access ThinkPad</li> <li>SystemSoft CardWizard</li> <li>Software Selections CD-ROM</li> <li>Recovery CD-ROM (Windows NT)</li> </ul>					
	The right bay (UltralimBay) has LED on release latch to provide status; supports warm swapping:					
	<ul style="list-style-type: none"> <li>std diskette and travel cover</li> <li>std or optional CD-ROM</li> <li>std or optional DVD drive<sup>19</sup></li> <li>optional UltralimBay battery (cold swap only; 600E only)</li> <li>optional LS-120 SuperDisk drive (cold swap only)</li> <li>optional Zip 100MB drive (cold swap)</li> <li>optional HDD adapter; for second disk (cold swap only)</li> <li>optional ThinkPad Proven™ solutions<sup>12</sup></li> </ul>					
	<b>PC 97 compliant</b>					
	<b>DMI 2.0 compliant</b>					
	DMI instrumentation (thermal monitoring)					
	<b>ACPI ready</b> (APM enabled)					
	<b>Wired for Management 1.1a</b>					
	<b>Wake on LAN® support<sup>23</sup></b>					
	Setup Guide, User's Reference, Quick Reference and Service Information Card, Options by IBM Catalog, Windows 98 manual					
	Plug and Play 1.0a					
	Standby, suspend, safe suspend, and hibernation modes					
	ENERGY STAR compliant					
	Asset ID™ wireless RF technology (available only as an AAP option on the 600E model AAU; Atmel® AT24RF08 EEPROM))					
	International Warranty Service <sup>14</sup>					
	<b>IBM SystemXtra®</b> , <sup>35</sup>					
	24 hour / 7 day <sup>30</sup> telephone, bulletin board, fax, electronic, and Internet (www.ibm.com/pc/us) support					

