



MiNote 8080



CPU	- Intel Banias CPU Support 1.3GHz ~ 1.7GHz or above - FSB 400MHz
Chipset	Intel Montara-GM+ICH4-M
L2 Cache	1M
System BIOS	- Flash EPROM (Include System BIOS and VGA BIOS) - ACPI 1.0b; DMI 2.3.1 compliant(P)
Memory	0MB on board; Expandable to 1024MB - Expandable with combination of optional 128MB/256MB/512MB(P)memory - Two 200-pin DDR SDRAM Memory Module, PC 2100/1600 specifications
ROM Drive	12.7mm Height 24X CD ROM Drive 8X DVD ROM Drive 24X10x24 CD-RW or above 16X10X8X24 Combo or above 2X2X1X8X24X10X24 DVD Multi - Swappable and hot plug for 2nd HDD .
HDD	2.5" 9.5 mm height: 20/30/40/60GB; Support Ultra DMA 66/100 - Reseller Exchangeable
Ext. FDD	Support External FDD w/z USB I/F; 3.5" Format for 720KB/1.2MB/1.44MB
Display	14.1" XGA/SXGA+ TFT display; Resolution: 1024x768/1400x1050
Video Controller	- Integrate in Northbridge - Support Multi Monitor - Ultra AGP
Keyboard	19mm pitch/2.7mm stroke,300mm length - Windows Logo Key x 2; Application Key x 1
Button	5x Easy Start Buttons (functions defined by user)/ instant play for Audio CD When System off 1xWireless RF ON/OFF
Pointing Device	- Glide pad with 6x buttons - Finger print for factory option
PCMCIA	- Type II x 1 - CardBus Support
Card Reader	4 in 1 card reader for (MS,SM,SD,MMC)
Audio System	- Sound Blaster Pro compatible - Built-in mono microphone - Support AC97 2.1 2X Speakers
I/O Port	- Standard USB2.0 port x 3 - RJ-11 port x 1 - RJ-45 port x 1 - IR port x1, complies with IrDA 1.1 - DC input x 1 - VGA monitor port x1 - Audio-out x 1 (SPIDF) - Mic-in x 1 - IEEE1394a Port x 1 - S-Video Out Port (7 pins)x 1 (NTSC/PAL)
Communication	- Built-in 56Kbps V.90 MDC modem - Built-in 10/100 based-T LAN - Built-in antenna for Mini-PCI wireless communication
Power Supply	8-cell Li-ion (2200mAh/3.7V) Cylindrical Type - User swappable - Min Battery Life: 5 hrs (P) - Support Power on charge
AC adapter	Universal AC adapter 60/70 W(P) ; Input: 100-240V, 50/60Hz AC
Dimensions	318x277 mm, thickness 25~30mm
Weight	2.5kg
Accessories	Power Cord, AC Adapter, RJ-11 Phone Cable, Manual, System Driver CD-Title, S-video to RCA cable
Architecture	Support PC2001 Specification, Designed for Windows 2000 & Windows XP
Options	128MB/256MB/512MB DDR SDRAM, 8-cell LI-ION Battery Pack, AC Adapter w/o Power Cord, Notebook Carry Bag

MiTAC PCs use genuine Window® Operating systems
<http://www.microsoft.com/piracy/howtotell>