

NP5680



CONSISTENTLY ON THE CUTTING EDGE

Sager's NP5680 boasts an Intel® Pentium® 4 Processor with Hyper-Threading Technology, 400MHz Dual Channel DDR Memory, front panel Audio DJ, Dual SmartBays, the powerful ATI MOBILITY™ RADEON™ 9600 PRO TURBO and an optional second battery pack that extends system usage time!

NP5680 Series

NP 5680 SERIES SPECIFICATIONS

Processor

Intel® Pentium® 4 2.4/2.5/2.6/2.8/3.0/3.2GHz (800FSB) w/HT

Core Logic

Intel® 865PE chipset + ICH5

Memory

Dual Channel DDR 266/333/400 (2 DIMM required for Dual channel mode)

256MB 400MHz DDR SDRAM Expandable to 2048MB

512KB On-die L2 Cache

Bios

4MB Flash ROM BIOS

Disk Storage

- Hard Disk Drive

PCI Local Bus Interface

Detachable 2.5" 9.5mm Hard Disk Drive

Supports Ultra DMA HDD for High Speed Access

- Floppy Disk Drive

Removable 3.5" 1.44MB Floppy Disk Drive

Display

15.0 SXGA+ TFT 1400x1050 / UXGA TFT 1600x1200

128MB DDR SGRAM

AGP 8X

ATIMOBILITY™ RADEON™ 9600 PRO TURBO

Dual-View Display Capability

TV resolution up 1024x768 32bpp

CRT Resolution up to 2048x1536x16m

DVD or CD-ROM Drive

Detachable 24X CD-ROM

Interchangeable with 8X DVD-ROM, 24X CD-R/10X CD-RW,

DVD/CD-RW Combo drive, DVD-RW drive

ATAPI Interface

Audio System

AC'97 2.1 compliant interface

3D stereo enhanced sound system

Compatible Sound-Blaster PRO™

S/PDIF Digital output(5.1 CH) for DVD content

Audio DJ Access Front Panel

1 Built-in Microphone

2 Built-in Speakers

PCMCIA Slot

PCMCIA 3.0 Standard Compliant

1 Type II PCMCIA Slot

Pointing Device

Integrated Touchpad With Scroll Up/Down key

Keyboard

87-key Membrane Keyboard

Windows 95 2 Hot keys

Integrated with Hot Keys for LCD Brightness, Suspend, Panel/CRT Display

3 Hot Keys for E-Mail, Web Browser. And AP-Key

Interface

1 Parallel Port, with ECP/EPP Support

1 External Keyboard Port

1 External CRT Port

4 USB 2.0 Ports

3 Audio Jacks for Microphone-in / Headphone out / Optical S/PDIF out

1 RJ-45 LAN

1 RJ-11 Modem

1 Mini-IEEE 1394 Fire Wire

1 S-video TV-Out

Communication

Infrared Communication, FIR, SIR and ASK Compliant

10/100/1000Mbps Ethernet LAN built-in

56K MDC Modem with V.90 & V.92 compliant

Power System

1 Lithium-Ion Battery

Full Range Auto-Switching 100V/240V AC Adapter

Power Management

System Management Mode (SMM)

Suspend to HDD / DRAM

Full features of SMI Power Management, Doze, Sleep,

Suspend/Resume Mode

Physical Characteristic

(H) x (W) x (D) : 1.7" x 13" x 11.4"

Weight: 9.65 lbs. with Battery

SmartBay Options

Second Battery

Second Hard Disk Drive

Second CD-Rom

Second DVD-Rom

Second CD-R/RW

Second DVD/CDRW Combo

Second DVD-RW

6-in-1 Card Reader

Standard Options

Car Adapter

Numeric Keypad

Internal 802.11b Wireless LAN mini-PCI interface

Internal 802.11g Wireless LAN mini-PCI interface

Internal Bluetooth Module mini-USB interface