

SCENIC Mobile 360

The complete entry-level communications solution for professional users

Available as:

SCENIC Mobile 360 C 333

SCENIC Mobile 360 P 333

- Intel® Celeron™ processor 333 MHz / 128 KB Cache
- Intel® Pentium® II processor 333 MHz / 256 KB Cache
- 32 MB up to 256 MB SDRAM
- Hard disk: 4.0 GB featuring ATA-33 technology
- Hard disk: 6.0 GB featuring ATA-33 technology
- 2 MB video SGRAM
- 12.1-inch LCD TFT SVGA display
- 13.3-inch LCD TFT XGA display

- Internal 24-speed CD-ROM drive
- Internal 3.5-inch floppy disk drive
- Internal 56K modem for usage in many countries
- Fast Infrared (FIRDa)
- Advanced Configuration Powermanagement Interface (ACPI) functionality for longer battery operation
- Universal Serial Bus (USB)

- 1-year warranty (bring-in service)
- 5-year spare supply
- Year 2000 support
- Ready for Euro
- PRIMUS Marketing and Sales Program



Technical Data SCENIC Mobile 360

	SCENIC Mobile 360 C	SCENIC Mobile 360 P
Processor	333 MHz (from 11/99 366 MHz)	333 MHz (from 10/99 366 MHz)
Second Level Cache (on-die)	128 KB	256 KB
Display	12.1" TFT SVGA / 13.3" TFT XGA	13.3" TFT XGA
Hard disk	4.0 GB (from 10/99 6.0 GB)	6.0 GB

Processor unit

Microprocessor	Intel Celeron processor 333 MHz Intel Pentium II processor 333 MHz
----------------	---

Cache in microprocessor integrated ('on-die')	128 KB (Celeron) 256 KB (Pentium II)
---	---

Basic unit

Main memory (SDRAM)	32 MB, max. 256 MB
Flash-EPROM	BIOS update via floppy disk

Interfaces

1 x serial	9-pin
1 x parallel 25-pin, with EPP and ECP	
1 x ext. keyboard or mouse	PS/2
- Y adapter can be used -	
1 x ext. monitor	15-pin, with DDC 1 / 2
1 x microphone	
1 x speaker	
1 x Fast IrDa	
1 x USB	

Audio

16-bit stereo 3D sound chip (Soundblaster-compatible)
Two built-in speakers and microphone

Graphics processor

On board on the PC bus	Silicon Motion LYNX E SM 811
Max. resolution	1024 x 768 at 75 Hz and 65.536 colors

Display

Display diagonal	
LCD TFT	12.1-inch (30.7 cm)
LCD TFT	13.3-inch (33.7 cm)
Resolution / colors (max)	
LCD TFT SVGA (12.1")	800 x 600 / 65.536 colors
LCD TFT XGA (13.3")	1024 x 768 / 65.536 colors

Drives

Floppy disk drive	3.5-inch 1.44 MB
Hard disk drive	1 x 2.5-inch, height: 12.7 mm
(net capacity/seek time)	4.0 GB (IDE) ≤ 12 ms 6.0 GB (IDE) ≤ 12 ms
24-speed CD-ROM drive	Data transfer rate 3600 KB/s

CardBus / PC Card

Free slots	2 1 x Type III or 2 x Type I / II
ZV support	Video display in real time bypassing the system bus

Security functions

Security functions integrated in the BIOS/Setup

- Password protection for system, setup and keyboard
- Boot protection for floppy drive
- Boot protection for PC Cards

Temperature / noise / dimensions / weight

Ambient temperature (to IEC 721)	5° C to 35° C
Sound pressure level at workplace LpA	< approx. 35 dB(A) (in standard configuration)
Dimensions (HxWxD)	42 x 311 x 249 mm
Weight	2.9 kg

Electrical values

Power supply	
Rated voltage range	100-240 V (autosensing)
Rated frequency	50-60 Hz (autosensing)
Max. power output from power supply	50 W
Dimensions (HxWxD)	30 x 58 x 108 mm
Weight	0.315 kg

Battery

NiMH (nickel metal hydride)	
Voltage	9.6 V
Rating	38 Wh
Charge time (not in use)	2.5 h
Charge time (in use)	4 h
Weight	540 g
Operating time, with one battery	approx. 2.5 h dependent on application

Internal modem

Maximum data transfer rate	56 Kbit/s
Transmission standard:	V.90, V.42 bis NMP 5
Available countries	Austria, Belgium, Denmark, Finland, France, Germany, Greece, Great Britain, Italy, Ireland, Island, Luxembourg, Norway, Netherlands, Portugal, Sweden, Switzerland, Slovenia, Spain, Turkey

Compliance with standards

Product safety	EN60950/IEC60950 UL1950, CSA22.22 No.950
Ergonomics	ISO9241
Electromagnetic compatibility	EN55022/B EN50082-1
CE certification	to EU Directive 89/336/EEC (EMC)
Power management	ACPI compatible
Microsoft Logo	PC 98 compatible

Operating systems / software

Windows 98 SE or Windows NT 4.0 Workstation preinstalled

Published by
Fujitsu Siemens Computers B.V.

Bürgermeister-Ulrich-Str. 100
D-86199 Augsburg

Tel. +49 180 52 11 100
Fax +49 180 52 11 101
World Wide Web:
<http://www.fujitsu-siemens.com>

All rights, including rights created by patent grant or registration of a utility model or design, are reserved.
Delivery subject to availability; right of technical modifications reserved.

Copyright ©
Fujitsu Siemens Computers B.V. 10/1999
Printed in Germany
Order No. **U26813-J-Z154-3-7600**

Company stamp

All hardware and software names used are brand names and/or trademarks of their respective holders.

Full support for this operating system is guaranteed by the hardware functionality.
