

TOSHIBA PORTEGE 320CT Specifications

PART# PA1274U-T2A

PROCESSOR	Intel Pentium® 266Mhz (1.8V/2.5V) w/MMX Technology		
External data bus width	64 bit		
External data/address bus speed	66 MHz		
Integrated Coprocessor	Yes		
Processor Cache	32KB: (16KB code; 16KB data)		
LEVEL 2 (L2) CACHE	Yes: 512KB		
Data Memory Type	2 Mbit Pipelined Burst Synchronous SRAM (2.5V)		
Data Bus Width	64 Bit		
Access Time	8 ns		
Cacheable main memory area	Up to 64 MB		
Local Bus Clock Speed	66 Mhz		
SYSTEM ARCHITECTURE	<u>Connecting Devices:</u>		
PCI (V.2.1) Bus: (32-bit, 33 MHz)	PC Card Slots; Graphics, Modem & USB Controllers		
ISA Bus: (16-bit, 8mhz)	BIOS, KBC, Sound chip		
MEMORY: 64Mbit EDO DRAM, 3.3V			
Standard	32 MB		
Maximum	96 MB		
Speed	60ns		
Hyper Page mode memory access	Yes		
Data width	64 bit		
Local Bus Clock Speed	66 MHz		
BIOS (4Mbit FLASH EPROM)	Yes: 512KB		
Supported standards	APM (V.1.2); PnP 1.0a ;VESA (V.2.0); DPMS, DCC2, DMI		
DISPLAY			
Type	Panoramic Active Matrix Color (16:9 aspect ratio)		
Size	10.4" Diagonal		
Resoluition	1024 x 600		
Dot Pitch	0.22mm x 0.22mm		
Contrast Ratio	100:1 (min)		
VIDEO			
Memory: 4Mbit EDO DRAM, 3V	2 MB		
Speed	50ns		
Hyper Page mode support	Yes		
Controller Chip	Chips & Technology (B65555) <i>w/64-bit Data Bus Width</i>		
PCI Bus Architecture w/burst mode	Yes: 32-bit, 33 MHz		
Graphics Accelerator:	Yes: Supports 64-bit BitBLT, H/W Cursor, DirectDraw, Direct3D		
Digital Video Accelerator:	Yes		
YUV-to-RGB color space conversion	Yes		
Scaling Support	Yes		
Zoomed Video Port Support	Yes		
Interpolation	Yes		
DirectVideo, DirectMPEG support	Yes		
INTERNAL SUPPORT			
Full screen	1024 x 600 x 16.7M colors		
Smaller Image	640 x 480 x 16.7M colors		
Smaller Image	800 x 600 x 16.7M colors		
EXTERNAL SUPPORT	<u>Colors</u>	<u>Vert. Refresh Rate (Non-Interlaced)</u>	
640 x 480	16.7M colors	75 Hz (95Hz max @ 64K colors)	
800 x 600	16.7M colors	75 Hz (85Hz max @ 64K colors)	
1024 x 768	64K colors	75 Hz (85Hz max @ 256 colors)	
1280 x 1024	256 colors	60Hz	

TOSHIBA PORTEGE 320CT Specifications

PART# PA1274U-T2A

STORAGE		
HDD (2.5" Enhanced IDE)		4.0 billion bytes = 3.82GB (13msec read /14 msec write)
FDD (3.5" 1.44MB) -- External		Bundled: Plugs into I/O BAR (Port Expander)
CD-ROM		See Optional Multimedia Port Replicator Section
KEYBOARD		
84 keys with Windows 95 support		Yes (full-size key caps; 3mm Travel)
Key Pitch		18mm (alpha characters); 17mm (remaining keys)
12 dedicated function keys		Yes
Cursor control (8 Keys, Inverted "T")		Yes
Numeric keypad (Integrated Overlay)		Yes
Integrated Pointing Device		AccuPoint™
EXPANSION SLOTS		
Two Stacked PC Card Slot ¹		Yes: CardBus & ZV Card Ready
32-bit, 3.3V PC CardBus Support		Yes
16-bit, 5.0V PC Card Support		Yes
Internal Memory Slot (One only)		Yes
EXPANSION PORTS		LOCATION
One 15-Pin RGB (SVGA video)		Yes: Rear of unit
One 160-pin expansion bus		Yes: Rear of unit
One Power-in Jack		Yes: Rear of unit
One Fast Infrared port (IrDA2.0: 4Mbps)		Yes: Top of unit
One Universal Serial Bus (USB) port		Yes: Left side (Supports 127 devices. Throughput Rate: 12Mbits/sec.)
One RJ11 Port for internal modem		Yes: Left side
One Headphone (3.5mm mini jack, stereo)		Yes: Left side
One Noteworthy security lock port		Yes: Right side
I/O BAR (Port Expander)		(1) Standard: Connects to 160-pin expansion bus -- rear of unit
One 9-Pin Serial (16550 UART compliant)		Yes
One 25-Pin Parallel (8 bit ECP)		Yes
One External Floppy Drive port		Yes
One (PS/2) 101 Keyboard/Mouse port		Yes: Supports use of Y-cable
POWER		
Autosensing External AC Adapter: PA2440U		3.94''L x 1.97''W x .98''D--- .46 lbs
Input (Voltage/Frequency)		100-240V; 50-60Hz
Output (Voltage/Amps)		15 VDC; 2.0A
Power Output (Watts)		30W
Battery Type: Li-Ion (10.8V, 2400mAh)		Yes: Part# PA2441URA (one standard)
Battery Life: (Full Power)		Standard Battery: 2.5 hr. Optional High Capacity Battery: 3.5hr.
Recharge Time (Computer Off/On)		2.5 hr./3-9 hr.
MaxTime® Power Management		Yes
INTERNAL MODEM		K56Flex Voice/Data/Fax modem w/V.80 for Video Conferencing
DAA Support		US/Canada/Japan
Data support	Protocols supported	Bell-103/212A, CCITT-V.21/V.22, V.32, V.32bis, V.34, V.80
	Error correction	MNP 1-4
	Data compression	MNP 5, CCITV V.42bis
Fax support		Fax class 1
	Protocols supported	V.21 ch2, V.27 ter, V.29, V.17
Supported Functions		Speaker Phone, Telephony Answering Machine, Ring Wake-up Resume, Incoming Call Discrimination

¹ Holds two - 5mm PC Cards Type II or one - 10.5mm PC Card Type III.

TOSHIBA PORTEGE 320CT Specifications

PART# PA1274U-T2A

SOUND SYSTEM

Chipsets:	Yamaha OPL3-SA3
16-bit stereo audio playback/record	Yes
Maximum Sampling Rate	48 kHz
FM Synthesis support	Yes
Full duplex support	Yes
Built-in Speaker	Yes (monaural)
Built in Microphone	Yes (monaural)
DirectSound, Direct3DSound support	Yes
Sound formats supported:	SoundBlaster Pro™ V3.01, MIDI, Windows Sound System V2.0

Multimedia Port Replicator (Optional)

(Shipping)

(Available May 1998)

Part Number

Part# PA2661U

Part# PA2662U

CD-ROM Speed

10x Average

20x Maximum/14X Average

Size

5.25" (Height: 12.7mm)

5.25" (Height: 12.7mm)

Interface: .ATAPI (Enhanced IDE)

Yes

Yes: *with 128KB buffer*

Random Access Time

180ms

150ms

Sustained Transfer Rate

1500 KB/sec

3000 KB/sec

Supported Disc formats (**All models**)

CD-DA, CD-ROM, CD-ROM XA, CD-Bridge (Photo-CD, Video-CD), CD-I, CD-I Ready, CD-G, Multisession (Photo-CD, CD-Plus)

One 9-Pin Serial (16550 UART compliant)

Yes

One 25-Pin Parallel (8 bit ECP)

Yes

One External Floppy Drive port

Yes

One (PS/2) 101 Keyboard/Mouse port

Yes: "Y"connector supported

One Universal Serial Bus (USB) port

Yes: Supports 127 devices. Throughput Rate: 12Mbits/sec.

One Microphone (3.5mm mini jack, monoaural)

Yes

One Headphone (3.5mm mini jack, stereo)

Yes

One Line-in (3.5mm mini jack, stereo, 2V rms)

Yes

One Line-out (3.5mm mini jack, stereo, 0.7V rms)

Yes

DIMENSIONS

10.35"W x 1.38"H x 7.56"D

WEIGHT (includes . 6 lb. battery)

3.9 lbs.

BUNDLED SOFTWARE

Windows®95; RingZero RingCentral v.4.xx Telephony application; Mediamatics MPEG ARCADE Pak, Yanmaha Station; Puma IntelliSync 97 (IR Software); Microsoft Internet Explorer 3.02 America Online, CompuServe

CD's Included: OS Recovery CD; Windows 95 Companion CD; Application CD

Application CD: LAN Desk 3.1; Systemsoft Cardworks; Fn-esse; Electronic manual; On-line registration

SECURITY

Miscellaneous

Screen blank (by Hotkey)

Lock mechanisms

PC Card, keyboard (by Hotkey), Noteworthy cable lock

Password security

Power-on & supervisor

WARRANTY

3 YR Parts & Labor (1 YR Battery)

ENVIRONMENTAL SPECIFICATIONS

	<u>Operating</u>	<u>Non-operating</u>
Temperature	41°F (5°C) to 95°F (35°C)	-4°F (-20°C) to 149°F (65°C)
Thermal Gradient: 20° C per hour (max.)	N/A	N/A
Relative Humidity	20% to 80% non-condensing	10% to 90% non-condensing
Altitude:	-197 to 9,843ft. (-60 to 3000m)	-197 to 32,808ft. (-60 to 10,000m)
Shock:	10G; 1.5G w/CD-ROM installed	60G; 50G w/CD-ROM installed
Vibration:	0.5G; 0.25G w/CD-ROM installed	1G; 1G w/CD-ROM installed