

TOSHIBA

Portégé 3480CT

Product Highlights

- Ultra-portability - .8" thin and 3.4 lbs. light
- Performance - Intel Mobile Pentium III SpeedStep technology processor
- Over 2.5 hours battery life with main battery and over 8 hours battery life with the addition of the high capacity battery
- 11.3" advanced Poly-silicon TFT color display with 1024x768 resolution
- Screaming multimedia performance - Savage S3 IX video controller with 8MB memory
- Expansion Flexibility and Connectivity

Product Specifications

Processors

Intel® Mobile Pentium® III SpeedStep

Technology™ processor:

◆ 600MHz (1.35V)

With 256KB Level 2 cache integrated on die

Integrated co-processor

32KB internal cache

Data/Address Bus Width: 64-bit/32-bit

100MHz Processor System Bus

Memory

Type: 64/128 Mbit PC100 SDRAM, 3.3V, 100MHz

Capacity: 64MB on board, expandable to 192MB

One available memory slot (for use with 64MB or 128MB memory module)

BIOS

APM V1.2; ACPI V1.0b; PnP V1.0a; VESA V2.0; DPMS; DDC2B; SM Bios V2.3, PCI BIOS V2.1

System Architecture

PCI Bus V2.2: Intel 440MX System Chipset

Hard Disk

12.0 billion byte Supports PIO Mode 4;

Supports Ultra DMA Mode 2,

Supports Multiword DMA mode 2

Accommodates 9.5mm height, 2.5" hard drive

13 ms average access time

Enhanced IDE (ATA-4) interface; Service removable

External Floppy Diskette Drive

USB, 3.5", 1.44MB

Video

S3 Savage IX graphics controller

8MB SGRAM Internal Video Memory

128-bit BitBLT engine, Direct3D support,

33MHz

Video Ports

SVGA

Display

Polysilicon TFT Color LCD

11.3" diagonal: up to 16 million colors at 1024 x 768 resolution

External Color Support

16M colors:

1024x768, 800x600, 640x480 @

60/75/85Hz Non-Interlaced, simultaneous mode

64K colors:

1024x768, 800x600, 640x480 @

60/75/85Hz Non-Interlaced, simultaneous mode

1280x1024 @ 60/75Hz Non-Interlaced,

1600x1200 @ 60Hz Non-Interlaced

256 colors:

1024x768, 800x600, 640x480 @

60/75/85Hz Non-Interlaced, simultaneous mode

1280x1024 @ 60/75Hz Non-Interlaced,

1600x1200 @ 60Hz Non-Interlaced

Audio

YAMAHA YMF752, 16-bit stereo

Compatibility: Windows Sound System V2.0

and Sound Blaster Pro compatible

MIDI playback

3D sound support

Direct Sound, Direct 3D Sound, Direct Music,

Full duplex sound support, 64 voices,

Headphone port (Stereo)

External mic port

Built-in speaker

Built-in mic

Communications

Integrated V.90 modem

Supports ring wake-up resume

RJ-11 modem port

Keyboard

85 keys with 12 function keys

2 mm key stroke

Dedicated Windows® key

Integrated AccuPoint II™ pointing device, scroll

function - programmable

Expansion

Two PC Card slots support two Type II or one

Type III PC Cards;

Supports: PCMCIA R2.01, PC Card 16,

CardBus

One expansion memory slot available (for use with 64MB or 128MB memory module)

SVGA video port

Fast infrared port (4Mbps, IrDA V1.1 compliant)

Universal Serial Bus (USB) port

RJ-11 modem port

LAN Port Replicator bundled with system

Serial PCI port - for use with LAN Port

Replicator, I/O Adapter, and Multi-Media Port

Replicator

Dimensions (WxDxH)

10.3" x 9.1" x 0.8" - thickness may vary at certain points on the system

Weight

3.4 lbs (With main 6-cell battery)

Power Supply

45W External AC Adapter

100-240V input voltage

50-60Hz frequency

4.9"W x 2.5"D x 1.0"H, .7 lbs.

Battery

Rechargeable, removable Lithium Ion battery

(10.8V, 3000mAh)

2.5 + hours battery life

3 hours recharge time (off)

ACPI V1.0b support

Battery life may vary depending on applications, power management settings and features utilized. Recharge time varies depending on usage.

System Management

SM V2.3 BIOS support with asset tag capability

ACPI V1.0b power management

Toshiba Configuration Builder CD

Security

Power-on password

HDD access password

Keyboard lock

CPU Serial Number Security (Using SVPW utility)

Setup Security (Using SVPW utility)

Screen Blank

Main system memory, modem, and internal

HDD security screws included

Cable lock slot

Software

Microsoft® Windows 2000, Windows NT 4.0

SP5,

Windows 98SE

AT&T WorldNet Services - 98SE

Customizable Toshiba/My Yahoo! Start page - 98SE

Microsoft Internet Explorer - 98SE/NT4.0/2000

Puma IntelliSync 97 - NT4.0 only

RingCentral - Win98SE only

Toshiba custom utilities - 98SE/NT4.0/2000

YAMAHA YMF744B Audio - 98SE/NT4.0/2000

Electronic User Guide - 98SE/2000

Warranty

1 year parts and labor

1 year battery

Environmental Specifications

Temperature:

Operating: 5° to 35° C (41° to 95° F)

Non-operating: -20° to 65° C (-4° to 149° F)

Thermal gradient:

Operating: 15° C per hour maximum

Non-operating: 20° C per hour maximum

Relative Humidity:

Operating: 20% to 80% non-condensing

Non-operating: 10% to 90% non-condensing

Altitude (relative to sea level):

Operating: -60m to 3,000m (-197' to 9,842')

Non-operating: -60m to 10,000m (-197' to 32,808')

Shock:

Operating: 10G

Non-operating: 60G

Vibration:

Operating: 0.5G

Non-operating: 1G

Featured Configurations

PP348U-4PU83

PIII-600/11.3/64MB/12GB/Mdm/Win98

PP348U-4PU86

PIII-600/11.3/64MB/12GB/Mdm/Win2K/NT

Accessories

PA3012U 6GB HDD for use with

Multimedia Port Replicator

PA3027U 12GB HDD for use with

Multimedia Port Replicator

PA3029U 18GB HDD for use with

Multimedia Port Replicator

PA3020U HDD Adapter

PA3015U CD-ROM Drive for use with

Multimedia Port Replicator

PA3014U DVD Drive for use with

Multimedia Port Replicator

PA3043U-1FDD USB Floppy Disk Drive

PA3041U-1PRP I/O Adapter (Port

Replicator)

PA3040U-1PRP LAN Port Replicator

PA3042U-1DST Multimedia Port Replicator

PA3035U-1ACA AC Adapter

PA3038U-1BRL Main Battery

PA3039U-1BRL High Capacity Battery

KTT-MD100/64 Kingston 64MB Memory

KTT-MD100/128 Kingston 128MB Memory

NWCC30130 Port-Noteworthy Portégé

Slimcase

* Hard disk drive: 1GB = 1BB