

# SATELLITE 2535CDS Product Specifications

<b>MODEL</b>	2535CDS/4.3 billion bytes		
<b>PART NUMBER</b>	PAS253U-S6CW8		
<b>PROCESSOR</b>			
Intel Pentium® 300Mhz (2.0v/2.5v) w/MMX	Yes ( <i>Uses 0.25 micron technology</i> )		
Integrated Coprocessor	Yes		
Processor Cache	32KB: (16KB code; 16KB data)		
<b>LEVEL 2 (L2) CACHE</b>			
	Yes: <b>512KB</b>		
Type of cache memory	Pipelined Burst Synchronous SRAM		
Cacheable Main Memory Area	Up to 64MB		
Data/Address Bus Width	64-bit/32-bit		
Local Clock Bus Speed	66 MHz		
<b>SYSTEM ARCHITECTURE</b>		<u>Connecting Devices</u>	
PCI BUS (v.2.1): (32-bit, 33 MHz)	PC Card Slots, Graphics Controller, HDD, CD-ROM, FDD		
ISA BUS: 16-bit, 8.25 MHz	BIOS, Sound chip, KBC		
<b>BIOS</b>			
	<b>4Mbit Flash EPROM (5V), 512KB</b>		
Supported standards	APM (v.1.2); ACPI; PnP (v.1.0a); VESA (v.2.0); DPMS; DCC2B; DMI (v.2.0); PCI BIOS; CD-ROM & ATA-HDD bootable		
<b>SYSTEM MANAGEMENT</b>		DMI 2.0 BIOS w/asset tag capability; Wired for Management (v.1.1a); ACPI	
<b>MEMORY: 64Mbit EDO DRAM, 3.3V</b>			
Standard	32 MB		
Maximum	160 MB		
Speed	60ns		
Hyper Page mode memory access	Yes		
Data /Address Bus width	64-bit/32-bit		
Local Bus Clock Speed	66 MHz		
<b>VIDEO</b>			
Memory: 4Mbit EDO DRAM, 3.3V	2 MB <i>integrated into the Graphics Controller</i>		
Speed	50ns <i>with Hyper Page mode support</i>		
Controller Chip	C&T 69000		
Data Bus Width	64-bit		
Local Bus Clock Speed	66MHz		
PCI Bus Architecture w/burst mode	Yes: 32-bit, 33 MHz		
Graphics Accelerator:	Yes with 64-bit BitBLT support		
2D graphics support	BitBLT, DirectDraw, H/W Cursor		
3D graphics support	Direct3D		
Digital Video Accelerator:	Yes		
YUV-to-RGB color space conversion	Yes		
Zoom	Yes		
Scaling/Interpolation	Yes		
DirectMPEG support	Yes		
DirectVideo support	Yes:w/Game SDK driver fr/Microsoft		
Color Palette	16.7M colors		
Internal Support	<u>Resolution</u>	<u>Colors Support</u>	
Full Screen	800 x 600	16.7M colors	
Smaller Image	640 x 480	16.7M colors	
Virtual Display Mode	1024 x 768	64K colors	
Virtual Display Mode	1280 x 1024	256 colors	
External Support	<u>Resolution</u>	<u>Colors Support</u>	<u>Vertical Refresh Rate (Non-Interlaced)</u>
	640 x 480	16.7M colors	85Hz @ 64K color
	800 x 600	16.7M colors	85Hz @ 64K color
	1024 x 768	64K colors	60 Hz @ 64K color
	1280 x 1024	256 colors	60 Hz @ 64K color

# SATELLITE 2535CDS Product Specifications

<b>MODEL</b>	2535CDS/4.3 billion bytes
<b>PART NUMBER</b>	PAS253U-S6CW8
<b>DISPLAY</b>	
Type	Color Bright Dual Scan (800 x 600)
Size	13.0" Diagonal
Dot Pitch	.30mm x .30mm
Contrast Ratio	40:1
Brightness Control	Yes: using SETUP or Power Save Utility
Contrast Control	Yes
<b>ALL-IN-ONE DESIGN</b>	
<b>HDD</b>	
Removable HDD (2.5" Enhanced IDE)	4.3 billion bytes (13msec read/14msec write)
Height	9.5mm
Buffer	512KB
Burst Data Transfer Rate	Ultra DMA33 Mode2 (33.3MB/sec) or PIO Mode 4 (16.7MB/sec)
Local Bus support	Yes
<b>FDD</b> (3.5" 1.44MB; 12.7mm high)	Yes
Simultaneous FDD & CD-ROM Support	Yes: two independent internal units
<b>CD-ROM:</b> (5.25" ; 12.7mm high)	24X Maximum Speed
Weight	.62 lbs.
Interface	.ATAPI (Enhanced IDE) <i>with 128KB buffer</i>
Random Access Time	130 ms
Average Sustained Transfer Rate	3,600 KB/sec
Burst Data Transfer Rate	PIO Mode 4 (16.7MB/sec) or Multi Word DMA Mode2 (16.6MB/sec)
Supported Disc formats	CD-DA, CD-ROM, CD-R, CD-ROM XA, Photo CD (Multisession), Video CD, CD Extra (CD Plus), CD-G, CD-RW (read only)
<b>KEYBOARD</b>	
84 keys, 3mm Travel	Yes
Key support	Windows 95/98, Application
Internet Browser function	F6 key
CD-ROM functions	Skip to Previous track (F7); Play & Stop (F8); Skip to next track (F9)
Dedicated function keys	12 dedicated function keys
Keyboard height	9.5mm
Key Pitch	19.05mm
Cursor control (8 Keys, Inverted "T")	Yes
Numeric keypad (Integrated Overlay)	Yes
<b>Integrated Pointing Device</b>	AccuPoint™
<b>EXPANSION SLOTS</b>	
Two Stacked PC Card Slots	Yes: Holds two - 5mm PC Cards Type II or one - 10.5mm PC Card Type III.
Support Standards	Yes: Supports 32-bit, 3.3V PC CardBus cards <i>and</i> 16-bit, 5.0V PC card standards
Internal Memory Slot (One only)	Yes
<b>EXPANSION PORTS</b>	
One 9-Pin Serial (16550 UART equivalent)	Yes
One 25-Pin Parallel (8 bit ECP)	Yes
One 15-Pin RGB (SVGA video)	Yes
Fast Infrared port (Back only)	Yes: IrDA 1.1:4Mbps compatible
One (PS/2) 101 Keyboard/Mouse port	Yes: "Y" connector supported
Universal Serial Bus (USB) port	Yes: Supports 127 devices. Throughput Rate: 12Mbits/sec.
Microphone (3.5mm mini jack, monaural)	Yes
Headphone (3.5mm mini jack, stereo)	Yes
Line-in (3.5mm mini jack, stereo, 2V rms)	Yes
Noteworthy security lock port	Yes

# SATELLITE 2535CDS Product Specifications

<b>MODEL</b>	<b>2535CDS/4.3 billion bytes</b>
<b>PART NUMBER</b>	<b>PAS253U-S6CW8</b>
<b>PC Card MODEM (Bundled)</b>	3Com-Noteworthy 56K PC Card Modem
Data support	
Protocols supported	Bell-103,& 212A, V.23, V.22, V.22bis, V.32, V.32bis, V.34, V.34+, <b>V.90</b>
Error correction	V.42/MNP 2-5
Data compression	MNP 5, CCITT V.42 bis
Fax support	Group 3, EIA/TIA, Fax class 1
Protocols supported	V.17, V.21 Channel 2, V.27 ter, V.29, V.33
Command Set	Hayes, Microcom compatible AT commands

<b>POWER (All models)</b>	
<b>Autosensing External AC Adapter</b>	3.94"L x 1.96"W x 0.98"H --- .48 lbs.
Input (Voltage/Frequency)	100-240V; 50-60Hz
Output (Voltage/Amps)	15 VDC; 2A (max)
Power Output (Watts)	30W
Battery Type: Li-Ion (10.8V, 3600mAH)	Yes (one standard): Part# PA2487URG
Dimensions	6.87"L x 2.76"W x .73"H
Battery Life: (Full Power)	3.0 hrs.
Recharge Time (Computer Off/On)	3+ hrs./4-10 hrs. <i>depending on the computer function performed</i>
Power Saving Features	ACPI (v.1.0) Power Management, CPU sleep, HDD Auto Off, Display Auto Off, CPU speed change, Auto Resume, and Hibernation

<b>SOUND SYSTEM</b>	
	<b>Yamaha Sound System</b>
Chipset:	Yamaha OPL3-SA3
16-bit stereo audio playback/record	Yes
Maximum sampling rate	48 kHz
FM Synthesis support	Yes (Soft Wave Table included)
Full duplex function	Yes
Sound formats supported:	SoundBlaster Pro™ V3.01, Windows Sound System V2.0, MIDI
3D Sound Support	Yes
Direct3DSound, DirectSound support	Yes: with Windows 95 Game SDK driver from Microsoft
Speaker system	Two top-mounted stereo speakers (28mm, 8 Ω) <i>with volume control</i>

<b>DIMENSIONS</b>	<b>Dimensions</b>	<b>Weight</b>
Notebook	12.2"W x 10.2"D x 1.7"H	6.7 lbs.
AC Adapter	3.94"L x 1.96"W x 0.98"H	.48 lbs.
Battery (Standard)	6.87"L x 2.76"W x .73"H	.88 lbs.

**BUNDLED SOFTWARE**  
 Windows®98; Ring Zero Ring Central Dialer application, Intel Indeo Video, Mediamatics Arcade Pak, Prodigy Internet, Symantec Norton Antivirus Scanner 4.0; Disney Daily Blast, Microsoft Money 98; Microsoft Outlook; Intuit Quicken Basic 98; Fn-esse™, Online documentation  
**CD's Included:** Bootable Configuration Builder CD; Toshiba Companion diskette; Microsoft Encarta 99 MPEG version; Microsoft Money; Microsoft Outlook 98; Microsoft Bookshelf 99

**Choice of a Total of 5 Additional Software Titles**

<b>Lotus® SmartSuite Millennium Edition (counts as 5 selections):</b> Lotus 123, Approach, Freelance Graphics, Wordpro, and Organizer	
<u><b>Mobile Productivity</b></u> Laplink® Rand McNally TripMaker® USA 98: Streets & Destinations Print Artist™ 4.0	<u><b>K-6 Education</b></u> Math Blaster™ 6-9 The Way Things Work Ultimate Creativity & Writing Center™ Eyewitness Children's Encyclopedia Freddi Fish 2: The Case of the Haunted Schoolhouse™
<u><b>7-12 Education</b></u> Math Blaster™ Algebra Encyclopedia of Science 2.0 Student Writing Center™ Higher Score Guaranteed ACT/SAT/PSAT	<u><b>Entertainment</b></u> Don't Know Jack™ Volume 3 Sierra Sports™ Ski Racing OddWorld: Abe's Oddysee™ Total Annihilation™

# SATELLITE 2535CDS Product Specifications

<b>MODEL</b>	<b>2535CDS/4.3 billion bytes</b>	
<b>PART NUMBER</b>	<b>PAS251U-S6CW8</b>	
<b>SECURITY</b>	Hardware	Cable Lock slot, PC Card lock slot, main HDD (by screw only), screen blank, keyboard lock
	Password	Power-on, Supervisor, & HDD password (both drives)
<b>WARRANTY</b>	1 YR Parts / 1 YR. Labor / 1 YR. Battery	
<b>ENVIRONMENTAL SPECIFICATIONS</b>	<b><u>Operating</u></b>	<b><u>Non-operating</u></b>
Temperature:	41°F (5°C) to 95°F (35°C)	-4°F (-20°C) to 149°F (65°C)
Thermal Gradient: 20° C per hour (max.)	N/A	N/A
Relative Humidity:	20% to 80% non-condensing	10% to 90% non-condensing
Altitude:	-197 to 9,843ft. (-60 to 3000m)	-197 to 32,808ft. (-60 to 10,000m)
Shock:	10G	60G
Vibration:	0.5G	1G