

# TECRA 730CDT Product Specifications

**730CDT**  
2.1 Billion Bytes: PA1228U-T2C

---

## PROCESSOR

Intel Pentium® 150Mhz (3.1v/3.3v) w/VRT	Yes
External data bus width	64 bit
External data/address bus speed	60 MHz
Integrated Coprocessor	Yes
Processor Cache	16KB: (8KB code; 8KB data)

---

## LEVEL 2 (L2) CACHE

Data Bus Width	64 bit
Data Bus Speed	60 MHz
DATA RAM:	Yes
1 Mbit Pipelined Burst Synchronous SRAM	(32K x 32bit, 3.3V) x 2
Access Time	8 ns
TAG-RAM:	Yes
256Kbit Asynchronous SRAM	(32K x 8bit, 3.3V) x 1
Access Time	14ns

---

## PCI BUS SYSTEM ARCHITECTURE

Yes: 32-bit, 30 MHz

---

## MEMORY: 16Mbit EDO DRAM, 3.3V

Standard	16 MB
Maximum	144 MB
Speed	60ns
Hyper Page mode memory access	Yes
Data width	64 bit
BIOS (256KB FLASH EPROM, 120ns, 5V)	Yes
PnP 1.0a SUPPORT	Yes

---

## DISPLAY

Type	TFT Active Matrix Color
Size	12.1" (9.68"W x 7.26"H)
Dot Pitch	.24mm x .24mm
Contrast Ratio	100:1 (min)

---

## VIDEO

Memory: 4Mbit EDO DRAM, 5V	2 MB
Speed	50ns
Hyper Page mode support	Yes
Controller Chip	C&T HIQV32 (CT65550)
PCI Bus Architecture w/burst mode	Yes: 32-bit, 30 MHz
Graphics Accelerator:	Yes
64-bit BitBLT, LINEdraw, H/W Cursor	Yes
Video Accelerator:	Yes
YUV-to-RGB color space conversion	Yes
Scaling Support	Yes
Zoomed Video Port Support	Yes
DirectVideo support	Yes:w/Game SDK driver fr/Microsoft
Color Palette	16.7M colors
Internal Resolution <sup>1</sup>	1024 x 768 x 64K/64K colors
Smaller Image	640 x 480 x 64K/64K colors
Smaller Image	800 x 600 x 64K/64K colors
Virtual Display Mode	N/A
Virtual Display Mode	1280 x 1024 x 256/256K colors
External Resolution	<u>Colors/Palette</u>
640 x 480	16.7M colors/16.7M colors
800 x 600	16.7M colors/16.7M colors
1024 x 768	64K colors/64K
1280 x 1024	256 colors/256K
Refresh Rate	Vert.: 60Hz; Hor.: 48.5kHz (taken.@ 1024x768/64K colors Non-Interlaced)

# TECRA 730CDT Product Specifications

730CDT (con.)

2.1 Billion Bytes: PA1228U-T2C

---

## STORAGE

Removeable HDD (2.5" Enhanced IDE) 2.1 Billion Bytes=2.02GB (13msec)

---

## SELECT BAY DEVICES

Modular FDD (3.5" 1.44MB)	Included/Swappable with CD-ROM
FDD Dimensions	4.57"L x 3.8"W x .59"H
FDD Weight	Weight: .29 lbs
Simultaneous FDD & CD-ROM Support	Yes: External FDD adapter included
FDD Adapter Dimensions	7.0"L x 5.5"W
FDD Adapter Weight	.25 lbs

### Modular CD-ROM: Toshiba XM-1402B

5.25" 6x-speed	<i>Installed/Swappable with FDD</i>
Interface	.ATAPI (Enhanced IDE)
Random Access Time	190 ms
Sustained Transfer Rate	1,026 KB/sec
Supported Disc formats	CD-DA, CD-ROM, CD-ROM XA, CD-Bridge (Photo-CD, Video-CD), CD-I, CD-I Ready, CD-G, Multisession (Photo-CD, CD-Plus)

---

## KEYBOARD

82 keys, 3mm Travel	Yes
12 dedicated function keys	Yes
Cursor control (8 Keys, Inverted "T")	Yes
Numeric keypad (Integrated Overlay)	Yes

---

**Integrated Pointing Device** AccuPoint™

---

## EXPANSION SLOTS

Two Stacked PC Card Slot <sup>2</sup>	Yes: CardBus & ZV Card Ready
32-bit, 3.3V PC CardBus Support	Yes
16-bit, 5.0V PC Card Support	Yes
Internal Memory Slot (One only)	Yes

---

## EXPANSION PORTS

One RJ-11 port for internal modem (supplied)	Yes
One 9-Pin Serial (16550 UART compliant)	Yes
One 25-Pin Parallel (8 bit ECP)	Yes
One 15-Pin RGB (SVGA video)	Yes
Serial Infrared port (back only)	Yes: IrDA 115.2Kbps compatible
One (PS/2) 101 Keyboard/Mouse port	Yes
One External Floppy Drive port	Yes
Microphone (3.5mm mini jack, monoaural)	Yes
Headphone (3.5mm mini jack, stereo)	Yes: (16 Ω min)
Line-in (3.5mm mini jack, stereo, 2V rms)	Yes
Line-out (3.5mm mini jack, stereo, 0.7V rms)	Yes
Noteworthy security lock port	Yes

---

## INTERNAL MODEM (All Models)

28.8 /14.4 Kbps Data/Fax modem

Data support	
Protocols supported	Bell-103/212A, CCITT-V.21/V.22, V.22bis, V.23, VV.32, V.32bis, V.32 terbo, V.34
Error correction	MNP 1-4
Data compression	MNP 5, CCITT V.42 bis
Fax support	
Protocols supported	V.21 ch2, V.27 ter, V.29, V.17
Fax class	1
Supported Functions	Speaker phone, Telephony Answering Machine, Ring Wake-up Resume Incoming Call Discrimination, Caller ID

<sup>2</sup> Holds two - 5mm PC Cards Type II or one - 10.5mm PC Card Type III.

# TECRA 730CDT Product Specifications

## 730CDT (con.)

2.1 Billion Bytes: PA1228U-T2C

<b>NoteDock II™ Port Replicator (Optional)</b>	Part# PA2713U (for Tecra 500Series, 710CDT, 720CDT, & 730CDT)
Two Type III CardBus ready PC Card slots	Yes: each slot supports one card
Supported Interfaces	Serial, parallel, PS/2 keyboard, PS/2 mouse, DC in, SVGA monitor, lock slot, joystick/MIDI, audio line-in, line-out, headphone, microphone

<b>Desk Station V Plus (Optional)</b>	Part# PA2710U
(2) Full length 32-bit PCI/16-bit ISA slots	Yes
(1) Half Length 32-bit PCI slot	Yes
(2) Type III PC Card slots	Yes
Built-in SCSI II	Yes
5.25" half height drive bay	Yes
Select Bay for Modular FDD or CD-ROM	Yes
Designed for Windows 95 and PNP	Yes
Hot Docking Support	Yes

## POWER

<b>Autosensing External AC Adapter: NW2484U</b>	5.51"L x 2.95"W x .98" --- .75 lbs.
Input (Voltage/Frequency)	100-240V; 50-60Hz
Output (Voltage/Amps)	15 VDC; 2.7A (max)
Power Output (Watts)	40W
Battery Type: Li-Ion (10.8V, 5600mAH)	Yes: Part# PA2485UR
Battery Life: (Full Power/Low Power)	2.75 hrs. - 3.5 hrs.
Recharge Time (Computer Off/On)	4 hrs.(Off) /4.5-11 hrs.(On)
MaxTime® Power Management	Yes

## SOUND SYSTEM (All Models)

Chipsets:	Crystal Semiconductor CS4232, Yamaha OPL3 (YMF262), Yamaha D/A converter (YAC512)
16 bit stereo audio playback/record	Yes
Full duplex function	Yes
Sound formats supported:	SoundBlaster Pro™, .WAV, MIDI, Zoomed video port audio (stereo), CardBus audio (monaural), CD-ROM audio
DirectSound support	Yes: with Windows 95 Game SDK driver from Microsoft
Speaker system:	Two top-mounted stereo speakers (28mm, 8 Ω)

## DIMENSIONS

11.7"W x 9.0"D x 2.3"H

## WEIGHT (includes 1.32 lbs. battery)

8.2 LBS.

## BUNDLED SOFTWARE (All Models)

*User selectable* Windows 95 *or* Windows for Workgroups 3.11 and MS-DOS 6.22® w/Special Enhancements; Intel Indeo Video™; Synchro multimedia connect Communications utilities; Sony Music Screeners™; Mediamatics MPEG Arcade Player, Netscape Navigator™ Personal Edition, magiCDisc™, Dow Jones Personal Journal, Fn-esse™, Hypertext online documentation

## SECURITY (All Models)

Lock slot, power-on, supervisor, HDD access, & Desk Station Eject password

## WARRANTY

3 YR Parts & Labor

## ENVIRONMENTAL SPECIFICATIONS

	Operating	Non-operating
Temperature:	41°F (5°C) to 95°F (35°C)	-4°F (-20°C) to 149°F (65°C)
Thermal Gradient: 20° C per hour (max.)	N/A	
Relative Humidity:	20% to 80% non-condensing	10% to 90% non-condensing
Altitude:	-197 to 9,843ft. (-60 to 3000m)	-197 to 32,808ft. (-60 to 10,000m)
Shock:	10G; 1.5G w/CD-ROM installed	60G; 50G w/CD-ROM installed
Vibration:	0.5G; 0.25G w/CD-ROM installed	1G; 1G w/CD-ROM installed